

Printing date 03/27/2019 Version Number 3 Reviewed on 03/23/2019

1 Identification

· Product identifier

· Trade name: Aromatics / Alkenes Standard (1X1 mL)

· Part number: DWM-503-1

· Application of the substance / the mixture Reagents and Standards for Analytical Chemical Laboratory Use

· Details of the supplier of the safety data sheet

· Manufacturer/Supplier:

Agilent Technologies, Inc. 5301 Stevens Creek Blvd. Santa Clara, CA 95051 USA

· Information department:

Telephone: 800-227-9770

e-mail: pdl-msds author@agilent.com

· Emergency telephone number: CHEMTREC®: 1-800-424-9300

2 Hazard(s) identification

· Classification of the substance or mixture



GHS02 Flame

Flam. Liq. 2 H225 Highly flammable liquid and vapor.



GHS06 Skull and crossbones

Acute Tox. 3 H331 Toxic if inhaled.



GHS08 Health hazard

Muta. 1B H340 May cause genetic defects.

Carc. 1A H350 May cause cancer.

Repr. 2 H361 Suspected of damaging fertility or the unborn child.

STOT SE 1 $\,$ H370 Causes damage to organs.



GHS07

Skin Sens. 1 H317 May cause an allergic skin reaction.

- · Label elements
- · GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS).
- · Hazard pictograms









GHS02

GHS06

GHS07

CHSU8



Printing date 03/27/2019 Reviewed on 03/23/2019 Version Number 3

Trade name: Aromatics / Alkenes Standard (1X1 mL)

(Contd. of page 1)

· Signal word Danger

· Hazard-determining components of labeling:

methanol

benzene

tetrachloroethylene

trichloroethylene

· Hazard statements

Highly flammable liquid and vapor.

Toxic if inhaled.

May cause an allergic skin reaction.

May cause genetic defects.

May cause cancer.

Suspected of damaging fertility or the unborn child.

Causes damage to organs.

· Precautionary statements

Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood.

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

Ground/bond container and receiving equipment.

Use explosion-proof electrical/ventilating/lighting/equipment.

Use only non-sparking tools.

Take precautionary measures against static discharge.

Do not breathe dust/fume/gas/mist/vapors/spray.

Wash thoroughly after handling.

Do not eat, drink or smoke when using this product.

Use only outdoors or in a well-ventilated area.

Contaminated work clothing must not be allowed out of the workplace.

Wear protective gloves/protective clothing/eye protection/face protection.

If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

IF exposed or concerned: Get medical advice/attention.

Specific treatment (see on this label).

If skin irritation or rash occurs: Get medical advice/attention.

Wash contaminated clothing before reuse.

In case of fire: Use for extinction: CO2, powder or water spray.

Store in a well-ventilated place. Keep container tightly closed.

Store in a well-ventilated place. Keep cool.

Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

· Classification system:

· NFPA ratings (scale 0 - 4)



Health = 1Fire = 3

Reactivity = 0

· HMIS-ratings (scale 0 - 4)



Health = *1

Fire = 3



Printing date 03/27/2019 Version Number 3 Reviewed on 03/23/2019

Trade name: Aromatics / Alkenes Standard (1X1 mL)

(Contd. of page 2)

- · Other hazards
- · Results of PBT and vPvB assessment

· PBT:	
87-68-3	hexachlorobuta-1,3-diene
87-61-6	1,2,3-trichlorobenzene
120-82-1	1,2,4-trichlorobenzene
· vPvB:	
87-68-3 1	hexachlorobuta-1,3-diene

3 Composition/information on ingredients

- · Chemical characterization: Mixtures
- · Description: Mixture of the substances listed below with nonhazardous additions.

· Dangeroi	us components:	
67-56-1	methanol	96.461%
106-46-7	1,4-dichlorobenzene	0.126%
87-68-3	hexachlorobuta-1,3-diene	0.126%
87-61-6	1,2,3-trichlorobenzene	0.126%
120-82-1	1,2,4-trichlorobenzene	0.126%
	naphthalene	0.126%
127-18-4	tetrachloroethylene	0.126%
	propylbenzene	0.126%
71-43-2	benzene	0.126%
108-88-3	toluene	0.126%
100-41-4	ethylbenzene	0.126%
98-82-8		0.126%
100-42-5		0.126%
79-01-6	trichloroethylene	0.126%

4 First-aid measures

- · Description of first aid measures
- · General information:

Immediately remove any clothing soiled by the product.

Remove breathing apparatus only after contaminated clothing have been completely removed.

In case of irregular breathing or respiratory arrest provide artificial respiration.

· After inhalation:

Supply fresh air or oxygen; call for doctor.

In case of unconsciousness place patient stably in side position for transportation.

- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eye contact: Rinse opened eye for several minutes under running water. Then consult a doctor.
- · After swallowing: If symptoms persist consult doctor.
- · Information for doctor:
- · Most important symptoms and effects, both acute and delayed No further relevant information available.

(Contd. on page 4)



Printing date 03/27/2019 Version Number 3 Reviewed on 03/23/2019

Trade name: Aromatics / Alkenes Standard (1X1 mL)

(Contd. of page 3)

Indication of any immediate medical attention and special treatment needed

No further relevant information available.

5 Fire-fighting measures

- · Extinguishing media
- · Suitable extinguishing agents:

CO2, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

- · For safety reasons unsuitable extinguishing agents: Water with full jet
- \cdot Special hazards arising from the substance or mixture

During heating or in case of fire poisonous gases are produced.

- · Advice for firefighters
- · Protective equipment: Mouth respiratory protective device.

6 Accidental release measures

· Personal precautions, protective equipment and emergency procedures

Mount respiratory protective device.

Wear protective equipment. Keep unprotected persons away.

- Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- · Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

· Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

· Protective Action Criteria for Chemicals

67-56-1	methanol	530 ppm
104-51-8	butylbenzene	3.6 ppm
135-98-8	2-Phenylbutane	1.2 ppm
98-06-6	tert-butylbenzene	1.7 ppm
95-49-8	2-chlorotoluene	75 ppm
106-43-4	4-chlorotoluene	1.2 ppm
99-87-6	p-cymene	120 mg/m
95-50-1	1,2-dichlorobenzene	50 ppm
541-73-1	1,3-dichlorobenzene	6 ppm
106-46-7	1,4-dichlorobenzene	30 ppm
87-68-3	hexachlorobuta-1,3-diene	1 ppm
87-61-6	1,2,3-trichlorobenzene	15 mg/m ³
120-82-1	1,2,4-trichlorobenzene	0.45 ppm
108-38-3	m-xylene	130 ppm
91-20-3	naphthalene	15 ppm



Printing date 03/27/2019 Version Number 3 Reviewed on 03/23/2019

		(Contd. of pa
	etrachloroethylene	35 ppm
1-	propylbenzene	3.7 ppm
71-43-2 t		52 ppm
108-88-3 t	oluene	67 ppm
	thylbenzene	33 ppm
98-82-8		50 ppm
108-67-8 r	•	140 ppn
100-42-5 s	tyrene	20 ppm
95-63-6	,2,4-trimethylbenzene	140 ppn
79-01-6 t	richloroethylene	130 ppn
108-90-7 c	hlorobenzene	10 ppm
108-86-1 l	oromobenzene	0.96 ррг
· PAC-2:		
67-56-1 r	nethanol	2,100 ppn
	outylbenzene	40 ppm
135-98-8 2	-Phenylbutane	13 ppm
98-06-6 t	ert-butylbenzene	18 ppm
95-49-8 2	-chlorotoluene	310 ppm
106-43-4	-chlorotoluene	13 ppm
99-87-6 p	-cymene	1,300 mg/
95-50-1	,2-dichlorobenzene	170 ppm
541-73-1	,3-dichlorobenzene	66 ppm
106-46-7	,4-dichlorobenzene	170 ppm
87-68-3 l	exachlorobuta-1,3-diene	3 ppm
87-61-6	,2,3-trichlorobenzene	60 mg/m ³
120-82-1	,2,4-trichlorobenzene	5 ppm
108-38-3 r	n-xylene	920 ppm
91-20-3 r	aphthalene	83 ppm
127-18-4 t	etrachloroethylene	230 ppm
103-65-1 p	propylbenzene	41 ppm
71-43-2 l	enzene	800 ppm
108-88-3 t	oluene	560 ppm
	thylbenzene	1100* ppi
98-82-8	•	300 ppm
108-67-8 r	nesitylene	360 ppm
100-42-5 s	•	130 ppm
	,2,4-trimethylbenzene	360 ppm
	richloroethylene	450 ppm
	hlorobenzene	150 ppm
	oromobenzene	11 ppm
		(Contd. on pa



Printing date 03/27/2019 Version Number 3 Reviewed on 03/23/2019

Trade name: Aromatics / Alkenes Standard (1X1 mL)

		(Contd. of page
PAC-3:		
	methanol	7200* ppm
104-51-8	butylbenzene	240 ppm
	2-Phenylbutane	81 ppm
98-06-6	tert-butylbenzene	110 ppm
95-49-8	2-chlorotoluene	1,800 ppm
106-43-4	4-chlorotoluene	80 ppm
99-87-6	p-cymene	1,900 mg/m
95-50-1	1,2-dichlorobenzene	1,000 ppm
541-73-1	1,3-dichlorobenzene	400 ppm
106-46-7	1,4-dichlorobenzene	1,000 ppm
87-68-3	hexachlorobuta-1,3-diene	10 ppm
87-61-6	1,2,3-trichlorobenzene	360 mg/m ³
120-82-1	1,2,4-trichlorobenzene	20 ppm
108-38-3	m-xylene	2500* ppm
91-20-3	naphthalene	500 ppm
127-18-4	tetrachloroethylene	1,200 ppm
103-65-1	propylbenzene	240 ppm
71-43-2	benzene	4000* ppm
108-88-3	toluene	3700* ppm
100-41-4	ethylbenzene	1800* ppm
98-82-8	cumene	730 ppm
108-67-8	mesitylene	480 ppm
100-42-5	styrene	1100* ppm
95-63-6	1,2,4-trimethylbenzene	480 ppm
79-01-6	trichloroethylene	3,800 ppm
108-90-7	chlorobenzene	400 ppm
108-86-1	bromobenzene	240 ppm

7 Handling and storage

- · Handling:
- · Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Open and handle receptacle with care.

Prevent formation of aerosols.

· Information about protection against explosions and fires:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

Keep respiratory protective device available.

- · Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles: Store in a cool location.

(Contd. on page 7)



Printing date 03/27/2019 Reviewed on 03/23/2019 Version Number 3

Trade name: Aromatics / Alkenes Standard (1X1 mL)

(Contd. of page 6)

- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions:

Keep receptacle tightly sealed.

Store in cool, dry conditions in well sealed receptacles.

· Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

· Addi	ional information about design of technical systems: No further data; see item 7.
· Cont	rol parameters
· Comj	oonents with limit values that require monitoring at the workplace:
67-56	-1 methanol
PEL	Long-term value: 260 mg/m³, 200 ppm
REL	Short-term value: 325 mg/m³, 250 ppm
	Long-term value: 260 mg/m³, 200 ppm
	Skin
TLV	Short-term value: 328 mg/m³, 250 ppm
	Long-term value: 262 mg/m³, 200 ppm Skin; BEI
106-4	6-7 1,4-dichlorobenzene
	Long-term value: 450 mg/m³, 75 ppm
REL	See Pocket Guide App. A
TLV	Long-term value: 60 mg/m³, 10 ppm
87-68	-3 hexachlorobuta-1,3-diene
REL	Long-term value: 0.24 mg/m³, 0.02 ppm
	Skin; See Pocket Guide App. A
TLV	Long-term value: 0.21 mg/m³, 0.02 ppm Skin
120-8	2-1 1,2,4-trichlorobenzene
	Ceiling limit value: 40 mg/m³, 5 ppm
	Ceiling limit value: 37 mg/m³, 5 ppm
	-3 naphthalene
	Long-term value: 50 mg/m³, 10 ppm
	Short-term value: 75 mg/m³, 15 ppm
	Long-term value: 50 mg/m³, 10 ppm
TLV	Long-term value: 52 mg/m³, 10 ppm
	Skin; BEI
	8-4 tetrachloroethylene
PEL	Long-term value: 100 ppm
	Ceiling limit value: 200; 300* ppm *5-min peak in any 3 hrs
RFI	Minimize workplace exp. concs.;Pocket Guide App. A
	Short-term value: 685 mg/m³, 100 ppm
ILV	Long-term value: 170 mg/m³, 25 ppm
	BEI

(Contd. on page 8)



Printing date 03/27/2019 Version Number 3 Reviewed on 03/23/2019

71 43	3-2 benzene	(Contd. of p
PEL	Short-term value: 15* mg/m³, 5* ppm Long-term value: 3* mg/m³, 1* ppm	
	*table Z-2 for exclusions in 29CFR1910.1028(d)	
RFI	Short-term value: 1 ppm	
KLL	Long-term value: 0.1 ppm	
	See Pocket Guide App. A	
TLV	Short-term value: 8 mg/m³, 2.5 ppm	
	Long-term value: 1.6 mg/m ³ , 0.5 ppm	
	Skin; BEI	
108-8	88-3 toluene	
PEL	Long-term value: 200 ppm	
	Ceiling limit value: 300; 500* ppm	
	*10-min peak per 8-hr shift	
REL	Short-term value: 560 mg/m³, 150 ppm	
	Long-term value: 375 mg/m³, 100 ppm	
TLV	Long-term value: 75 mg/m³, 20 ppm	
	BEI	
	41-4 ethylbenzene	
	Long-term value: 435 mg/m³, 100 ppm	
REL	Short-term value: 545 mg/m³, 125 ppm	
	Long-term value: 435 mg/m³, 100 ppm	
TLV	Long-term value: 87 mg/m³, 20 ppm BEI	
98-82	2-8 cumene	
PEL	Long-term value: 245 mg/m³, 50 ppm Skin	
REL	Long-term value: 245 mg/m³, 50 ppm Skin	
TLV	Long-term value: (246) NIC-0.5 mg/m³, (50) NIC-0.1 ppm	
	NIC-A3	
	42-5 styrene	
PEL	Long-term value: 100 ppm	
	Ceiling limit value: 200; 600* ppm *5-min peak in any 3 hrs	
DEL	· · · · · · · · · · · · · · · · · · ·	
KEL	Short-term value: 425 mg/m³, 100 ppm Long-term value: 215 mg/m³, 50 ppm	
TT 3.7	1 - 2	
ILV	Short-term value: (170) mg/m³, (40) ppm Long-term value: (85) NIC-8.5 mg/m³, (20) NIC-2 ppm	
	BEI, NIC-A3, NIC-OTO	
79-0 1	1-6 trichloroethylene	
PEL	Long-term value: 100 ppm	
	Ceiling limit value: 200; 300* ppm	
	*5-min peak in any 2 hrs	



Printing date 03/27/2019 Version Number 3 Reviewed on 03/23/2019

Trade name: Aromatics / Alkenes Standard (1X1 mL)

(Contd. of page 8)

REL See Pocket Guide Apps. A and C
TLV Short-term value: 135 mg/m³, 25 ppm
Long-term value: 54 mg/m³, 10 ppm

BEI

· Ingredients with biological limit values:

67-56-1 methanol

BEI 15 mg/L

Medium: urine Time: end of shift

Parameter: Methanol (background, nonspecific)

127-18-4 tetrachloroethylene

BEI 3 ppm

Medium: end-exhaled air Time: prior to shift

Parameter: Tetrachloroethylene

0.5 mg/L Medium: blood Time: prior to shift

Parameter: Tetrachloroethylene

71-43-2 benzene

BEI 25 μg/g creatinine

Medium: urine

Time: end of shift Parameter

Parameter: S-Phenylmercapturic acid (background

500 μg/g creatinine Medium: urine Time: end of shift

Parameter: t,t-Muconic acid (background)

108-88-3 toluene

BEI 0.02 mg/L

Medium: blood

Time: prior to last shift of workweek

Parameter: Toluene

0.03 mg/L Medium: urine Time: end of shift Parameter: Toluene

0.3 mg/g creatinine Medium: urine Time: end of shift

Parameter: o-Cresol with hydrolysis (background)

(Contd. on page 10)



Printing date 03/27/2019 Version Number 3 Reviewed on 03/23/2019

Trade name: Aromatics / Alkenes Standard (1X1 mL)

(Contd. of page 9)

100-41-4 ethylbenzene

BEI 0.7 g/g creatinine

Medium: urine

Time: end of shift at end of workweek

Parameter: Sum of mandelic acid and phenylglyoxylic acid (nonspecific, semi-quantitative)

-

Medium: end-exhaled air Time: not critical

Parameter: Ethyl benzene (semi-quantitative)

100-42-5 styrene

BEI 400 mg/g creatinine

Medium: urine Time: end of shift

Parameter: Mandelic acid plus phenylglyoxylic acid (nonspecific)

0.2 mg/L

Medium: venous blood Time: end of shift

Parameter: Styrene (semi-quantitative)

79-01-6 trichloroethylene

BEI 15 mg/L

Medium: urine

Time: end of shift at end of workweek Parameter: Trichloroacetic acid (nonspecific)

0.5 mg/L Medium: blood

Time: end of shift at end of workweek

Parameter: Trichloroethanol without hydrolysis (nonspecific)

-

Medium: blood

Time: end of shift at end of workweek

Parameter: Trichloroethylene (semi-quantitative)

-

Medium: end-exhaled air

Time: end of shift at end of workweek

Parameter: Trichloroethylene (semi-quantitative)

- Additional information: The lists that were valid during the creation were used as basis.
- · Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Store protective clothing separately.

· Breathing equipment:

When used as intended with Agilent instruments, the use of the product under normal laboratory conditions and with standard practices does not result in significant airborne exposures and therefore respiratory protection is not

(Contd. on page 11)



Printing date 03/27/2019 Version Number 3 Reviewed on 03/23/2019

Trade name: Aromatics / Alkenes Standard (1X1 mL)

(Contd. of page 10)

needed.

Under an emergency condition where a respirator is deemed necessary, use a NIOSH or equivalent approved device/equipment with appropriate organic or acid gas cartridge.

· Protection of hands:

Although not recommended for constant contact with the chemicals or for clean-up, nitrile gloves 11-13 mil thickness are recommended for normal use. The breakthrough time is 1 hr. For cleaning a spill where there is direct contact of the chemical, butyl rubber gloves are recommended 12-15 mil thickness with breakthrough times exceeding 4 hrs. Supplier recommendations should be followed.

· Material of gloves

For normal use: nitrile rubber, 11-13 mil thickness

For direct contact with the chemical: butyl rubber, 12-15 mil thickness

· Penetration time of glove material

For normal use: nitrile rubber: 1 hour

For direct contact with the chemical: butyl rubber: >4 hours

· Eye protection:



Tightly sealed goggles

0 DI . 1			
9 Physical	and	chemica	l properties
		,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,	

· Information on basic physical and cl	hemical properties
· Appearance:	
Form:	Fluid
Color:	Colorless
· Odor:	Alcohol-like
· Odor threshold:	Not determined.
· pH-value:	Not determined.
· Change in condition	
Melting point/Melting range:	-98 °C (-144.4 °F)
Boiling point/Boiling range:	64 °C (147.2 °F)
· Flash point:	9 °C (48.2 °F)
· Flammability (solid, gaseous):	Not applicable.
· Ignition temperature:	455 °C (851 °F)
· Decomposition temperature:	Not determined.
· Auto igniting:	Product is not selfigniting.
· Danger of explosion:	Product is not explosive. However, formation of explosive air/vapor mixtures are possible.
· Explosion limits:	
Lower:	5.5 Vol %
Upper:	44 Vol %
· Vapor pressure at 20 °C (68 °F):	100 hPa (75 mm Hg)

(Contd. on page 12)



Printing date 03/27/2019 Version Number 3 Reviewed on 03/23/2019

Trade name: Aromatics / Alkenes Standard (1X1 mL)

(Contd. of page 11)

		(Contd. of page 11)
· Density at 20 °C (68 °F):	0.81052 g/cm³ (6.76379 lbs/gal)	
· Relative density	Not determined.	
· Vapor density	Not determined.	
Evaporation rate	Not determined.	
· Solubility in / Miscibility with		
Water:	Not miscible or difficult to mix.	
· Partition coefficient (n-octanol/wa	ter): Not determined.	
· Viscosity:		
Dynamic:	Not determined.	
Kinematic:	Not determined.	
· Solvent content:		
Organic solvents:	98.7 %	
VOC content:	98.61 %	
	799.3 g/l / 6.67 lb/gal	
Solids content:	0.4 %	
· Other information	No further relevant information available.	

10 Stability and reactivity

- · Reactivity No further relevant information available.
- · Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

11 Toxicological information

- · Information on toxicological effects

٠,	· Acute toxicity:		
•]	· LD/LC50 values that are relevant for classification:		
1	ATE (Acu	te Toxicity	y Estimate)
(Oral	LD50	64,873 mg/kg (rat)
]	Dermal	LD50	25,659 mg/kg
]	Inhalative	LC50/4 h	3.11 mg/L
	67-56-1 methanol		
(Oral	LD50	5,628 mg/kg (rat)
]	Dermal	LD50	15,800 mg/kg (rabbit)
9	95-50-1 1,	2-dichloro	benzene
(Oral	LD50	500 mg/kg (rat)
]	Dermal	LD50	>10,000 mg/kg (rabbit)

(Contd. on page 13)



Printing date 03/27/2019 Version Number 3 Reviewed on 03/23/2019

106-46-7	,4-dichlor	obenzene	(Contd. of page
Oral	LD50	>2,000 mg/kg (rat)	
Dermal	LD50	>2,000 mg/kg (rat)	
		>5.07 mg/L (rat)	
		uta-1,3-diene	
Oral	LD50	82 mg/kg (rat)	
Dermal	LD50	100 mg/kg (rabbit)	
		370 mg/L (mouse)	
87-61-6 1,			
Oral	LD50	1,830 mg/kg (rat)	
120-82-1	,2,4-trichl	orobenzene	
Oral	LD50	756 mg/kg (rat)	
Dermal	LD50	6,139 mg/kg (rat)	
91-20-3 na	aphthalene		
Oral	LD50	490 mg/kg (rat)	
Dermal	LD50	5,000 mg/kg (rat)	
		20,000 mg/kg (rabbit)	
127-18-4 t	etrachloro	ethylene	
Oral	LD50	2,629 mg/kg (rat)	
Inhalative	LC50/4 h	4,000 mg/L (rat)	
103-65-1	propylbenz	ene	
Oral	LD50	6,040 mg/kg (rat)	
71-43-2 be	enzene		
Oral	LD50	3,340 mg/kg (rat)	
Dermal	LD50	48 mg/kg (mouse)	
		>8,260 mg/kg (rabbit)	
Inhalative	LC50/4 h	9,980 mg/L (mouse)	
108-88-3 t	oluene		
Oral	LD50	5,580 mg/kg (rat)	
Dermal	LD50	12,124 mg/kg (rabbit)	
Inhalative	LC50/4 h	5,320 mg/L (mouse)	
		28.1 mg/L (rat)	
100-41-4	ethylbenze	ne	
Oral	LD50	3,500 mg/kg (rat)	
Dermal	LD50	15,354 mg/kg (rabbit)	
Inhalative		17.2 mg/L (rat)	
98-82-8 cı			
Oral	LD50	1,400 mg/kg (rat)	
Dermal	LD50	>3,160 mg/kg (rabbit)	
Inhalative	LC50/4 h	24.7 mg/L (mouse)	



Printing date 03/27/2019 Version Number 3 Reviewed on 03/23/2019

Trade name: Aromatics / Alkenes Standard (1X1 mL)

(Contd. of page 13) 100-42-5 styrene Oral LD50 5,000 mg/kg (rat) Dermal LD50 >2,000 mg/kg (rat) Inhalative LC50/4 h 11.8 mg/L (rat) 79-01-6 trichloroethylene LD50 Oral 2,402 mg/kg (mouse) 4,290 mg/kg (rat) 8,450 mg/kg (mouse) LD50 Dermal

- · Primary irritant effect:
- on the skin: No irritant effect.
- · on the eye: No irritating effect.
- · Sensitization: Sensitization possible through skin contact.
- · Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations:

Toxic Irritant

The product can cause inheritable damage.

· Carcinogenic categories

LADGE	,	
	nternational Agency for Research on Cancer)	
	1,2-dichlorobenzene	3
541-73-1	1,3-dichlorobenzene	3
	1,4-dichlorobenzene	2B
87-68-3	hexachlorobuta-1,3-diene	3
95-47-6	o-xylene	3
108-38-3	m-xylene	3
106-42-3	p-xylene	3
91-20-3	naphthalene	2B
127-18-4	tetrachloroethylene	2A
71-43-2	benzene	1
108-88-3	toluene	3
100-41-4	ethylbenzene	2B
98-82-8	cumene	2B
100-42-5	styrene	2B
79-01-6	trichloroethylene	1
· NTP (Na	tional Toxicology Program)	
106-46-7	1,4-dichlorobenzene	R
91-20-3	naphthalene	R
127-18-4	tetrachloroethylene	R
71-43-2	benzene	K
98-82-8	cumene	R
100-42-5	styrene	R
79-01-6	trichloroethylene	K
	I .	(Contd. on page 15)



Printing date 03/27/2019 Version Number 3 Reviewed on 03/23/2019

Trade name: Aromatics / Alkenes Standard (1X1 mL)

(Contd. of page 14)

· OSHA-Ca (Occupational Safety & Health Administration)

71-43-2 benzene

12 Ecological information

- · Toxicity
- · Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.
- · Additional ecological information:
- · General notes:

Water hazard class 3 (Self-assessment): extremely hazardous for water

Do not allow product to reach ground water, water course or sewage system, even in small quantities.

Danger to drinking water if even extremely small quantities leak into the ground.

· Results of PBT and vPvB assessment

· PBT:			
87-68-3	hexachlorobuta-1,3-diene		
87-61-6	1,2,3-trichlorobenzene		
120-82-1	1,2,4-trichlorobenzene		
· vPvB:	· vPvB:		
87-68-3 hexachlorobuta-1,3-diene			

[•] Other adverse effects No further relevant information available.

13 Disposal considerations

- · Waste treatment methods
- · Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packagings:
- · Recommendation: Disposal must be made according to official regulations.

4 4 7	٦ .		p .	
4.	ransnor	m	ormai	TON

· Not Regulated, De minimus Quantities	-
· UN-Number · DOT, IMDG, IATA	UN1230
· UN proper shipping name· DOT· IMDG, IATA	Methanol solution METHANOL solution

(Contd. on page 16)



Printing date 03/27/2019 Version Number 3 Reviewed on 03/23/2019

Trade name: Aromatics / Alkenes Standard (1X1 mL)

· Limited quantities (LQ)

· Excepted quantities (EQ)

(Contd. of page 15) · Transport hazard class(es) · DOT 3 Flammable liquids · Class ·Label 3, 6.1 ·IMDG 3 Flammable liquids · Class ·Label 3/6.1 \cdot IATA 3 Flammable liquids · Class ·Label 3(6.1)· Packing group · DOT, IMDG, IATA II · Environmental hazards: Not applicable. Warning: Flammable liquids · Special precautions for user · Danger code (Kemler): 336 · EMS Number: F-E,S-D · Stowage Category · Stowage Code SW2 Clear of living quarters. · Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code Not applicable. · Transport/Additional information: \cdot **DOT** · Quantity limitations On passenger aircraft/rail: 1 L On cargo aircraft only: 60 L · IMDG

> 1L Code: E2

Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml

(Contd. on page 17)



Printing date 03/27/2019 Version Number 3 Reviewed on 03/23/2019

Trade name: Aromatics / Alkenes Standard (1X1 mL)

(Contd. of page 16)

· UN "Model Regulation": UN 1230 METHANOL SOLUTION, 3 (6.1), II

15 Regulatory information

- Safety, health and environmental regulations/legislation specific for the substance or mixture
- ·Sara

· Section 355	(ovtromoly	hozordouc	cubetanos).
Section 333	(exti eiiieiy	nazai uous	substances).

None of the ingredients is listed.

· Section 313 (Specific toxic chemical listings):

67-56-1	methanol

- 95-50-1 1,2-dichlorobenzene
- 541-73-1 1,3-dichlorobenzene
- 106-46-7 1,4-dichlorobenzene
- 87-68-3 hexachlorobuta-1,3-diene
- 120-82-1 1,2,4-trichlorobenzene
- 95-47-6 o-xylene
- 108-38-3 m-xylene
- 106-42-3 p-xylene
- 91-20-3 naphthalene
- 127-18-4 tetrachloroethylene
- 71-43-2 benzene
- 108-88-3 toluene
- 100-41-4 ethylbenzene
 - 98-82-8 cumene
- 100-42-5 styrene
 - 95-63-6 1,2,4-trimethylbenzene
- 79-01-6 trichloroethylene
- 108-90-7 chlorobenzene

· TSCA (Toxic Substances Control Act):

All ingredients are listed.

· TSCA new (21st Century Act): (Substances not listed)

87-68-3 hexachlorobuta-1,3-diene

Proposition 65

· Chemicals known to cause cancer:

- 106-46-7 1,4-dichlorobenzene
- 87-68-3 hexachlorobuta-1,3-diene
- 91-20-3 naphthalene
- 127-18-4 tetrachloroethylene
 - 71-43-2 benzene
- 100-41-4 ethylbenzene

(Contd. on page 18)



Printing date 03/27/2019 Version Number 3 Reviewed on 03/23/2019

		(Contd. of page
98-82-8		
100-42-5	· ·	
79-01-6	trichloroethylene	
	s known to cause reproductive toxicity for females:	
None of tl	ne ingredients is listed.	
Chemical	s known to cause reproductive toxicity for males:	
71-43-2 b	enzene	
79-01-6 t	richloroethylene	
Chemical	s known to cause developmental toxicity:	
	methanol	
71-43-2	benzene	
108-88-3	toluene	
79-01-6	trichloroethylene	
Carcinog	enic categories	
_	vironmental Protection Agency)	
	1,2-dichlorobenzene	D
	1,3-dichlorobenzene	D
	hexachlorobuta-1,3-diene	C
120-82-1	1,2,4-trichlorobenzene	D
95-47-6	o-xylene	I
108-38-3	m-xylene	I
106-42-3	p-xylene	I
91-20-3	naphthalene	C, CI
127-18-4	tetrachloroethylene	L
71-43-2	benzene	A, K
108-88-3	toluene	II
100-41-4	ethylbenzene	D
98-82-8	cumene	D, Cl
	mesitylene	II
	1,2,4-trimethylbenzene	II
	trichloroethylene	СаН
	chlorobenzene	D
108-86-1	bromobenzene	II
TLV (Th	reshold Limit Value established by ACGIH)	
	1,2-dichlorobenzene	
	1,4-dichlorobenzene	
	hexachlorobuta-1,3-diene	
	o-xylene	
108-38-3	•	
106-42-3		
91-20-3	naphthalene	



Printing date 03/27/2019 Version Number 3 Reviewed on 03/23/2019

Trade name: Aromatics / Alkenes Standard (1X1 mL)

		(Contd. of page 18)
127-18-4	tetrachloroethylene	A3
71-43-2	benzene	A1
108-88-3	toluene	A4
100-41-4	ethylbenzene	A3
100-42-5		A4
79-01-6	trichloroethylene	A2
108-90-7	chlorobenzene	A3
· NIOSH-0	Ca (National Institute for Occupational Safety and Health)	
106-46-7	1,4-dichlorobenzene	
87-68-3	hexachlorobuta-1,3-diene	
127-18-4	tetrachloroethylene	
71-43-2	benzene	
79-01-6	trichloroethylene	

- · National regulations:
- $\cdot \ Additional \ classification \ according \ to \ Decree \ on \ Hazardous \ Materials:$

Carcinogenic hazardous material group III (dangerous).

· Information about limitation of use:

Workers are not allowed to be exposed to the hazardous carcinogenic materials contained in this preparation. Exceptions can be made by the authorities in certain cases.

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

The information contained in this document is based on Agilent's state of knowledge at the time of preparation. No warranty as to its accurateness, completeness or suitability for a particular purpose is expressed or implied.

- · Department issuing SDS: Document Control / Regulatory
- · Contact: regulatory@ultrasci.com
- · Date of preparation / last revision 03/27/2019 / 2
- · Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

ACGIH: American Conference of Governmental Industrial Hygienists

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety & Health

TLV: Threshold Limit Value

PEL: Permissible Exposure Limit

REL: Recommended Exposure Limit

BEI: Biological Exposure Limit

(Contd. on page 20)



Printing date 03/27/2019 Reviewed on 03/23/2019 Version Number 3

Trade name: Aromatics / Alkenes Standard (1X1 mL)

(Contd. of page 19)

Flam. Liq. 2: Flammable liquids – Category 2 Acute Tox. 3: Acute toxicity – Category 3 Skin Sens. 1: Skin sensitisation - Category 1 Muta. 1B: Germ cell mutagenicity - Category 1B Carc. 1A: Carcinogenicity – Category 1A

Repr. 2: Reproductive toxicity – Category 2

STOT SE 1: Specific target organ toxicity (single exposure) – Category 1

* Data compared to the previous version altered.