

Printing date 03/27/2019 Version Number 4 Reviewed on 03/23/2019

1 Identification

· Product identifier

· Trade name: Halomethanes Standard (1X1 mL)

· Part number: DWM-510-1

· Application of the substance / the mixture Reagents and Standards for Analytical Chemical Laboratory Use

· Details of the supplier of the safety data sheet

· Manufacturer/Supplier: Agilent Technologies, Inc. 5301 Stevens Creek Blvd.

Santa Clara, CA 95051 USA

· Information department:

Telephone: 800-227-9770

e-mail: pdl-msds author@agilent.com

· Emergency telephone number: CHEMTREC®: 1-800-424-9300

2 Hazard(s) identification

· Classification of the substance or mixture



GHS02 Flame

Flam. Liq. 2 H225 Highly flammable liquid and vapor.



GHS06 Skull and crossbones

Acute Tox. 3 H331 Toxic if inhaled.



GHS08 Health hazard

STOT SE 1 H370 Causes damage to organs.

- · Label elements
- · GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS).
- · Hazard pictograms







GHS02

GHS06

· Signal word Danger

· Hazard-determining components of labeling:

methanol

· Hazard statements

Highly flammable liquid and vapor.

Toxic if inhaled.

Causes damage to organs.

(Contd. on page 2)



Printing date 03/27/2019 Version Number 4 Reviewed on 03/23/2019

Trade name: Halomethanes Standard (1X1 mL)

(Contd. of page 1)

· Precautionary statements

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

Ground/bond container and receiving equipment.

Use explosion-proof electrical/ventilating/lighting/equipment.

Use only non-sparking tools.

Take precautionary measures against static discharge.

Do not breathe dust/fume/gas/mist/vapors/spray.

Wash thoroughly after handling.

Do not eat, drink or smoke when using this product.

Use only outdoors or in a well-ventilated area.

Wear protective gloves/protective clothing/eye protection/face protection.

If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

IF exposed: Call a POISON CENTER or doctor/physician.

Specific treatment (see on this label).

In case of fire: Use for extinction: CO2, powder or water spray.

Store in a well-ventilated place. Keep container tightly closed.

Store in a well-ventilated place. Keep cool.

Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

- · Classification system:
- · NFPA ratings (scale 0 4)



Health = 1 Fire = 3 Reactivity = 0

· HMIS-ratings (scale 0 - 4)



Health = *1Fire = 3

REACTIVITY 0 Reactivity = 0

- · Other hazards
- · Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · **vPvB**: Not applicable.

3 Composition/information on ingredients

- · Chemical characterization: Mixtures
- · Description: Mixture of the substances listed below with nonhazardous additions.
- · Dangerous components:

67-56-1 methanol

99.696%

4 First-aid measures

- · Description of first aid measures
- · General information:

Immediately remove any clothing soiled by the product.

(Contd. on page 3)



Printing date 03/27/2019 Version Number 4 Reviewed on 03/23/2019

Trade name: Halomethanes Standard (1X1 mL)

(Contd. of page 2)

Remove breathing apparatus only after contaminated clothing have been completely removed.

In case of irregular breathing or respiratory arrest provide artificial respiration.

· After inhalation:

Supply fresh air or oxygen; call for doctor.

In case of unconsciousness place patient stably in side position for transportation.

- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eye contact: Rinse opened eye for several minutes under running water. Then consult a doctor.
- · After swallowing: If symptoms persist consult doctor.
- · Information for doctor:
- Most important symptoms and effects, both acute and delayed No further relevant information available.
- · Indication of any immediate medical attention and special treatment needed

No further relevant information available.

5 Fire-fighting measures

- · Extinguishing media
- · Suitable extinguishing agents:

CO2, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

- · For safety reasons unsuitable extinguishing agents: Water with full jet
- · Special hazards arising from the substance or mixture

During heating or in case of fire poisonous gases are produced.

- · Advice for firefighters
- · Protective equipment: Mouth respiratory protective device.

6 Accidental release measures

· Personal precautions, protective equipment and emergency procedures

Mount respiratory protective device.

Wear protective equipment. Keep unprotected persons away.

- Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- · Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

· Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

· Protective Action Criteria for Chemicals

67-56-1 methanol 74-83-9 bromomethane		530 ppm
		10
		19 ppm
75-71-8 dichlorodifluorometha	ne	3,000 ppm
74-97-5 bromochloromethane		600 ppm
75-27-4 bromodichloromethan	e	1.3 mg/m ³
75-25-2 bromoform		1.5 ppm
67-66-3 trichloromethane		2 ppm
74-95-3 dibromomethane		3 ppm



Printing date 03/27/2019 Version Number 4 Reviewed on 03/23/2019

Trade name: Halomethanes Standard (1X1 mL)

	((Contd. of page 3)
124-48-1	dibromochloromethane	1.1 mg/m ³
75-69-4	trichlorofluoromethane	91 ppm
75-09-2	dichloromethane	200 ppm
56-23-5	carbon tetrachloride	1.2 ppm
74-87-3	chloromethane	150 ppm
· PAC-2:		
67-56-1	methanol	2,100 ppm
74-83-9	bromomethane	210 ppm
75-71-8	dichlorodifluoromethane	10,000 ppm
74-97-5	bromochloromethane	830 ppm
75-27-4	bromodichloromethane	14 mg/m ³
75-25-2	bromoform	6.8 ppm
67-66-3	trichloromethane	64 ppm
74-95-3	dibromomethane	33 ppm
124-48-1	dibromochloromethane	12 mg/m ³
75-69-4	trichlorofluoromethane	1,000 ppm
	dichloromethane	560 ppm
	carbon tetrachloride	13 ppm
74-87-3	chloromethane	910 ppm
· PAC-3:		
67-56-1	methanol	7200* ppm
74-83-9	bromomethane	740 ppm
75-71-8	dichlorodifluoromethane	50,000 ppm
74-97-5		5,000 ppm
75-27-4	bromodichloromethane	85 mg/m ³
		41 ppm
	trichloromethane	3,200 ppm
	dibromomethane	200 ppm
	dibromochloromethane	73 mg/m ³
	trichlorofluoromethane	10,000 ppm
		6,900 ppm
		340 ppm
74-87-3	chloromethane	3,000 ppm

7 Handling and storage

- · Handling:
- · Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Open and handle receptacle with care.

Prevent formation of aerosols.

· Information about protection against explosions and fires:

Keep ignition sources away - Do not smoke.

(Contd. on page 5)



Printing date 03/27/2019 Version Number 4 Reviewed on 03/23/2019

Trade name: Halomethanes Standard (1X1 mL)

(Contd. of page 4)

Protect against electrostatic charges.

Keep respiratory protective device available.

- · Conditions for safe storage, including any incompatibilities
- · Storage:
- Requirements to be met by storerooms and receptacles: Store in a cool location.
- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions:

Keep receptacle tightly sealed.

Store in cool, dry conditions in well sealed receptacles.

· Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

- · Additional information about design of technical systems: No further data; see item 7.
- · Control parameters

· Components with limit values that require monitoring at the workplace:

67-56-1 methanol

PEL	Long-term value: 260 mg/m³, 200 ppm
REL	Short-term value: 325 mg/m³, 250 ppm
	Long-term value: 260 mg/m³, 200 ppm Short-term value: 325 mg/m³, 250 ppm Long-term value: 260 mg/m³, 200 ppm Skin
TLV	Short-term value: 328 mg/m³, 250 ppm Long-term value: 262 mg/m³, 200 ppm Skin; BEI

· Ingredients with biological limit values:

67-56-1 methanol

BEI 15 mg/L

Medium: urine Time: end of shift

Parameter: Methanol (background, nonspecific)

- · Additional information: The lists that were valid during the creation were used as basis.
- · Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Store protective clothing separately.

· Breathing equipment:

When used as intended with Agilent instruments, the use of the product under normal laboratory conditions and with standard practices does not result in significant airborne exposures and therefore respiratory protection is not needed

Under an emergency condition where a respirator is deemed necessary, use a NIOSH or equivalent approved device/equipment with appropriate organic or acid gas cartridge.

· Protection of hands:

Although not recommended for constant contact with the chemicals or for clean-up, nitrile gloves 11-13 mil thickness are recommended for normal use. The breakthrough time is 1 hr. For cleaning a spill where there is direct contact of the chemical, butyl rubber gloves are recommended 12-15 mil thickness with breakthrough times

(Contd. on page 6)



Printing date 03/27/2019 Version Number 4 Reviewed on 03/23/2019

Trade name: Halomethanes Standard (1X1 mL)

(Contd. of page 5)

exceeding 4 hrs. Supplier recommendations should be followed.

· Material of gloves

For normal use: nitrile rubber, 11-13 mil thickness

For direct contact with the chemical: butyl rubber, 12-15 mil thickness

• **Penetration time of glove material** For normal use: nitrile rubber: 1 hour

For direct contact with the chemical: butyl rubber: >4 hours

· Eye protection:



Tightly sealed goggles

9 Physical and chemical proper	ties
· Information on basic physical and c · General Information	hemical properties
· Appearance:	
Form:	Fluid
Color: · Odor:	Colorless Alcohol-like
· Odor: · Odor threshold:	Not determined.
Odor threshold:	
· pH-value:	Not determined.
· Change in condition	
Melting point/Melting range:	-98 °C (-144.4 °F)
Boiling point/Boiling range:	64 °C (147.2 °F)
· Flash point:	9 °C (48.2 °F)
· Flammability (solid, gaseous):	Not applicable.
· Ignition temperature:	455 °C (851 °F)
· Decomposition temperature:	Not determined.
· Auto igniting:	Product is not selfigniting.
· Danger of explosion:	Product is not explosive. However, formation of explosive air/vapor mixtures are possible.
· Explosion limits:	
Lower:	5.5 Vol %
Upper:	44 Vol %
· Vapor pressure at 20 °C (68 °F):	100 hPa (75 mm Hg)
· Density at 20 °C (68 °F):	0.8 g/cm³ (6.676 lbs/gal)
· Relative density	Not determined.
· Vapor density	Not determined.
Evaporation rate	Not determined.
· Solubility in / Miscibility with	
Water:	Not miscible or difficult to mix.

(Contd. on page 7)



Printing date 03/27/2019 Version Number 4 Reviewed on 03/23/2019

Trade name: Halomethanes Standard (1X1 mL)

(Contd. of page 6)

· Partition coefficient (n-octanol/water): Not determined.

· Viscosity:

Dynamic: Not determined. **Kinematic:** Not determined.

· Solvent content:

 Organic solvents:
 99.8 %

 VOC content:
 99.77 %

997.7 g/l / 8.33 lb/gal

• Other information No further relevant information available.

10 Stability and reactivity

- · Reactivity No further relevant information available.
- · Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

11 Toxicological information

- · Information on toxicological effects
- · Acute toxicity:

· LD/LC50	values	that are re	levant for c	lassification:

ATE (Acute Toxicity Estimate)

Inhalative LC50/4 h 3.01 mg/L

67 56 1	methanol
0 / - 30 - 1	шепияног

Oral	LD50	5,628 mg/kg (rat)
Dermal	LD50	15,800 mg/kg (rabbit)

- · Primary irritant effect:
- · on the skin: No irritant effect.
- · on the eye: No irritating effect.
- · Sensitization: No sensitizing effects known.
- · Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations: Toxic

· Carcinogenic categories

· IARC (In	· IARC (International Agency for Research on Cancer)	
74-83-9	bromomethane	3
75-27-4	bromodichloromethane	2B
75-25-2	bromoform	3
67-66-3	trichloromethane	2B
	/a - 1	0)

(Contd. on page 8)



Printing date 03/27/2019 Version Number 4 Reviewed on 03/23/2019

Trade name: Halomethanes Standard (1X1 mL)

		(Contd. of page 7)
124-48-1	dibromochloromethane	3
75-09-2	dichloromethane	2A
56-23-5	carbon tetrachloride	2B
74-87-3	chloromethane	3
· NTP (Na	ntional Toxicology Program)	
75-27-4	bromodichloromethane	R
67-66-3	trichloromethane	R
75-09-2	dichloromethane	R
56-23-5	carbon tetrachloride	R
· OSHA-0	Ca (Occupational Safety & Health Administration)	
75-09-2	dichloromethane	

12 Ecological information

- · Toxicity
- · Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- · Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.
- · Additional ecological information:
- · General notes:

Water hazard class 1 (Self-assessment): slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

- · Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.
- · Other adverse effects No further relevant information available.

13 Disposal considerations

- · Waste treatment methods
- · Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packagings:
- · **Recommendation:** Disposal must be made according to official regulations.

14 Transport information

- · Not Regulated, De minimus Quantities
- · UN-Number
- · DOT, IMDG, IATA UN1230
- · UN proper shipping name
- **DOT** Methanol solution

(Contd. on page 9)



Printing date 03/27/2019 Version Number 4 Reviewed on 03/23/2019

Trade name: Halomethanes Standard (1X1 mL)

	(Contd. of page
IMDG, IATA	METHANOL solution
Transport hazard class(es)	
DOT	
3	
Class	3 Flammable liquids
Label	3, 6.1
IMDG	
Class	3 Flammable liquids
Label	3/6.1
IATA	
Class	3 Flammable liquids
Label	3 (6.1)
Packing group DOT, IMDG, IATA	II
Environmental hazards:	Not applicable.
Special precautions for user	Warning: Flammable liquids
Danger code (Kemler):	336
EMS Number:	F-E,S-D
Stowage Category Stowage Code	B SW2 Clear of living quarters.
Transport in bulk according to Annex MARPOL73/78 and the IBC Code	Not applicable.
Transport/Additional information:	11
DOT	
Quantity limitations	On passenger aircraft/rail: 1 L
	On cargo aircraft only: 60 L
IMDG	
Limited quantities (LQ)	1L
Excepted quantities (EQ)	Code: E2
	Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per outer packaging: 500 ml



Printing date 03/27/2019 Version Number 4 Reviewed on 03/23/2019

Trade name: Halomethanes Standard (1X1 mL)

(Contd. of page 9)

· UN "Model Regulation": UN 1230 METHANOL SOLUTION, 3 (6.1), II

15 Regulatory information Safety, health and environmental regulations/legislation specific for the substance or mixture Sara Section 355 (extremely hazardous substances):

. Section	313 (Specific toxic chemical listings):
67-66-3	trichloromethane

Section	515 (Specific toxic chemical fishings)
67-56-1	methanol

	bromometnane
75-71-8	dichlorodifluoromethane

75-27-4 bromodichloromethane

75-25-2 bromoform

67-66-3 trichloromethane

74-83-9 bromomethane

74-95-3 dibromomethane

75-69-4 trichlorofluoromethane

75-09-2 dichloromethane

56-23-5 carbon tetrachloride

74-87-3 chloromethane

· TSCA (Toxic Substances Control Act):

All ingredients are listed.

· Proposition 65

· Chemic	· Chemicals known to cause cancer:	
75-27-4	bromodichloromethane	
75-25-2	bromoform	
67-66-3	trichloromethane	
75-09-2	dichloromethane	
56-23-5	carbon tetrachloride	

· Chemicals known to cause reproductive toxicity for females:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for males:

74-87-3 chloromethane

· Chemicals known to cause developmental toxicity:

67-56-1 methanol

74-83-9 bromomethane

67-66-3 trichloromethane

74-87-3 chloromethane

(Contd. on page 11)



Printing date 03/27/2019 Version Number 4 Reviewed on 03/23/2019

Trade name: Halomethanes Standard (1X1 mL)

(Contd. of page 10)

· Carcinogenic categories

· EPA (Environmental Protection Agency)		
74-83-9	bromomethane	D
74-97-5	bromochloromethane	D
75-27-4	bromodichloromethane	B2
75-25-2	bromoform	B2
67-66-3	trichloromethane	B2, L, NL
124-48-1	dibromochloromethane	С
75-09-2	dichloromethane	L
56-23-5	carbon tetrachloride	L
74-87-3	chloromethane	D, CBD
· TLV (Threshold Limit Value established by ACGIH)		

· TLV (Threshold Limit Value established by ACGIH)		
74-83-9	bromomethane	A4
75-71-8	dichlorodifluoromethane	A4
75-25-2	bromoform	A3
67-66-3	trichloromethane	A3
75-69-4	trichlorofluoromethane	A4
75-09-2	dichloromethane	A3
56-23-5	carbon tetrachloride	A2
74-87-3	chloromethane	A4

· NIOSH-Ca (National Institute for Occupational Safety and Health)		
	bromomethane	
67-66-3	trichloromethane	
75-09-2	dichloromethane	
56-23-5	carbon tetrachloride	
74-87-3	chloromethane	

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

The information contained in this document is based on Agilent's state of knowledge at the time of preparation. No warranty as to its accurateness, completeness or suitability for a particular purpose is expressed or implied.

- · Department issuing SDS: Document Control / Regulatory
- · Contact: regulatory@ultrasci.com
- \cdot Date of preparation / last revision 03/27/2019 / 3
- · Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

ACGIH: American Conference of Governmental Industrial Hygienists

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

(Contd. on page 12)



Printing date 03/27/2019 Version Number 4 Reviewed on 03/23/2019

Trade name: Halomethanes Standard (1X1 mL)

HMIS: Hazardous Materials Identification System (USA)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety & Health TLV: Threshold Limit Value PEL: Permissible Exposure Limit REL: Recommended Exposure Limit BEI: Biological Exposure Limit

Flam. Liq. 2: Flammable liquids – Category 2

Acute Tox. 3: Acute toxicity – Category 3
STOT SE 1: Specific target organ toxicity (single exposure) – Category 1

* Data compared to the previous version altered.

(Contd. of page 11)