

Safety Data Sheet
acc. to OSHA HCS

Printing date 03/29/2019

Version Number 2

Reviewed on 03/29/2019

1 Identification

- **Product identifier**
- **Trade name:** VOC Standard (1X1 mL)
- **Part number:** DWM-620-1
- **Application of the substance / the mixture** Reagents and Standards for Analytical Chemical Laboratory Use
- **Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**
Agilent Technologies, Inc.
5301 Stevens Creek Blvd.
Santa Clara, CA 95051 USA
- **Information department:**
Telephone: 800-227-9770
e-mail: pdl-msds_author@agilent.com
- **Emergency telephone number:** CHEMTREC®: 1-800-424-9300

2 Hazard(s) identification

- **Classification of the substance or mixture**



GHS02 Flame

Flam. Liq. 2 H225 Highly flammable liquid and vapor.



GHS06 Skull and crossbones

Acute Tox. 3 H331 Toxic if inhaled.



GHS08 Health hazard

Muta. 1B H340 May cause genetic defects.

Carc. 1B H350 May cause cancer.

Repr. 1A H360 May damage fertility or the unborn child.

STOT SE 1 H370 Causes damage to organs.



GHS07

Acute Tox. 4 H312 Harmful in contact with skin.

Skin Sens. 1 H317 May cause an allergic skin reaction.

- **Label elements**

- **GHS label elements** The product is classified and labeled according to the Globally Harmonized System (GHS).

(Contd. on page 2)

Safety Data Sheet

acc. to OSHA HCS

Printing date 03/29/2019

Version Number 2

Reviewed on 03/29/2019

Trade name: VOC Standard (1X1 mL)

(Contd. of page 1)

· Hazard pictograms

· Signal word Danger
· Hazard-determining components of labeling:

methanol
 1,2-dibromo-3-chloropropane
 1,1,2,2-tetrachloroethane
 1,2-dibromoethane
 (Z)-1,3-dichloropropene
 trans-1,3-dichloropropene

· Hazard statements

Highly flammable liquid and vapor.
 Harmful in contact with skin.
 Toxic if inhaled.
 May cause an allergic skin reaction.
 May cause genetic defects.
 May cause cancer.
 May damage fertility or the unborn child.
 Causes damage to organs.

· Precautionary statements

Obtain special instructions before use.
 Do not handle until all safety precautions have been read and understood.
 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.
 Ground/bond container and receiving equipment.
 Use explosion-proof electrical/ventilating/lighting/equipment.
 Use only non-sparking tools.
 Take precautionary measures against static discharge.
 Do not breathe dust/fume/gas/mist/vapors/spray.
 Wash thoroughly after handling.
 Do not eat, drink or smoke when using this product.
 Use only outdoors or in a well-ventilated area.
 Contaminated work clothing must not be allowed out of the workplace.
 Wear protective gloves/protective clothing/eye protection/face protection.
 If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
 IF INHALED: Remove person to fresh air and keep comfortable for breathing.
 IF exposed or concerned: Get medical advice/attention.
 Specific treatment (see on this label).
 Call a poison center/doctor if you feel unwell.
 Take off contaminated clothing and wash it before reuse.
 If skin irritation or rash occurs: Get medical advice/attention.
 Wash contaminated clothing before reuse.
 In case of fire: Use for extinction: CO₂, powder or water spray.
 Store in a well-ventilated place. Keep container tightly closed.
 Store in a well-ventilated place. Keep cool.
 Store locked up.
 Dispose of contents/container in accordance with local/regional/national/international regulations.

(Contd. on page 3)

Safety Data Sheet

acc. to OSHA HCS

Printing date 03/29/2019

Version Number 2

Reviewed on 03/29/2019

Trade name: VOC Standard (1X1 mL)

(Contd. of page 2)

- **Classification system:**
- **NFPA ratings (scale 0 - 4)**



- **HMIS-ratings (scale 0 - 4)**



- **Other hazards**
- **Results of PBT and vPvB assessment**

· PBT:

87-68-3	hexachlorobuta-1,3-diene
---------	--------------------------

· vPvB:

87-68-3	hexachlorobuta-1,3-diene
---------	--------------------------

3 Composition/information on ingredients

- **Chemical characterization: Mixtures**
- **Description:** Mixture of the substances listed below with nonhazardous additions.

· Dangerous components:

67-56-1	methanol	96.461%
96-12-8	1,2-dibromo-3-chloropropane	0.253%
106-93-4	1,2-dibromoethane	0.253%
107-06-2	1,2-dichloroethane	0.253%
10061-01-5	(Z)-1,3-dichloropropene	0.253%
10061-02-6	trans-1,3-dichloropropene	0.253%
87-68-3	hexachlorobuta-1,3-diene	0.253%
630-20-6	1,1,1,2-Tetrachloroethane	0.253%
79-34-5	1,1,2,2-tetrachloroethane	0.253%
79-00-5	1,1,2-trichloroethane	0.253%
79-01-6	trichloroethylene	0.253%
96-18-4	1,2,3-trichloropropane	0.253%

4 First-aid measures

- **Description of first aid measures**
- **General information:**
 Immediately remove any clothing soiled by the product.
 Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.
 Remove breathing apparatus only after contaminated clothing have been completely removed.

(Contd. on page 4)

Safety Data Sheet

acc. to OSHA HCS

Printing date 03/29/2019

Version Number 2

Reviewed on 03/29/2019

Trade name: VOC Standard (1X1 mL)

(Contd. of page 3)

- In case of irregular breathing or respiratory arrest provide artificial respiration.
- **After inhalation:**
Supply fresh air or oxygen; call for doctor.
In case of unconsciousness place patient stably in side position for transportation.
- **After skin contact:** Immediately wash with water and soap and rinse thoroughly.
- **After eye contact:** Rinse opened eye for several minutes under running water. Then consult a doctor.
- **After swallowing:** If symptoms persist consult doctor.
- **Information for doctor:**
- **Most important symptoms and effects, both acute and delayed** No further relevant information available.
- **Indication of any immediate medical attention and special treatment needed**
No further relevant information available.

5 Fire-fighting measures

- **Extinguishing media**
- **Suitable extinguishing agents:**
CO₂, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- **For safety reasons unsuitable extinguishing agents:** Water with full jet
- **Special hazards arising from the substance or mixture**
During heating or in case of fire poisonous gases are produced.
- **Advice for firefighters**
- **Protective equipment:** Mouth respiratory protective device.

6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures**
Mount respiratory protective device.
Wear protective equipment. Keep unprotected persons away.
- **Environmental precautions:** Do not allow to enter sewers/ surface or ground water.
- **Methods and material for containment and cleaning up:**
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Dispose contaminated material as waste according to item 13.
Ensure adequate ventilation.
- **Reference to other sections**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.
- **Protective Action Criteria for Chemicals**

- **PAC-1:**

67-56-1	methanol	530 ppm
96-12-8	1,2-dibromo-3-chloropropane	0.003 ppm
106-93-4	1,2-dibromoethane	17 ppm
107-06-2	1,2-dichloroethane	50 ppm
78-87-5	1,2-dichloropropane	30 ppm
142-28-9	1,3-dichloropropane	5.4 ppm
563-58-6	1,1-dichloropropene	1.3 ppm
87-68-3	hexachlorobuta-1,3-diene	1 ppm

(Contd. on page 5)

Safety Data Sheet

acc. to OSHA HCS

Printing date 03/29/2019

Version Number 2

Reviewed on 03/29/2019

Trade name: VOC Standard (1X1 mL)

(Contd. of page 4)

630-20-6	1,1,1,2-Tetrachloroethane	0.2 ppm
79-34-5	1,1,2,2-tetrachloroethane	3 ppm
79-00-5	1,1,2-trichloroethane	30 ppm
79-01-6	trichloroethylene	130 ppm
96-18-4	1,2,3-trichloropropane	0.015 ppm

· PAC-2:

67-56-1	methanol	2,100 ppm
96-12-8	1,2-dibromo-3-chloropropane	2.2 ppm
106-93-4	1,2-dibromoethane	24 ppm
107-06-2	1,2-dichloroethane	200 ppm
78-87-5	1,2-dichloropropane	220 ppm
142-28-9	1,3-dichloropropane	59 ppm
563-58-6	1,1-dichloropropene	15 ppm
87-68-3	hexachlorobuta-1,3-diene	3 ppm
630-20-6	1,1,1,2-Tetrachloroethane	2.2 ppm
79-34-5	1,1,2,2-tetrachloroethane	120 ppm
79-00-5	1,1,2-trichloroethane	180 ppm
79-01-6	trichloroethylene	450 ppm
96-18-4	1,2,3-trichloropropane	170 ppm

· PAC-3:

67-56-1	methanol	7200* ppm
96-12-8	1,2-dibromo-3-chloropropane	4.3 ppm
106-93-4	1,2-dibromoethane	46 ppm
107-06-2	1,2-dichloroethane	300 ppm
78-87-5	1,2-dichloropropane	2,000 ppm
142-28-9	1,3-dichloropropane	350 ppm
563-58-6	1,1-dichloropropene	87 ppm
87-68-3	hexachlorobuta-1,3-diene	10 ppm
630-20-6	1,1,1,2-Tetrachloroethane	13 ppm
79-34-5	1,1,2,2-tetrachloroethane	150 ppm
79-00-5	1,1,2-trichloroethane	500 ppm
79-01-6	trichloroethylene	3,800 ppm
96-18-4	1,2,3-trichloropropane	1,000 ppm

7 Handling and storage

· Handling:
· Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Open and handle receptacle with care.

Prevent formation of aerosols.

· Information about protection against explosions and fires:

Keep ignition sources away - Do not smoke.

(Contd. on page 6)

Safety Data Sheet acc. to OSHA HCS

Printing date 03/29/2019

Version Number 2

Reviewed on 03/29/2019

Trade name: VOC Standard (1X1 mL)

(Contd. of page 5)

Protect against electrostatic charges.
Keep respiratory protective device available.

- **Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:** Store in a cool location.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:**
 - Keep receptacle tightly sealed.
 - Store in cool, dry conditions in well sealed receptacles.
- **Specific end use(s)** No further relevant information available.

* 8 Exposure controls/personal protection

- **Additional information about design of technical systems:** No further data; see item 7.
- **Control parameters**

· **Components with limit values that require monitoring at the workplace:**

67-56-1 methanol

PEL	Long-term value: 260 mg/m ³ , 200 ppm
REL	Short-term value: 325 mg/m ³ , 250 ppm Long-term value: 260 mg/m ³ , 200 ppm Skin
TLV	Short-term value: 328 mg/m ³ , 250 ppm Long-term value: 262 mg/m ³ , 200 ppm Skin; BEI

96-12-8 1,2-dibromo-3-chloropropane

PEL	Long-term value: 0.001 ppm see 29 CFR 1910.1044
REL	See Pocket Guide App. A

106-93-4 1,2-dibromoethane

PEL	Long-term value: 20 ppm Ceiling limit value: 30; 50* ppm *5-min peak per 8-hr shift
REL	Long-term value: 0.045 ppm Ceiling limit value: 0.13* ppm *15-min; See Pocket Guide App. A
TLV	Skin

107-06-2 1,2-dichloroethane

PEL	Long-term value: 50 ppm Ceiling limit value: 100; 200* ppm *5-min peak in any 3 hrs
REL	Short-term value: 8 mg/m ³ , 2 ppm Long-term value: 4 mg/m ³ , 1 ppm See Pocket Guide Apps. A and C
TLV	Long-term value: 40 mg/m ³ , 10 ppm

(Contd. on page 7)

Safety Data Sheet

acc. to OSHA HCS

Printing date 03/29/2019

Version Number 2

Reviewed on 03/29/2019

Trade name: VOC Standard (1X1 mL)

(Contd. of page 6)

87-68-3 hexachlorobuta-1,3-diene

REL	Long-term value: 0.24 mg/m ³ , 0.02 ppm Skin; See Pocket Guide App. A
TLV	Long-term value: 0.21 mg/m ³ , 0.02 ppm Skin

630-20-6 1,1,1,2-Tetrachloroethane

REL	Handle with caution; See Pocket Guide App. C
-----	--

79-34-5 1,1,2,2-tetrachloroethane

PEL	Long-term value: 35 mg/m ³ , 5 ppm Skin
REL	Long-term value: 7 mg/m ³ , 1 ppm Skin; See Pocket Guide Apps. A and C
TLV	Long-term value: 6.9 mg/m ³ , 1 ppm Skin

79-00-5 1,1,2-trichloroethane

PEL	Long-term value: 45 mg/m ³ , 10 ppm Skin
REL	Long-term value: 45 mg/m ³ , 10 ppm Skin; See Pocket Guide Apps. A and C
TLV	Long-term value: 55 mg/m ³ , 10 ppm Skin

79-01-6 trichloroethylene

PEL	Long-term value: 100 ppm Ceiling limit value: 200; 300* ppm *5-min peak in any 2 hrs
REL	See Pocket Guide Apps. A and C
TLV	Short-term value: 135 mg/m ³ , 25 ppm Long-term value: 54 mg/m ³ , 10 ppm BEI

96-18-4 1,2,3-trichloropropane

PEL	Long-term value: 300 mg/m ³ , 50 ppm
REL	Long-term value: 60 mg/m ³ , 10 ppm Skin, See Pocket Guide App. A
TLV	Long-term value: 0.03 mg/m ³ , 0.005 ppm

Ingredients with biological limit values:
67-56-1 methanol

BEI	15 mg/L Medium: urine Time: end of shift Parameter: Methanol (background, nonspecific)
-----	---

(Contd. on page 8)

US

Safety Data Sheet acc. to OSHA HCS

Printing date 03/29/2019

Version Number 2

Reviewed on 03/29/2019

Trade name: VOC Standard (1X1 mL)

(Contd. of page 7)

79-01-6 trichloroethylene

BEI	15 mg/L Medium: urine Time: end of shift at end of workweek Parameter: Trichloroacetic acid (nonspecific)
	0.5 mg/L Medium: blood Time: end of shift at end of workweek Parameter: Trichloroethanol without hydrolysis (nonspecific)
-	Medium: blood Time: end of shift at end of workweek Parameter: Trichloroethylene (semi-quantitative)
-	Medium: end-exhaled air Time: end of shift at end of workweek Parameter: Trichloroethylene (semi-quantitative)

· **Additional information:** The lists that were valid during the creation were used as basis.

· **Exposure controls**

· **Personal protective equipment:**

· **General protective and hygienic measures:**

- Keep away from foodstuffs, beverages and feed.
- Immediately remove all soiled and contaminated clothing.
- Wash hands before breaks and at the end of work.
- Store protective clothing separately.
- Avoid contact with the eyes and skin.

· **Breathing equipment:**

When used as intended with Agilent instruments, the use of the product under normal laboratory conditions and with standard practices does not result in significant airborne exposures and therefore respiratory protection is not needed.

Under an emergency condition where a respirator is deemed necessary, use a NIOSH or equivalent approved device/equipment with appropriate organic or acid gas cartridge.

· **Protection of hands:**

Although not recommended for constant contact with the chemicals or for clean-up, nitrile gloves 11-13 mil thickness are recommended for normal use. The breakthrough time is 1 hr. For cleaning a spill where there is direct contact of the chemical, butyl rubber gloves are recommended 12-15 mil thickness with breakthrough times exceeding 4 hrs. Supplier recommendations should be followed.

· **Material of gloves**

- For normal use: nitrile rubber, 11-13 mil thickness
- For direct contact with the chemical: butyl rubber, 12-15 mil thickness

· **Penetration time of glove material**

- For normal use: nitrile rubber: 1 hour
- For direct contact with the chemical: butyl rubber: >4 hours

(Contd. on page 9)

Safety Data Sheet

acc. to OSHA HCS

Printing date 03/29/2019

Version Number 2

Reviewed on 03/29/2019

Trade name: VOC Standard (1X1 mL)

(Contd. of page 8)

· Eye protection:


Tightly sealed goggles

9 Physical and chemical properties

· Information on basic physical and chemical properties
· General Information
· Appearance:

Form:	Fluid
Color:	Colorless
· Odor:	Alcohol-like
· Odor threshold:	Not determined.

· pH-value: Not determined.

· Change in condition

Melting point/Melting range:	-98 °C (-144.4 °F)
Boiling point/Boiling range:	64.7 °C (148.5 °F)

· Flash point: 9 °C (48.2 °F)

· Flammability (solid, gaseous): Not applicable.

· Ignition temperature: 455 °C (851 °F)

· Decomposition temperature: Not determined.

· Auto igniting: Product is not selfigniting.

· Danger of explosion: Product is not explosive. However, formation of explosive air/vapor mixtures are possible.

· Explosion limits:

Lower:	5.5 Vol %
Upper:	44 Vol %

· Vapor pressure at 20 °C (68 °F): 100 hPa (75 mm Hg)

· Density at 20 °C (68 °F): 0.82382 g/cm³ (6.87478 lbs/gal)

· Relative density Not determined.

· Vapor density Not determined.

· Evaporation rate Not determined.

· Solubility in / Miscibility with
Water: Not miscible or difficult to mix.

· Partition coefficient (n-octanol/water): Not determined.

· Viscosity:

Dynamic:	Not determined.
Kinematic:	Not determined.

(Contd. on page 10)

Safety Data Sheet

acc. to OSHA HCS

Printing date 03/29/2019

Version Number 2

Reviewed on 03/29/2019

Trade name: VOC Standard (1X1 mL)

(Contd. of page 9)

· Solvent content:	
Organic solvents:	97.5 %
VOC content:	97.47 %
	803.0 g/l / 6.70 lb/gal
· Solids content:	
	0.0 %
· Other information	
	No further relevant information available.

10 Stability and reactivity

- **Reactivity** No further relevant information available.
- **Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **Possibility of hazardous reactions** No dangerous reactions known.
- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:** No dangerous decomposition products known.

11 Toxicological information

- **Information on toxicological effects**
- **Acute toxicity:**

· LD/LC50 values that are relevant for classification:
ATE (Acute Toxicity Estimate)

Oral	LD50	6,675 mg/kg
Dermal	LD50	1,798 mg/kg
Inhalative	LC50/4 h	3.05 mg/L

67-56-1 methanol

Oral	LD50	5,628 mg/kg (rat)
Dermal	LD50	15,800 mg/kg (rabbit)

96-12-8 1,2-dibromo-3-chloropropane

Oral	LD50	170 mg/kg (rat)
Dermal	LD50	1,420 mg/kg (rat)
		1,400 mg/kg (rabbit)

106-93-4 1,2-dibromoethane

Oral	LD50	108 mg/kg (rat)
		55 mg/kg (rabbit)
Dermal	LD50	300 mg/kg (rabbit)

107-06-2 1,2-dichloroethane

Oral	LD50	670 mg/kg (rat)
Dermal	LD50	2,800 mg/kg (rat)
		2,800 mg/kg (rabbit)

(Contd. on page 11)

US

Safety Data Sheet

acc. to OSHA HCS

Printing date 03/29/2019

Version Number 2

Reviewed on 03/29/2019

Trade name: VOC Standard (1X1 mL)

(Contd. of page 10)

10061-01-5 (Z)-1,3-dichloropropene		
Oral	LD50	250 mg/kg (rat)
10061-02-6 trans-1,3-dichloropropene		
Oral	LD50	250 mg/kg (rat)
87-68-3 hexachlorobuta-1,3-diene		
Oral	LD50	82 mg/kg (rat)
Dermal	LD50	100 mg/kg (rabbit)
Inhalative	LC50/4 h	370 mg/L (mouse)
630-20-6 1,1,1,2-Tetrachloroethane		
Oral	LD50	670 mg/kg (rat)
Dermal	LD50	20,000 mg/kg (rabbit)
Inhalative	LC50/4 h	2,100 mg/L (rat)
79-34-5 1,1,2,2-tetrachloroethane		
Oral	LD50	200 mg/kg (rat)
79-00-5 1,1,2-trichloroethane		
Oral	LD50	836 mg/kg (rat)
79-01-6 trichloroethylene		
Oral	LD50	2,402 mg/kg (mouse) 4,290 mg/kg (rat)
Dermal	LD50	8,450 mg/kg (mouse)
96-18-4 1,2,3-trichloropropane		
Oral	LD50	152 mg/kg (rat)
Dermal	LD50	523 mg/kg (rabbit)
Inhalative	LC50/4 h	4,800 mg/L (rat)

- **Primary irritant effect:**

- **on the skin:** No irritant effect.

- **on the eye:** No irritating effect.

- **Sensitization:** Sensitization possible through skin contact.

- **Additional toxicological information:**

The product shows the following dangers according to internally approved calculation methods for preparations:

Toxic

Harmful

Irritant

The product can cause inheritable damage.

- **Carcinogenic categories**

- **IARC (International Agency for Research on Cancer)**

96-12-8	1,2-dibromo-3-chloropropane	2B
106-93-4	1,2-dibromoethane	2A
107-06-2	1,2-dichloroethane	2B
78-87-5	1,2-dichloropropane	1
87-68-3	hexachlorobuta-1,3-diene	3
630-20-6	1,1,1,2-Tetrachloroethane	2B
79-34-5	1,1,2,2-tetrachloroethane	2B

(Contd. on page 12)

Safety Data Sheet

acc. to OSHA HCS

Printing date 03/29/2019

Version Number 2

Reviewed on 03/29/2019

Trade name: VOC Standard (1X1 mL)

(Contd. of page 11)

79-00-5	1,1,2-trichloroethane	3
79-01-6	trichloroethylene	1
96-18-4	1,2,3-trichloropropane	2A

· NTP (National Toxicology Program)

96-12-8	1,2-dibromo-3-chloropropane	R
106-93-4	1,2-dibromoethane	R
107-06-2	1,2-dichloroethane	R
79-01-6	trichloroethylene	K
96-18-4	1,2,3-trichloropropane	R

· OSHA-Ca (Occupational Safety & Health Administration)

96-12-8	1,2-dibromo-3-chloropropane	
---------	-----------------------------	--

12 Ecological information

- **Toxicity**
- **Aquatic toxicity:** No further relevant information available.
- **Persistence and degradability** No further relevant information available.
- **Behavior in environmental systems:**
- **Bioaccumulative potential** No further relevant information available.
- **Mobility in soil** No further relevant information available.
- **Additional ecological information:**

· General notes:

Water hazard class 3 (Self-assessment): extremely hazardous for water
 Do not allow product to reach ground water, water course or sewage system, even in small quantities.
 Danger to drinking water if even extremely small quantities leak into the ground.

· Results of PBT and vPvB assessment

· PBT:		
87-68-3	hexachlorobuta-1,3-diene	

· vPvB:		
87-68-3	hexachlorobuta-1,3-diene	

- **Other adverse effects** No further relevant information available.

13 Disposal considerations

- **Waste treatment methods**
- **Recommendation:**
Must not be disposed of together with household garbage. Do not allow product to reach sewage system.
- **Uncleaned packagings:**
- **Recommendation:** Disposal must be made according to official regulations.

14 Transport information

- **Not Regulated, De minimus Quantities** -

(Contd. on page 13)

Safety Data Sheet

acc. to OSHA HCS

Printing date 03/29/2019

Version Number 2

Reviewed on 03/29/2019

Trade name: VOC Standard (1X1 mL)

(Contd. of page 12)

· **UN-Number**
 · **DOT, IMDG, IATA** UN1230

· **UN proper shipping name**
 · **DOT** Methanol solution
 · **IMDG, IATA** METHANOL solution

· **Transport hazard class(es)**

· **DOT**



· **Class** 3 Flammable liquids
 · **Label** 3, 6.1

· **IMDG**



· **Class** 3 Flammable liquids
 · **Label** 3/6.1

· **IATA**



· **Class** 3 Flammable liquids
 · **Label** 3 (6.1)

· **Packing group**

· **DOT, IMDG, IATA** II

· **Environmental hazards:** Not applicable.

· **Special precautions for user** Warning: Flammable liquids

· **Danger code (Kemler):** 336

· **EMS Number:** F-E,S-D

· **Stowage Category** B

· **Stowage Code** SW2 Clear of living quarters.

· **Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code** Not applicable.

· **Transport/Additional information:**

· **DOT**

· **Quantity limitations** On passenger aircraft/rail: 1 L
On cargo aircraft only: 60 L

(Contd. on page 14)

Safety Data Sheet

acc. to OSHA HCS

Printing date 03/29/2019

Version Number 2

Reviewed on 03/29/2019

Trade name: VOC Standard (1X1 mL)

(Contd. of page 13)

- | | |
|--|---|
| <ul style="list-style-type: none"> · IMDG · Limited quantities (LQ) · Excepted quantities (EQ) | 1L
Code: E2
Maximum net quantity per inner packaging: 30 ml
Maximum net quantity per outer packaging: 500 ml |
| <ul style="list-style-type: none"> · UN "Model Regulation": | UN 1230 METHANOL SOLUTION, 3 (6.1), II |

15 Regulatory information

- **Safety, health and environmental regulations/legislation specific for the substance or mixture**
- **Sara**

- **Section 355 (extremely hazardous substances):**

None of the ingredients is listed.

- **Section 313 (Specific toxic chemical listings):**

67-56-1	methanol
96-12-8	1,2-dibromo-3-chloropropane
106-93-4	1,2-dibromoethane
107-06-2	1,2-dichloroethane
78-87-5	1,2-dichloropropane
10061-02-6	trans-1,3-dichloropropene
87-68-3	hexachlorobuta-1,3-diene
630-20-6	1,1,1,2-Tetrachloroethane
79-34-5	1,1,2,2-tetrachloroethane
79-00-5	1,1,2-trichloroethane
79-01-6	trichloroethylene
96-18-4	1,2,3-trichloropropane

- **TSCA (Toxic Substances Control Act):**

67-56-1	methanol
96-12-8	1,2-dibromo-3-chloropropane
106-93-4	1,2-dibromoethane
107-06-2	1,2-dichloroethane
78-87-5	1,2-dichloropropane
142-28-9	1,3-dichloropropane
10061-02-6	trans-1,3-dichloropropene
87-68-3	hexachlorobuta-1,3-diene
630-20-6	1,1,1,2-Tetrachloroethane
79-34-5	1,1,2,2-tetrachloroethane
79-00-5	1,1,2-trichloroethane
79-01-6	trichloroethylene
96-18-4	1,2,3-trichloropropane

(Contd. on page 15)

Safety Data Sheet

acc. to OSHA HCS

Printing date 03/29/2019

Version Number 2

Reviewed on 03/29/2019

Trade name: VOC Standard (1X1 mL)

(Contd. of page 14)

· TSCA new (21st Century Act): (Substances not listed)

96-12-8	1,2-dibromo-3-chloropropane
10061-01-5	(Z)-1,3-dichloropropene
10061-02-6	trans-1,3-dichloropropene
87-68-3	hexachlorobuta-1,3-diene

· Proposition 65
· Chemicals known to cause cancer:

96-12-8	1,2-dibromo-3-chloropropane
106-93-4	1,2-dibromoethane
107-06-2	1,2-dichloroethane
78-87-5	1,2-dichloropropane
87-68-3	hexachlorobuta-1,3-diene
630-20-6	1,1,1,2-Tetrachloroethane
79-34-5	1,1,2,2-tetrachloroethane
79-00-5	1,1,2-trichloroethane
79-01-6	trichloroethylene
96-18-4	1,2,3-trichloropropane

· Chemicals known to cause reproductive toxicity for females:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for males:

96-12-8	1,2-dibromo-3-chloropropane
106-93-4	1,2-dibromoethane
79-01-6	trichloroethylene

· Chemicals known to cause developmental toxicity:

67-56-1	methanol
106-93-4	1,2-dibromoethane
79-01-6	trichloroethylene

· Carcinogenic categories
· EPA (Environmental Protection Agency)

106-93-4	1,2-dibromoethane	L
107-06-2	1,2-dichloroethane	B2
87-68-3	hexachlorobuta-1,3-diene	C
630-20-6	1,1,1,2-Tetrachloroethane	C
79-34-5	1,1,2,2-tetrachloroethane	L
79-00-5	1,1,2-trichloroethane	C
79-01-6	trichloroethylene	CaH
96-18-4	1,2,3-trichloropropane	L

· TLV (Threshold Limit Value established by ACGIH)

106-93-4	1,2-dibromoethane	A3
107-06-2	1,2-dichloroethane	A4
78-87-5	1,2-dichloropropane	A4

(Contd. on page 16)

Safety Data Sheet

acc. to OSHA HCS

Printing date 03/29/2019

Version Number 2

Reviewed on 03/29/2019

Trade name: VOC Standard (1X1 mL)

(Contd. of page 15)

87-68-3	hexachlorobuta-1,3-diene	A3
79-34-5	1,1,2,2-tetrachloroethane	A3
79-00-5	1,1,2-trichloroethane	A3
79-01-6	trichloroethylene	A2
96-18-4	1,2,3-trichloropropane	A3

· NIOSH-Ca (National Institute for Occupational Safety and Health)

96-12-8	1,2-dibromo-3-chloropropane
106-93-4	1,2-dibromoethane
107-06-2	1,2-dichloroethane
78-87-5	1,2-dichloropropane
87-68-3	hexachlorobuta-1,3-diene
79-34-5	1,1,2,2-tetrachloroethane
79-00-5	1,1,2-trichloroethane
79-01-6	trichloroethylene
96-18-4	1,2,3-trichloropropane

· National regulations:
· Additional classification according to Decree on Hazardous Materials:

Carcinogenic hazardous material group III (dangerous).

· Information about limitation of use:

Workers are not allowed to be exposed to the hazardous carcinogenic materials contained in this preparation.

Exceptions can be made by the authorities in certain cases.

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

The information contained in this document is based on Agilent's state of knowledge at the time of preparation. No warranty as to its accurateness, completeness or suitability for a particular purpose is expressed or implied.

· Date of preparation / last revision 03/29/2019 / 1

· Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

ACGIH: American Conference of Governmental Industrial Hygienists

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety & Health

TLV: Threshold Limit Value

PEL: Permissible Exposure Limit

REL: Recommended Exposure Limit

BEI: Biological Exposure Limit

(Contd. on page 17)

Safety Data Sheet
acc. to OSHA HCS

Printing date 03/29/2019

Version Number 2

Reviewed on 03/29/2019

Trade name: VOC Standard (1X1 mL)

Flam. Liq. 2: Flammable liquids – Category 2
Acute Tox. 4: Acute toxicity – Category 4
Acute Tox. 3: Acute toxicity – Category 3
Skin Sens. 1: Skin sensitisation – Category 1
Muta. 1B: Germ cell mutagenicity – Category 1B
Carc. 1B: Carcinogenicity – Category 1B
Repr. 1A: Reproductive toxicity – Category 1A
STOT SE 1: Specific target organ toxicity (single exposure) – Category 1

(Contd. of page 16)

*** Data compared to the previous version altered.**

US