Printing date 03/28/2019

Agilent

Version Number 2

Reviewed on 03/28/2019

1 Identification

· Product identifier

· Trade name: Halowax 1000 Standard (1X2 mL)

- · Part number: HPCK-2F
- · Application of the substance / the mixture Reagents and Standards for Analytical Chemical Laboratory Use
- · Details of the supplier of the safety data sheet

• Manufacturer/Supplier: Agilent Technologies, Inc. 5301 Stevens Creek Blvd. Santa Clara, CA 95051 USA

· Information department:

Telephone: 800-227-9770 e-mail: pdl-msds_author@agilent.com • Emergency telephone number: CHEMTREC®: 1-800-424-9300

2 Hazard(s) identification

· Classification of the substance or mixture

GHS02 Flame

Flam. Liq. 2 H225 Highly flammable liquid and vapor.

GHS08 Health hazard

Repr. 2 H361 Suspected of damaging fertility or the unborn child.

STOT RE 2 H373 May cause damage to organs through prolonged or repeated exposure.

Asp. Tox. 1 H304 May be fatal if swallowed and enters airways.

GHS07

Skin Irrit. 2 H315 Causes skin irritation.

STOT SE 3 H336 May cause drowsiness or dizziness.

· Label elements

 \cdot GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS).

· Hazard pictograms



· Signal word Danger

- Hazard-determining components of labeling: n-hexane
- **Hazard statements** Highly flammable liquid and vapor.

(Contd. on page 2)

US

Reviewed on 03/28/2019

(Contd. on page 3)

Trade name: Halowax 1000 Standard (1X2 mL)

(Contd. of page 1) Causes skin irritation. Suspected of damaging fertility or the unborn child. May cause drowsiness or dizziness. May cause damage to organs through prolonged or repeated exposure. May be fatal if swallowed and enters airways. · Precautionary statements Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Ground/bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting/equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Do not breathe dust/fume/gas/mist/vapors/spray. Wash thoroughly after handling. Use only outdoors or in a well-ventilated area. Wear protective gloves/protective clothing/eye protection/face protection. If swallowed: Immediately call a poison center/doctor. Specific treatment (see on this label). Do NOT induce vomiting. If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. IF INHALED: Remove person to fresh air and keep comfortable for breathing. IF exposed or concerned: Get medical advice/attention. Call a poison center/doctor if you feel unwell. Get medical advice/attention if you feel unwell. Take off contaminated clothing and wash it before reuse. If skin irritation occurs: Get medical advice/attention. In case of fire: Use for extinction: CO2, powder or water spray. Store in a well-ventilated place. Keep container tightly closed. Store in a well-ventilated place. Keep cool. Store locked up. Dispose of contents/container in accordance with local/regional/national/international regulations. · Classification system: NFPA ratings (scale 0 - 4) Health = 1Fire = 3Reactivity = 0· HMIS-ratings (scale 0 - 4) HEALTH 1 Health = 1FIRE 3 Fire = 3**REACTIVITY** Reactivity = 0· Other hazards · Results of PBT and vPvB assessment • **PBT:** Not applicable. • **vPvB**: Not applicable.



Printing date 03/28/2019

Version Number 2

Reviewed on 03/28/2019

Trade name: Halowax 1000 Standard (1X2 mL)

(Contd. of page 2)

99.985%

3 Composition/information on ingredients

· Chemical characterization: Mixtures

• Description: Mixture of the substances listed below with nonhazardous additions.

· Dangerous components:

110-54-3 n-hexane

Printing date 03/28/2019

4 First-aid measures

· Description of first aid measures

· General information:

Immediately remove any clothing soiled by the product.

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

- After inhalation: In case of unconsciousness place patient stably in side position for transportation.
- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- After eye contact: Rinse opened eye for several minutes under running water.
- After swallowing: If symptoms persist consult doctor.
- · Information for doctor:
- · Most important symptoms and effects, both acute and delayed No further relevant information available.
- · Indication of any immediate medical attention and special treatment needed
- No further relevant information available.

5 Fire-fighting measures

- · Extinguishing media
- Suitable extinguishing agents:
- CO2, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- For safety reasons unsuitable extinguishing agents: Water with full jet
- · Special hazards arising from the substance or mixture
- During heating or in case of fire poisonous gases are produced.
- · Advice for firefighters
- · Protective equipment: Mouth respiratory protective device.

6 Accidental release measures

Personal precautions, protective equipment and emergency procedures Mount respiratory protective device.
Wear protective equipment. Keep unprotected persons away.
Environmental precautions: Do not allow to enter sewers/ surface or ground water.
Methods and material for containment and cleaning up: Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

- · Reference to other sections
- See Section 7 for information on safe handling.
- See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

(Contd. on page 4)



Version Number 2

Reviewed on 03/28/2019

Trade name: Halowax 1000 Standard (1X2 mL)

(Contd. of page 3)

260 ppm

2900* ppm

8600** ppm

· Protective Action Criteria for Chemicals

· PAC-1:

110-54-3 n-hexane

· PAC-2:

110-54-3 n-hexane

Printing date 03/28/2019

· PAC-3:

110-54-3 n-hexane

7 Handling and storage

· Handling:

- · Precautions for safe handling
- Ensure good ventilation/exhaustion at the workplace.

Open and handle receptacle with care.

Prevent formation of aerosols.

· Information about protection against explosions and fires: Keep ignition sources away - Do not smoke. Protect against electrostatic charges. Keep respiratory protective device available.

- · Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles: Store in a cool location.
- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions:

Keep receptacle tightly sealed.

Store in cool, dry conditions in well sealed receptacles.

• Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

· Additional information about design of technical systems: No further data; see item 7.

· Control parameters

· Components with limit values that require monitoring at the workplace:

110-54-3 n-hexane

PEL Long-term value: 1800 mg/m³, 500 ppm

- REL Long-term value: 180 mg/m³, 50 ppm
- TLV Long-term value: 176 mg/m³, 50 ppm Skin; BEI

· Ingredients with biological limit values:

110-54-3 n-hexane

BEI 0.4 mg/L

Medium: urine

Time: end of shift at end of workweek

Parameter: 2.5-Hexanedione without hydrolysis

• Additional information: The lists that were valid during the creation were used as basis.

(Contd. on page 5)



Version Number 2

Version Number 2

Reviewed on 03/28/2019

Trade name: Halowax 1000 Standard (1X2 mL)

(Contd. of page 4)

US

	(Contd. of page 4
· Exposure controls	
Personal protective equipment:	
· General protective and hygienic n	isures:
Keep away from foodstuffs, beverage	
Immediately remove all soiled and o	
Wash hands before breaks and at the	
Store protective clothing separately.	
Avoid contact with the skin.	
Avoid contact with the eyes and skin	n.
Breathing equipment:	
	t instruments, the use of the product under normal laboratory conditions and
	ult in significant airborne exposures and therefore respiratory protection is not
needed.	
	re a respirator is deemed necessary, use a NIOSH or equivalent approved
device/equipment with appropriate of	
• Protection of hands:	and an and Bas cananaban
	stant contact with the chemicals or for clean-up, nitrile gloves 11-13 mil
6	nal use. The breakthrough time is 1 hr. For cleaning a spill where there is
	rubber gloves are recommended 12-15 mil thickness with breakthrough times
exceeding 4 hrs. Supplier recomme	
	ildations should be followed.
• Material of gloves	2 1.1.1
For normal use: nitrile rubber, 11-1	
For direct contact with the chemical	
· Penetration time of glove materia	
For normal use: nitrile rubber: 1 hou	
For direct contact with the chemical	: butyl rubber: >4 hours
· Eye protection:	
Tightly sealed goggles	
Tightiy sealed goggles	
Physical and chemical property	erties
Information on basis abusis allowed	
 Information on basic physical and General Information 	i chemical properties
· Appearance:	Fluid
Form:	Fluid
Color:	Colorless
· Odor:	Characteristic
· Odor threshold:	Not determined.
· pH-value:	Not determined.
• Change in condition	
Malting point/Malting range	-95 °C (-139 °F)

Melting point/Melting range: -95 °C (-139 °F) **Boiling point/Boiling range:** 69 °C (156.2 °F) · Flash point: -22 °C (-7.6 °F) Not applicable. · Flammability (solid, gaseous): (Contd. on page 6)



Printing date 03/28/2019

Reviewed on 03/28/2019

Trade name: Halowax 1000 Standard (1X2 mL)

	(Contd. of page :
· Ignition temperature:	240 °C (464 °F)
· Decomposition temperature:	Not determined.
· Auto igniting:	Product is not selfigniting.
Danger of explosion:	Product is not explosive. However, formation of explosive air/vapor mixtures are possible.
Explosion limits:	
Lower:	1.2 Vol %
Upper:	7.4 Vol %
· Vapor pressure at 20 °C (68 °F):	110 hPa (82.5 mm Hg)
Density at 20 °C (68 °F):	0.7 g/cm ³ (5.8415 lbs/gal)
Relative density	Not determined.
Vapor density	Not determined.
Evaporation rate	Not determined.
Solubility in / Miscibility with	
Water at 20 °C (68 °F):	0.1 g/l
Partition coefficient (n-octanol/wate	er): Not determined.
Viscosity:	
Dynamic:	Not determined.
Kinematic:	Not determined.
Solvent content:	
Organic solvents:	100.0 %
VOC content:	99.98 %
	999.8 g/l / 8.34 lb/gal
• Other information	No further relevant information available.

10 Stability and reactivity

• Reactivity No further relevant information available.

· Chemical stability

- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

11 Toxicological information

- · Information on toxicological effects
- Acute toxicity:

· LD/LC50 values that are relevant for classification:

ATE (Acute Toxicity Estimate)

Oral LD50 5,001 mg/kg (rat)

Dermal LD50 3,000 mg/kg (rabbit)

US

Version Number 2

Printing date 03/28/2019

Reviewed on 03/28/2019

Trade name: Halowax 1000 Standard (1X2 mL)

110-54-3 n-hexane

Printing date 03/28/2019

Oral LD50 5,000 mg/kg (rat)

Dermal LD50 3,000 mg/kg (rabbit)

· Primary irritant effect:

• on the skin: Irritant to skin and mucous membranes.

• on the eye: No irritating effect.

· Sensitization: No sensitizing effects known.

· Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations: Irritant

· Carcinogenic categories

· IARC (International Agency for Research on Cancer)

None of the ingredients is listed.

· NTP (National Toxicology Program)

None of the ingredients is listed.

· OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients is listed.

12 Ecological information

- · Toxicity
- · Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- · Behavior in environmental systems:
- · **Bioaccumulative potential** No further relevant information available.
- Mobility in soil No further relevant information available.
- · Additional ecological information:
- · General notes:

Water hazard class 2 (Self-assessment): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

- · Results of PBT and vPvB assessment
- **PBT:** Not applicable.
- · vPvB: Not applicable.
- · Other adverse effects No further relevant information available.

13 Disposal considerations

- · Waste treatment methods
- · Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packagings:
- Recommendation: Disposal must be made according to official regulations.

(Contd. on page 8)



Version Number 2

D

(Contd. of page 6)

Reviewed on 03/28/2019

Trade name: Halowax 1000 Standard (1X2 mL)

UN-Number DOT, IMDG, IATA UN1208 UN proper shipping name DOT Hexanes solution MDG IMDG HEXANES solution, MARINE POLLUTANT IATA IATA HEXANES solution Transport hazard class(cs) DOT, IATA Image: Class 3 Flammable liquids Label 3 IMDG Image: Class Image: Class 3 Flammable liquids Label 3 Image: Class 3 Flammable liquids I		(Contd. of pa
DOT, IMDG, IATA UN1208 UN proper shipping name DOT Hexanes solution MDG HEXANES solution, MARINE POLLUTANT IATA HEXANES solution Transport hazard class(es) DOT, IATA Image: Class 3 Flammable liquids Label 3 IMDG Image: Class Image: Class 3 Flammable liquids Label 3 Image: Class 3 Flammable liquids Label 3 Packing group Image: Class Dot, IATA II Environmental hazards: Product contains environmentally hazardous substances: n-hexar Marine pollutant: Symbol (fish and tree) Special precautions for user Warning: Flammable liquids Danger code (Kemler): 33 Stowage Category E Transport in bulk according to Annex II of MARPOL7378 and the IBC Code Not applicable. Transport/Additional information: On passenger aircraft/rail: 5 L On cargo aircraft only: 60 L MDG IL Excepted quantities (LO) IL Excepted quantities (EQ) IL	Transport information	
DOT, IMDG, IATA UN1208 UN proper shipping name DOT Hexanes solution MDG HEXANES solution, MARINE POLLUTANT IATA HEXANES solution Transport hazard class(es) DOT, IATA Image: Class 3 Flammable liquids Label 3 IMDG Image: Class Image: Class 3 Flammable liquids Label 3 Image: Class 3 Flammable liquids Label 3 Packing group Image: Class Dot, IATA II Environmental hazards: Product contains environmentally hazardous substances: n-hexar Marine pollutant: Symbol (fish and tree) Special precautions for user Warning: Flammable liquids Danger code (Kemler): 33 Stowage Category E Transport in bulk according to Annex II of MARPOL7378 and the IBC Code Not applicable. Transport/Additional information: On passenger aircraft/rail: 5 L On cargo aircraft only: 60 L MDG IL Excepted quantities (LO) IL Excepted quantities (EQ) IL	UN-Number	
DOT Hexanes solution MDG HEXANES solution, MARINE POLLUTANT HEXANES solution Transport hazard class(es) DOT, IATA HEXANES solution Image: Class 3 Label 3 Image: Class 3 Flammable liquids 3 Image: Class 3 Image: Class 3 Image: Class 3 Image: Class 3 Flammable liquids 3 Image: Class 3 Image: Class 3 Flammable liquids 3 Packing group Product contains environmentally hazardous substances: n-hexar Marine pollutant: Symbol (fish and tree) Special precautions for user Warning: Flammable liquids Danger code (Kemler): 33 EMS Number: F-E,S-D Stowage Category E Transport in bulk according to Annex II of MARPOL7378 and the IBC Code Not applicable. Transport/Additional information: On eargo aircraft only: 60 L DOT On cargo aircraft only: 60 L IMDG	DOT, IMDG, IATA	UN1208
DOT Hexanes solution MDG HEXANES solution, MARINE POLLUTANT HEXANES solution Transport hazard class(es) DOT, IATA HEXANES solution Image: Class 3 Label 3 Image: Class 3 Flammable liquids 3 Image: Class 3 Image: Class 3 Image: Class 3 Image: Class 3 Flammable liquids 3 Image: Class 3 Image: Class 3 Flammable liquids 3 Packing group Product contains environmentally hazardous substances: n-hexar Marine pollutant: Symbol (fish and tree) Special precautions for user Warning: Flammable liquids Danger code (Kemler): 33 EMS Number: F-E,S-D Stowage Category E Transport in bulk according to Annex II of MARPOL7378 and the IBC Code Not applicable. Transport/Additional information: On eargo aircraft only: 60 L DOT On cargo aircraft only: 60 L IMDG	UN proper shipping name	
IATA HEXANES solution Transport hazard class(es) DOT, IATA Image: Class 3 Label 3 IMDG 3 Image: Class 3 File 3 IMDG 3 Image: Class 3 File 3 Class 3 Image: Class 3 File 3 Class 3 File 3 Class 3 File 3 Class 3 Label 3 Packing group DOT, IMDG, IATA DOT, IMDG, IATA II Environmental hazards: Product contains environmentally hazardous substances: n-hexar Marine pollutant: Symbol (fish and tree) Special precautions for user Warning: Flammable liquids Dage: code (Keenler): 33 EMS Number: F-E,S-D Stowage Category E Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code Not applicable. Transport/Additional information:	DOT	Hexanes solution
Transport hazard class(es) DOT, IATA Class 3 Flammable liquids Label 3 IMDG Class 3 Flammable liquids Label 3 Class 3 Flammable liquids Label 3 Class 3 Flammable liquids Label 3 Packing group DOT, IMDG, IATA DOT, IMDG, IATA II Environmental hazards: Product contains environmentally hazardous substances: n-hexar Marine pollutant: Symbol (fish and tree) Special precautions for user Warning: Flammable liquids Danger code (Kemler): 33 Special precautions for user Warning: Flammable liquids Special precautions for user Warning: Flammable liquids Stowage Category E Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code Not applicable. Transport/Additional information: DOT On passenger aircraft/rail: 5 L On cargo aircraft only: 60 L IMDG Limited quantities (LQ) IL Excepted quantities (EQ) IL	IMDG	
DOT, IATA Class 3 Flammable liquids Label 3 IMDG Class 3 Flammable liquids Class 3 Class 3 Label 3 Packing group DOT, IMDG, IATA II Environmental hazards: Product contains environmentally hazardous substances: n-hexar Marine pollutant: Symbol (fish and tree) Special precautions for user Warning: Flammable liquids Danger code (Kemler): 33 EMS Number: F-E,S-D Stowage Category E Transport in bulk according to Annex II of MARPOL73778 and the IBC Code Not applicable. Transport in bulk according to Annex II of MARPOL73778 and the IBC Code Not applicable. Transport in bulk according to Annex II of MARPOL73778 and the IBC Code Not applicable. Transport in bulk according to Annex II of MARPOL73778 and the IBC Code Not applicable. Transport in bulk according to Annex II of MARPOL73778 and the IBC Code Not applicable. Transport in bulk according to Annex II of MARPOL73778 in the IBC Code Not applicable. Transport in bulk according to Annex II of MARPOL73778 in the IBC Code Not applicable. Transport in bulk according to Annex II of MARPOL73778 in the IBC Code Not applicable. Transport in bulk according to Annex II of MARPOL73778 in the IBC Code Not applicable. Transport in bulk according to Annex II of MARPOL73778 in the IBC Code Not applicable. Transport in bulk according to Annex II of MARPOL73778 in the IBC Code Not applicable. Transport in bulk according to Annex II of MARPOL73778 in the IBC Code Not applicable. Transport in bulk according to Annex II of MARPOL73778 in the IBC Code Not applicable. Transport in bulk according to Annex II of MARPOL73778 in the IBC Code Not applicable. Transport in bulk according to Annex II of MARPOL73778 in the IBC Code Not applicable. Transport in bulk according to Annex II of MARPOL73778 in the IBC Code Not applicable. MARPOL73778 in the IBC Code Not applicable	ΙΑΤΑ	HEXANES solution
Class 3 Flammable liquids Label 3 IMDG 3 IMDG Improvementation Improvementation 3 Packing group 3 DOT, IMDG, IATA II Environmental hazards: Product contains environmentally hazardous substances: n-hexar Marine pollutant: Symbol (fish and tree) Special precautions for user Warning: Flammable liquids Danger code (Kemler): 33 EMS Number: F-E,S-D Stowage Category E Transport in bulk according to Annex II of MARPOL73778 and the IBC Code Not applicable. Transport/Additional information: On passenger aircraft/rail: 5 L On cargo aircraft only: 60 L IMDG IL Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per inner packaging: 30 ml	Transport hazard class(es)	
Label 3 IMDG Impose Impose Impose Class 3 Flammable liquids Label 3 Packing group Jot DOT, IMDG, IATA II Environmental hazards: Product contains environmentally hazardous substances: n-hexar Marine pollutant: Symbol (fish and tree) Special precautions for user Warning: Flammable liquids Danger code (Kemler): 33 EMS Number: F-E,S-D Stowage Category E Transport in bulk according to Annex II of Not applicable. Transport/Additional information: DOT Quantity limitations On passenger aircraft/rail: 5 L On cargo aircraft only: 60 L IMDG Limited quantities (LQ) IL Excepted quantities (LQ) IL Excepted quantities (EQ) Code: E2 Maximum net quantity per inner packaging: 30 ml	DOT, IATA	
Label 3 IMDG Impose Impose Impose Class 3 Flammable liquids Label 3 Packing group Jot DOT, IMDG, IATA II Environmental hazards: Product contains environmentally hazardous substances: n-hexar Marine pollutant: Symbol (fish and tree) Special precautions for user Warning: Flammable liquids Danger code (Kemler): 33 EMS Number: F-E,S-D Stowage Category E Transport in bulk according to Annex II of Not applicable. Transport/Additional information: DOT Quantity limitations On passenger aircraft/rail: 5 L On cargo aircraft only: 60 L IMDG Limited quantities (LQ) IL Excepted quantities (LQ) IL Excepted quantities (EQ) Code: E2 Maximum net quantity per inner packaging: 30 ml		
Label 3 IMDG Impose Impose Impose Class 3 Flammable liquids Label 3 Packing group Jot DOT, IMDG, IATA II Environmental hazards: Product contains environmentally hazardous substances: n-hexar Marine pollutant: Symbol (fish and tree) Special precautions for user Warning: Flammable liquids Danger code (Kemler): 33 EMS Number: F-E,S-D Stowage Category E Transport in bulk according to Annex II of Not applicable. Transport/Additional information: DOT Quantity limitations On passenger aircraft/rail: 5 L On cargo aircraft only: 60 L IMDG Limited quantities (LQ) IL Excepted quantities (LQ) IL Excepted quantities (EQ) Code: E2 Maximum net quantity per inner packaging: 30 ml		
Label 3 IMDG Impose Impose Impose Class 3 Flammable liquids Label 3 Packing group Jot DOT, IMDG, IATA II Environmental hazards: Product contains environmentally hazardous substances: n-hexar Marine pollutant: Symbol (fish and tree) Special precautions for user Warning: Flammable liquids Danger code (Kemler): 33 EMS Number: F-E,S-D Stowage Category E Transport in bulk according to Annex II of Not applicable. Transport/Additional information: DOT Quantity limitations On passenger aircraft/rail: 5 L On cargo aircraft only: 60 L IMDG Limited quantities (LQ) IL Excepted quantities (LQ) IL Excepted quantities (EQ) Code: E2 Maximum net quantity per inner packaging: 30 ml	*	
Label 3 IMDG Impose Impose Impose Class 3 Flammable liquids Label 3 Packing group Jot DOT, IMDG, IATA II Environmental hazards: Product contains environmentally hazardous substances: n-hexar Marine pollutant: Symbol (fish and tree) Special precautions for user Warning: Flammable liquids Danger code (Kemler): 33 EMS Number: F-E,S-D Stowage Category E Transport in bulk according to Annex II of Not applicable. Transport/Additional information: DOT Quantity limitations On passenger aircraft/rail: 5 L On cargo aircraft only: 60 L IMDG Limited quantities (LQ) IL Excepted quantities (LQ) IL Excepted quantities (EQ) Code: E2 Maximum net quantity per inner packaging: 30 ml		
IMDG View View Class 3 Flammable liquids Label 3 Packing group Jot, IATA DOT, IMDG, IATA II Environmental hazards: Product contains environmentally hazardous substances: n-hexar Marine pollutant: Symbol (fish and tree) Special precautions for user Warning: Flammable liquids Danger code (Kemler): 33 EMS Number: F-E,S-D Stowage Category E Transport in bulk according to Annex II of Mot applicable. MARPOL73/78 and the IBC Code Not applicable. Transport/Additional information: On passenger aircraft/rail: 5 L On cargo aircraft only: 60 L DOT Quantity limitations On passenger aircraft/rail: 5 L On cargo aircraft only: 60 L IMDG Lint Excepted quantities (LQ) IL Excepted quantities (EQ) Code: E2 Maximum net quantity per inner packaging: 30 ml		• •
Class 3 Flammable liquids Label 3 Packing group Jong DOT, IMDG, IATA II Environmental hazards: Product contains environmentally hazardous substances: n-hexar Marine pollutant: Symbol (fish and tree) Special precautions for user Warning: Flammable liquids Danger code (Kemler): 33 EMS Number: F-E,S-D Stowage Category E Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code MARPOL73/78 and the IBC Code Not applicable. Transport/Additional information: DOn passenger aircraft/rail: 5 L On cargo aircraft only: 60 L IMDG IL Limited quantities (LQ) IL Excepted quantities (EQ) Code: E2 Maximum net quantity per inner packaging: 30 ml		5
Label3Packing group DOT, IMDG, IATAIIEnvironmental hazards:Product contains environmentally hazardous substances: n-hexar Symbol (fish and tree)Special precautions for userWarning: Flammable liquidsDanger code (Kemler):33EMS Number:F-E,S-DStowage CategoryETransport in bulk according to Annex II of MARPOL73/78 and the IBC CodeNot applicable.Transport/Additional information:On passenger aircraft/rail: 5 L On cargo aircraft only: 60 LIMDG Limited quantities (LQ)IL Excepted quantities (EQ)Code: E2 Maximum net quantity per inner packaging: 30 ml	IMDG	
Label3Packing group DOT, IMDG, IATAIIEnvironmental hazards:Product contains environmentally hazardous substances: n-hexar Symbol (fish and tree)Special precautions for userWarning: Flammable liquidsDanger code (Kemler):33EMS Number:F-E,S-DStowage CategoryETransport in bulk according to Annex II of MARPOL73/78 and the IBC CodeNot applicable.Transport/Additional information:On passenger aircraft/rail: 5 L On cargo aircraft only: 60 LIMDG Limited quantities (LQ)IL Excepted quantities (EQ)Code: E2 Maximum net quantity per inner packaging: 30 ml		
Label3Packing group DOT, IMDG, IATAIIEnvironmental hazards:Product contains environmentally hazardous substances: n-hexar Symbol (fish and tree)Special precautions for userWarning: Flammable liquidsDanger code (Kemler):33EMS Number:F-E,S-DStowage CategoryETransport in bulk according to Annex II of MARPOL73/78 and the IBC CodeNot applicable.Transport/Additional information:On passenger aircraft/rail: 5 L On cargo aircraft only: 60 LIMDG Limited quantities (LQ)IL Excepted quantities (EQ)Code: E2 Maximum net quantity per inner packaging: 30 ml		
Label3Packing group DOT, IMDG, IATAIIEnvironmental hazards:Product contains environmentally hazardous substances: n-hexar Symbol (fish and tree)Special precautions for userWarning: Flammable liquidsDanger code (Kemler):33EMS Number:F-E,S-DStowage CategoryETransport in bulk according to Annex II of MARPOL73/78 and the IBC CodeNot applicable.Transport/Additional information:On passenger aircraft/rail: 5 L On cargo aircraft only: 60 LIMDG Limited quantities (LQ)IL Excepted quantities (EQ)Code: E2 Maximum net quantity per inner packaging: 30 ml		
Label3Packing group DOT, IMDG, IATAIIEnvironmental hazards:Product contains environmentally hazardous substances: n-hexar Symbol (fish and tree)Special precautions for userWarning: Flammable liquidsDanger code (Kemler):33EMS Number:F-E,S-DStowage CategoryETransport in bulk according to Annex II of MARPOL73/78 and the IBC CodeNot applicable.Transport/Additional information:On passenger aircraft/rail: 5 L On cargo aircraft only: 60 LIMDG Limited quantities (LQ)IL Excepted quantities (EQ)Code: E2 Maximum net quantity per inner packaging: 30 ml	Class	3 Flammable liquids
DOT, IMDG, IATAIIEnvironmental hazards: Marine pollutant:Product contains environmentally hazardous substances: n-hexar Symbol (fish and tree)Special precautions for user Danger code (Kemler): Stowage CategoryWarning: Flammable liquids 33 F-E,S-D EStowage CategoryF-E,S-D ETransport in bulk according to Annex II of MARPOL73/78 and the IBC CodeNot applicable.Transport/Additional information: DOT Quantity limitationsOn passenger aircraft/rail: 5 L On cargo aircraft only: 60 LIMDG Limited quantities (LQ)IL Code: E2 Maximum net quantity per inner packaging: 30 ml	Label	-
DOT, IMDG, IATAIIEnvironmental hazards: Marine pollutant:Product contains environmentally hazardous substances: n-hexar Symbol (fish and tree)Special precautions for user Danger code (Kemler): Stowage CategoryWarning: Flammable liquids 33 F-E,S-D EStowage CategoryF-E,S-D ETransport in bulk according to Annex II of MARPOL73/78 and the IBC CodeNot applicable.Transport/Additional information: DOT Quantity limitationsOn passenger aircraft/rail: 5 L On cargo aircraft only: 60 LIMDG Limited quantities (LQ)IL Code: E2 Maximum net quantity per inner packaging: 30 ml	Packing group	
Marine pollutant:Symbol (fish and tree)Special precautions for userWarning: Flammable liquidsDanger code (Kemler):33EMS Number:F-E,S-DStowage CategoryETransport in bulk according to Annex II of MARPOL73/78 and the IBC CodeNot applicable.Transport/Additional information:On passenger aircraft/rail: 5 L On cargo aircraft only: 60 LIMDG Limited quantities (LQ)1L Code: E2 Maximum net quantity per inner packaging: 30 ml	DOT, IMDG, IATA	II
Special precautions for user Warning: Flammable liquids Danger code (Kemler): 33 EMS Number: F-E,S-D Stowage Category E Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code Not applicable. Transport/Additional information: DOT Quantity limitations On passenger aircraft/rail: 5 L On cargo aircraft only: 60 L IMDG IL Limited quantities (LQ) 1L Excepted quantities (EQ) Code: E2 Maximum net quantity per inner packaging: 30 ml	Environmental hazards:	Product contains environmentally hazardous substances: n-hexan
Danger code (Kemler):33EMS Number:F-E,S-DStowage CategoryETransport in bulk according to Annex II of MARPOL73/78 and the IBC CodeNot applicable.Transport/Additional information:Not applicable.DOT Quantity limitationsOn passenger aircraft/rail: 5 L On cargo aircraft only: 60 LIMDG Limited quantities (LQ)1L Code: E2 Maximum net quantity per inner packaging: 30 ml	Marine pollutant:	
Danger code (Kemler):33EMS Number:F-E,S-DStowage CategoryETransport in bulk according to Annex II of MARPOL73/78 and the IBC CodeNot applicable.Transport/Additional information:Not applicable.DOT Quantity limitationsOn passenger aircraft/rail: 5 L On cargo aircraft only: 60 LIMDG Limited quantities (LQ)1L Code: E2 Maximum net quantity per inner packaging: 30 ml	Special precautions for user	Warning: Flammable liquids
Stowage CategoryETransport in bulk according to Annex II of MARPOL73/78 and the IBC CodeNot applicable.Transport/Additional information:Not applicable.DOT Quantity limitationsOn passenger aircraft/rail: 5 L On cargo aircraft only: 60 LIMDG Limited quantities (LQ)1L Code: E2 Maximum net quantity per inner packaging: 30 ml	Danger code (Kemler):	33
Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code Not applicable. Transport/Additional information: Not applicable. DOT Quantity limitations On passenger aircraft/rail: 5 L On cargo aircraft only: 60 L IMDG Limited quantities (LQ) 1L Code: E2 Maximum net quantity per inner packaging: 30 ml		F-E,S-D
MARPOL73/78 and the IBC Code Not applicable. Transport/Additional information: DOT DOT On passenger aircraft/rail: 5 L Quantity limitations On passenger aircraft/rail: 5 L IMDG IL Excepted quantities (LQ) 1L Excepted quantities (EQ) Code: E2 Maximum net quantity per inner packaging: 30 ml	Stowage Category	E
Transport/Additional information: DOT Quantity limitations On passenger aircraft/rail: 5 L On cargo aircraft only: 60 L IMDG Limited quantities (LQ) Excepted quantities (EQ) Code: E2 Maximum net quantity per inner packaging: 30 ml		
DOT On passenger aircraft/rail: 5 L Quantity limitations On passenger aircraft/rail: 5 L On cargo aircraft only: 60 L IMDG Limited quantities (LQ) 1L Excepted quantities (EQ) Code: E2 Maximum net quantity per inner packaging: 30 ml		Not applicable.
Quantity limitations On passenger aircraft/rail: 5 L On cargo aircraft only: 60 L IMDG Limited quantities (LQ) 1L Excepted quantities (EQ) Code: E2 Maximum net quantity per inner packaging: 30 ml	Transport/Additional information:	
On cargo aircraft only: 60 L IMDG Limited quantities (LQ) 1L Excepted quantities (EQ) Code: E2 Maximum net quantity per inner packaging: 30 ml	DOT	
IMDG Limited quantities (LQ) 1L Excepted quantities (EQ) Code: E2 Maximum net quantity per inner packaging: 30 ml	Quantity limitations	
Limited quantities (LQ)1LExcepted quantities (EQ)Code: E2Maximum net quantity per inner packaging: 30 ml		On cargo aircraft only: 60 L
Excepted quantities (EQ) Code: E2 Maximum net quantity per inner packaging: 30 ml	IMDG	
Maximum net quantity per inner packaging: 30 ml		
	Excepted quantities (EQ)	
Maximum net quantity per outer packaging: 500 ml		
		Maximum net quantity per outer packaging: 500 ml



Printing date 03/28/2019

Version Number 2

017

Reviewed on 03/28/2019

Trade name: Halowax 1000 Standard (1X2 mL)

· UN "Model Regulation":

Printing date 03/28/2019

UN 1208 HEXANES SOLUTION, 3, II, ENVIRONMENTALLY HAZARDOUS

15 Regulatory information

Safety, health and environmental regulations/legislation specific for the substance or mixture · Sara

· Section 355 (extremely hazardous substances):

None of the ingredients is listed.

· Section 313 (Specific toxic chemical listings):

110-54-3 n-hexane

· TSCA (Toxic Substances Control Act):

110-54-3 n-hexane

· Proposition 65

· Chemicals known to cause cancer:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for females:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for males:

110-54-3 n-hexane

· Chemicals known to cause developmental toxicity:

None of the ingredients is listed.

· Carcinogenic categories

· EPA (Environmental Protection Agency)

110-54-3 n-hexane

· TLV (Threshold Limit Value established by ACGIH)

None of the ingredients is listed.

· NIOSH-Ca (National Institute for Occupational Safety and Health)

None of the ingredients is listed.

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

The information contained in this document is based on Agilent's state of knowledge at the time of preparation. No warranty as to its accurateness, completeness or suitability for a particular purpose is expressed or implied.

· Department issuing SDS: Document Control / Regulatory

- · Contact: regulatory@ultrasci.com
- · Date of preparation / last revision 03/28/2019 / 1
- · Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

- DOT: US Department of Transportation
- IATA: International Air Transport Association

(Contd. on page 10)

Π



Version Number 2

(Contd. of page 8)

Version Number 2

Reviewed on 03/28/2019

Trade name: Halowax 1000 Standard (1X2 mL)

	(Contd. of page 9)
ACGIH: American Conference of Governmental Industrial Hygienists	
EINECS: European Inventory of Existing Commercial Chemical Substances	
ELINCS: European List of Notified Chemical Substances	
CAS: Chemical Abstracts Service (division of the American Chemical Society)	
NFPA: National Fire Protection Association (USA)	
HMIS: Hazardous Materials Identification System (USA)	
VOC: Volatile Organic Compounds (USA, EU)	
LC50: Lethal concentration, 50 percent	
LD50: Lethal dose, 50 percent	
PBT: Persistent, Bioaccumulative and Toxic	
vPvB: very Persistent and very Bioaccumulative	
NIOSH: National Institute for Occupational Safety	
OSHA: Occupational Safety & Health	
TLV: Threshold Limit Value	
PEL: Permissible Exposure Limit	
REL: Recommended Exposure Limit	
BEI: Biological Exposure Limit	
Flam. Liq. 2: Flammable liquids – Category 2	
Skin Irrit. 2: Skin corrosion/irritation – Category 2	
Repr. 2: Reproductive toxicity – Category 2	
STOT SE 3: Specific target organ toxicity (single exposure) – Category 3	
STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2	
Asp. Tox. 1: Aspiration hazard – Category 1	
* Data compared to the previous version altered.	
	US
	-03



Printing date 03/28/2019