

Printing date 03/30/2019 Version Number 4 Reviewed on 03/30/2019

1 Identification

· Product identifier

· Trade name: Arsenic AA Standard (125 mL)

· Part number: IAA-233

· Application of the substance / the mixture Reagents and Standards for Analytical Chemical Laboratory Use

· Details of the supplier of the safety data sheet

· Manufacturer/Supplier: Agilent Technologies, Inc.

5301 Stevens Creek Blvd. Santa Clara, CA 95051 USA

· Information department:

Telephone: 800-227-9770

e-mail: pdl-msds author@agilent.com

· Emergency telephone number: CHEMTREC®: 1-800-424-9300

2 Hazard(s) identification

· Classification of the substance or mixture



GHS08 Health hazard

Carc. 1A H350 May cause cancer.



GHS07

Skin Irrit. 2 H315 Causes skin irritation.

Eye Irrit. 2A H319 Causes serious eye irritation.

- · Label elements
- · GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS).
- · Hazard pictograms





GHS07

GHS08

- · Signal word Danger
- · Hazard-determining components of labeling:

diarsenic trioxide

· Hazard statements

Causes skin irritation.

Causes serious eye irritation.

May cause cancer.

· Precautionary statements

Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood.

Wash thoroughly after handling.

Wear protective gloves/protective clothing/eye protection/face protection.

(Contd. on page 2)



Printing date 03/30/2019 Version Number 4 Reviewed on 03/30/2019

Trade name: Arsenic AA Standard (125 mL)

(Contd. of page 1)

If on skin: Wash with plenty of water.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.

Continue rinsing.

IF exposed or concerned: Get medical advice/attention.

Specific treatment (see on this label).

Take off contaminated clothing and wash it before reuse.

If skin irritation occurs: Get medical advice/attention.

If eye irritation persists: Get medical advice/attention.

Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

- · Classification system:
- · NFPA ratings (scale 0 4)



Health = 2Fire = 0Reactivity = 0

· HMIS-ratings (scale 0 - 4)



Health = *2Fire = 0

- · Other hazards
- · Results of PBT and vPvB assessment
- · **PBT**: Not applicable.
- · vPvB: Not applicable.

3 Composition/information on ingredients

- · Chemical characterization: Mixtures
- **Description:** Mixture of the substances listed below with nonhazardous additions.

· Dangerou	s components:	
7697-37-2	nitric acid	1.979%
1327-53-3	diarsenic trioxide	0.132%

4 First-aid measures

- · Description of first aid measures
- · General information: Immediately remove any clothing soiled by the product.
- · After inhalation: In case of unconsciousness place patient stably in side position for transportation.
- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

- · After swallowing: If symptoms persist consult doctor.
- · Information for doctor:
- · Most important symptoms and effects, both acute and delayed No further relevant information available.

(Contd. on page 3)



Printing date 03/30/2019 Version Number 4 Reviewed on 03/30/2019

Trade name: Arsenic AA Standard (125 mL)

(Contd. of page 2)

· Indication of any immediate medical attention and special treatment needed No further relevant information available.

5 Fire-fighting measures

- · Extinguishing media
- · Suitable extinguishing agents: Use fire fighting measures that suit the environment.
- Special hazards arising from the substance or mixture No further relevant information available.
- · Advice for firefighters
- · Protective equipment: No special measures required.

6 Accidental release measures

- · Personal precautions, protective equipment and emergency procedures Not required.
- Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- · Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

· Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

· Protective Action Criteria for Chemicals

· PAC-1:		
7697-37-2		0.16 ppm
1327-53-3	diarsenic trioxide	0.27 mg/m^3
· PAC-2:		
7697-37-2		24 ppm
1327-53-3	diarsenic trioxide	3.0 mg/m^3
· PAC-3:		
7697-37-2	nitric acid	92 ppm
1327-53-3	diarsenic trioxide	9.1 mg/m ³

7 Handling and storage

- · Handling:
- · Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Open and handle receptacle with care.

- Information about protection against explosions and fires: Keep respiratory protective device available.
- · Conditions for safe storage, including any incompatibilities
- · Storage:
- Requirements to be met by storerooms and receptacles: No special requirements.
- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions: Keep receptacle tightly sealed.

(Contd. on page 4)

(Contd. of page 3)



Safety Data Sheet acc. to OSHA HCS

Printing date 03/30/2019 Version Number 4 Reviewed on 03/30/2019

Trade name: Arsenic AA Standard (125 mL)

· Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

- · Additional information about design of technical systems: No further data; see item 7.
- · Control parameters

· Components with limit	llues that require monitoring at the workplace:
7697-37-2 nitric acid	

PEL	Long-term value: 5 mg/m ³ , 2 ppm
REL	Short-term value: 10 mg/m³, 4 ppm
	Long-term value: 5 mg/m³, 2 ppm
TLV	Short-term value: 10 mg/m³, 4 ppm

1327-53-3 diarsenic trioxide

PEL	Long-term value: 0.01 mg/m ³
	Long-term value: 0.01 mg/m ³ as As; 29CFR1910.1018
REL	Ceiling limit value: 0.002 mg/m³
	as As; 15min; See Pocket Guide App. A
TOT 3.7	T / 1 0.01 / 2

Long-term value: 5.2 mg/m³, 2 ppm

TLV Long-term value: 0.01 mg/m³

- · Additional information: The lists that were valid during the creation were used as basis.
- · Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Store protective clothing separately.

Avoid contact with the eyes and skin.

· Breathing equipment:

When used as intended with Agilent instruments, the use of the product under normal laboratory conditions and with standard practices does not result in significant airborne exposures and therefore respiratory protection is not needed.

Under an emergency condition where a respirator is deemed necessary, use a NIOSH or equivalent approved device/equipment with appropriate organic or acid gas cartridge.

Protection of hands:

Although not recommended for constant contact with the chemicals or for clean-up, nitrile gloves 11-13 mil thickness are recommended for normal use. The breakthrough time is 1 hr. For cleaning a spill where there is direct contact of the chemical, butyl rubber gloves are recommended 12-15 mil thickness with breakthrough times exceeding 4 hrs. Supplier recommendations should be followed.

· Material of gloves

For normal use: nitrile rubber, 11-13 mil thickness

For direct contact with the chemical: butyl rubber, 12-15 mil thickness

· Penetration time of glove material

For normal use: nitrile rubber: 1 hour

For direct contact with the chemical: butyl rubber: >4 hours

(Contd. on page 5)




Printing date 03/30/2019 Version Number 4 Reviewed on 03/30/2019

Trade name: Arsenic AA Standard (125 mL)

· Eye protection:

(Contd. of page 4)



9 Physical and chemical proper	ties				
Information on basic physical and c	chemical properties				
General Information	r · r				
· Appearance:					
Form: Fluid					
Color:	Colorless				
· Odor:	Odorless				
· Odor threshold:	reshold: Not determined.				
· pH-value:	Not determined.				
· Change in condition					
Melting point/Melting range:	Undetermined.				
Boiling point/Boiling range:	100 °C (212 °F)				
· Flash point:	Not applicable.				
· Flammability (solid, gaseous):	Not applicable.				
· Decomposition temperature:	Not determined.				
· Auto igniting: Product is not selfigniting.					
· Danger of explosion:	nger of explosion: Product does not present an explosion hazard.				
· Explosion limits:					
Lower: Not determined.					
Upper:	Not determined.				
· Vapor pressure at 20 °C (68 °F):	23 hPa (17.3 mm Hg)				
Density at 20 °C (68 °F):	1.00995 g/cm ³ (8.42803 lbs/gal)				
· Relative density	Not determined.				
· Vapor density	Not determined.				
· Evaporation rate	Not determined.				
· Solubility in / Miscibility with					
Water:	Not miscible or difficult to mix.				
· Partition coefficient (n-octanol/wate	er): Not determined.				
· Viscosity:					
Dynamic:	Not determined.				
Kinematic:	Not determined.				
· Solvent content:					
Water: 97.9 %					
VOC content: 0.00 %					
	0.0 g/l / 0.00 lb/gal				

(Contd. on page 6)



Printing date 03/30/2019 Version Number 4 Reviewed on 03/30/2019

Trade name: Arsenic AA Standard (125 mL)

(Contd. of page 5)

Solids content: 0.1 %

• Other information No further relevant information available.

10 Stability and reactivity

- · Reactivity No further relevant information available.
- · Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- **Incompatible materials:** No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

11 Toxicological information

- Information on toxicological effects
- · Acute toxicity:

· LD/LC50 va	lues that are	relevant for o	classification:

ATE (Acute Toxicity Estimate)

Oral LD50 15,152 mg/kg (rat) Inhalative LC50/4 h 3,386 mg/L (rat)

7697-37-2 nitric acid

Inhalative LC50/4 h 67 mg/L (rat)

1327-53-3 diarsenic trioxide

Oral LD50 20 mg/kg (rat)

- · Primary irritant effect:
- on the skin: Irritant to skin and mucous membranes.
- · on the eye: Irritating effect.
- · Sensitization: No sensitizing effects known.
- · Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations: Irritant

· Carcinogenic categories

· IARC (International Agency for Research on Cancer)

1327-53-3 diarsenic trioxide

1

· NTP (National Toxicology Program)

1327-53-3 diarsenic trioxide

K

· OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients is listed.

US



Printing date 03/30/2019 Version Number 4 Reviewed on 03/30/2019

Trade name: Arsenic AA Standard (125 mL)

(Contd. of page 6)

12 Ecological information

- · Toxicity
- · Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.
- · Additional ecological information:
- · General notes:

Water hazard class 3 (Self-assessment): extremely hazardous for water

Do not allow product to reach ground water, water course or sewage system, even in small quantities.

Danger to drinking water if even extremely small quantities leak into the ground.

- · Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.
- · Other adverse effects No further relevant information available.

13 Disposal considerations

- · Waste treatment methods
- · Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packagings:
- · Recommendation: Disposal must be made according to official regulations.

4 4 6			r e	. •
4.	ransnor	t ini	orma	Ton

· UN-Number · DOT, IMDG, IATA	UN3264
· UN proper shipping name	Corrosive liquid, acidic, inorganic, n.o.s. (Nitric acid)
· DOT	CORROSIVE LIQUID, ACIDIC, INORGANIC, N.O.S. (NITRIC
· IMDG, IATA	ACID)

- · Transport hazard class(es)
- · DOT, IMDG, IATA



· Class · Label	8 Corrosive substances 8		
· Packing group · DOT, IMDG, IATA	III		
· Environmental hazards:	Not applicable.		

(Contd. on page 8)



Printing date 03/30/2019 Version Number 4 Reviewed on 03/30/2019

Trade name: Arsenic AA Standard (125 mL)

(Contd. of page 7)

Special precautions for user
 Danger code (Kemler):
 EMS Number:
 Segregation groups
 Stowage Category
 Warning: Corrosive substances
 80
 F-A,S-B
 Acids
 A

• Stowage Code SW2 Clear of living quarters.

· Transport in bulk according to Annex II of

MARPOL73/78 and the IBC Code Not applicable.

· Transport/Additional information:

· DOT

• Quantity limitations On passenger aircraft/rail: 5 L

On cargo aircraft only: 60 L

· IMDG

Limited quantities (LQ)Excepted quantities (EQ)Code: E1

Maximum net quantity per inner packaging: 30 ml

Maximum net quantity per outer packaging: 1000 ml

· UN "Model Regulation": UN 3264 CORROSIVE LIQUID, ACIDIC, INORGANIC, N.O.S.

(NITRIC ACID), 8, III

15 Regulatory information

- · Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Sara

· Section 355	(extremely	hazardo	us subs	tances):
---------------	------------	---------	---------	----------

7697-37-2 nitric acid

1327-53-3 diarsenic trioxide

· Section 313 (Specific toxic chemical listings):

7697-37-2 nitric acid

1327-53-3 diarsenic trioxide

· TSCA (Toxic Substances Control Act):

All ingredients are listed.

· Proposition 65

· Chemicals known to cause cancer:

1327-53-3 diarsenic trioxide

· Chemicals known to cause reproductive toxicity for females:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for males:

None of the ingredients is listed.

· Chemicals known to cause developmental toxicity:

1327-53-3 diarsenic trioxide

(Contd. on page 9)



Printing date 03/30/2019 Version Number 4 Reviewed on 03/30/2019

Trade name: Arsenic AA Standard (125 mL)

(Contd. of page 8)

· Carcinogenic categories

· EPA (Environmental Protection Agency)

1327-53-3 diarsenic trioxide

A

TLV (Threshold Limit Value established by ACGIH)

1327-53-3 diarsenic trioxide

A1

· NIOSH-Ca (National Institute for Occupational Safety and Health)

None of the ingredients is listed.

- · National regulations:
- · Additional classification according to Decree on Hazardous Materials:

Carcinogenic hazardous material group III (dangerous).

Information about limitation of use:

Workers are not allowed to be exposed to the hazardous carcinogenic materials contained in this preparation. Exceptions can be made by the authorities in certain cases.

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

The information contained in this document is based on Agilent's state of knowledge at the time of preparation. No warranty as to its accurateness, completeness or suitability for a particular purpose is expressed or implied.

- · Department issuing SDS: Document Control / Regulatory
- · Contact: regulatory@ultrasci.com
- · Date of preparation / last revision 03/30/2019 / 3
- · Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

ACGIH: American Conference of Governmental Industrial Hygienists

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety & Health

TLV: Threshold Limit Value

PEL: Permissible Exposure Limit

REL: Recommended Exposure Limit

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Irrit. 2A: Serious eye damage/eye irritation - Category 2A

Carc. 1A: Carcinogenicity - Category 1A

* Data compared to the previous version altered.

US