Printing date 03/30/2019

Agilent

Version Number 4

Reviewed on 03/30/2019

# **1** Identification

· Product identifier

· Trade name: Tellurium AA Standard (125 mL)

- · Part number: IAA-252
- · Application of the substance / the mixture Reagents and Standards for Analytical Chemical Laboratory Use
- · Details of the supplier of the safety data sheet


· Manufacturer/Supplier: Agilent Technologies, Inc. 5301 Stevens Creek Blvd. Santa Clara, CA 95051 USA

### · Information department:

Telephone: 800-227-9770 e-mail: pdl-msds author@agilent.com · Emergency telephone number: CHEMTREC®: 1-800-424-9300

# 2 Hazard(s) identification

· Classification of the substance or mixture



Eye Dam. 1 H318 Causes serious eye damage.

## · Label elements

• GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS). · Hazard pictograms



· Signal word Danger

- · Hazard-determining components of labeling: hydrochloric acid
- · Hazard statements
- Causes serious eye damage.
- · Precautionary statements

Wear eye protection / face protection.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

- Immediately call a poison center/doctor.
- · Classification system:
- · NFPA ratings (scale 0 4)



(Contd. on page 2)

US

Reviewed on 03/30/2019

Trade name: Tellurium AA Standard (125 mL)

(Contd. of page 1)

· HMIS-ratings (scale 0 - 4)

HEALTH \*3 Health = \*30 Fire = 0**REACTIVITY** Reactivity = 0

· Other hazards

FIRE

Printing date 03/30/2019

- · Results of PBT and vPvB assessment
- **PBT:** Not applicable.
- · vPvB: Not applicable.

## **3** Composition/information on ingredients

· Chemical characterization: Mixtures

· Description: Mixture of the substances listed below with nonhazardous additions.

### · Dangerous components:

7647-01-0 hydrochloric acid

## **4 First-aid measures**

- · Description of first aid measures
- · After inhalation: Supply fresh air; consult doctor in case of complaints.
- · After skin contact: Generally the product does not irritate the skin.
- After eye contact: Rinse opened eye for several minutes under running water. Then consult a doctor.
- · After swallowing: If symptoms persist consult doctor.
- · Information for doctor:
- Most important symptoms and effects, both acute and delayed No further relevant information available.
- · Indication of any immediate medical attention and special treatment needed

No further relevant information available.

## **5** Fire-fighting measures

- · Extinguishing media
- Suitable extinguishing agents: Use fire fighting measures that suit the environment.
- Special hazards arising from the substance or mixture No further relevant information available.
- · Advice for firefighters
- · Protective equipment: No special measures required.

## **6** Accidental release measures

- · Personal precautions, protective equipment and emergency procedures Wear protective equipment. Keep unprotected persons away.
- Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- · Methods and material for containment and cleaning up: Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
- Use neutralizing agent.

Dispose contaminated material as waste according to item 13.

(Contd. on page 3)

US



Version Number 4



4.38%

Version Number 4

Reviewed on 03/30/2019

Trade name: Tellurium AA Standard (125 mL)

(Contd. of page 2)

· Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information. • Protective Action Criteria for Chemicals

| Trotective |                   |                        |
|------------|-------------------|------------------------|
| · PAC-1:   |                   |                        |
| 7647-01-0  | hydrochloric acid | 1.8 ppm                |
| 7446-07-3  | tellurium dioxide | 0.38 mg/m <sup>3</sup> |
| · PAC-2:   |                   |                        |
| 7647-01-0  | hydrochloric acid | 22 ppm                 |
| 7446-07-3  | tellurium dioxide | 4.3 mg/m <sup>3</sup>  |
| · PAC-3:   |                   |                        |
| 7647-01-0  | hydrochloric acid | 100 ppm                |
| 7446-07-3  | tellurium dioxide | 26 mg/m <sup>3</sup>   |
| 7446-07-3  | tellurium dioxide | 26 mg/1                |

## 7 Handling and storage

· Handling:

- · Precautions for safe handling No special precautions are necessary if used correctly.
- · Information about protection against explosions and fires: No special measures required.
- · Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles: No special requirements.
- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions: Keep receptacle tightly sealed.
- Specific end use(s) No further relevant information available.

## 8 Exposure controls/personal protection

• Additional information about design of technical systems: No further data; see item 7.

· Control parameters

## · Components with limit values that require monitoring at the workplace:

## 7647-01-0 hydrochloric acid

PEL Ceiling limit value: 7 mg/m<sup>3</sup>, 5 ppm

REL Ceiling limit value: 7 mg/m<sup>3</sup>, 5 ppm

TLV Ceiling limit value: 2.98 mg/m<sup>3</sup>, 2 ppm

• Additional information: The lists that were valid during the creation were used as basis.

## · Exposure controls

- · Personal protective equipment:
- · General protective and hygienic measures:
- Keep away from foodstuffs, beverages and feed.
- Immediately remove all soiled and contaminated clothing.
- Wash hands before breaks and at the end of work.
- Avoid contact with the eyes.
- Avoid contact with the eyes and skin.



Printing date 03/30/2019

Reviewed on 03/30/2019

## Trade name: Tellurium AA Standard (125 mL)

(Contd. of page 3)

### · Breathing equipment:

When used as intended with Agilent instruments, the use of the product under normal laboratory conditions and with standard practices does not result in significant airborne exposures and therefore respiratory protection is not needed.

Under an emergency condition where a respirator is deemed necessary, use a NIOSH or equivalent approved device/equipment with appropriate organic or acid gas cartridge.

### · Protection of hands:

Although not recommended for constant contact with the chemicals or for clean-up, nitrile gloves 11-13 mil thickness are recommended for normal use. The breakthrough time is 1 hr. For cleaning a spill where there is direct contact of the chemical, butyl rubber gloves are recommended 12-15 mil thickness with breakthrough times exceeding 4 hrs. Supplier recommendations should be followed.

### · Material of gloves

For normal use: nitrile rubber, 11-13 mil thickness

For direct contact with the chemical: butyl rubber, 12-15 mil thickness

### · Penetration time of glove material

For normal use: nitrile rubber: 1 hour

For direct contact with the chemical: butyl rubber: >4 hours

• Eye protection:



Tightly sealed goggles

| 9 Physical and chemical properties  |   |  |
|---|---|--|
| · Information on basic physical and c<br>· General Information  | chemical properties                           |  |
| · Appearance:<br>Form:  | Fluid   |  |
| Color:  | Colorless                                     |  |
| · Odor:   | Odorless                                      |  |
| · Odor threshold:   | Not determined.                               |  |
| · pH-value:   | Not determined.                               |  |
| <ul> <li>Change in condition</li> <li>Melting point/Melting range:</li> <li>Boiling point/Boiling range:</li> </ul> | Undetermined.<br>100 °C (212 °F)              |  |
| · Flash point:  | Not applicable.                               |  |
| · Flammability (solid, gaseous):  | Not applicable.                               |  |
| · Decomposition temperature:  | Not determined.                               |  |
| · Auto igniting:  | Product is not selfigniting.                  |  |
| · Danger of explosion:  | Product does not present an explosion hazard. |  |
| · Explosion limits:   |   |  |
| Lower:  | Not determined.                               |  |
| Upper:  | Not determined.                               |  |
| · Vapor pressure at 20 °C (68 °F):  | 23 hPa (17.3 mm Hg)                           |  |
|   | (Contd. on page                               |  |



Printing date 03/30/2019

Version Number 4

Reviewed on 03/30/2019

Trade name: Tellurium AA Standard (125 mL)

|                                      |   | (Contd. of page |
|--------------------------------------|---|-----------------|
| · Density at 20 °C (68 °F):          | 1.01307 g/cm <sup>3</sup> (8.45407 lbs/gal) |                 |
| · Relative density                   | Not determined.                             |                 |
| · Vapor density                      | Not determined.                             |                 |
| · Evaporation rate                   | Not determined.                             |                 |
| · Solubility in / Miscibility with   |   |                 |
| Water:                               | Not miscible or difficult to mix.           |                 |
| · Partition coefficient (n-octanol/w | vater): Not determined.                     |                 |
| · Viscosity:                         |   |                 |
| Dynamic:                             | Not determined.                             |                 |
| Kinematic:                           | Not determined.                             |                 |
| · Solvent content:                   |   |                 |
| Water:                               | 95.5 %                                      |                 |
| VOC content:                         | 0.00 %                                      |                 |
|                                      | 0.0 g/l / 0.00 lb/gal                       |                 |
| Solids content:                      | 0.1 %                                       |                 |
| • Other information                  | No further relevant information available.  |                 |

# **10 Stability and reactivity**

· Reactivity No further relevant information available.

· Chemical stability

- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

## **11 Toxicological information**

- · Information on toxicological effects
- Acute toxicity:

### · LD/LC50 values that are relevant for classification:

## ATE (Acute Toxicity Estimate)

| Oral       | LD50     | 20,548 mg/kg (rabbit) |
|------------|----------|-----------------------|
|            |          | 239,808 mg/kg         |
| Inhalative | LC50/4 h | 2,398 mg/L            |

## 7647-01-0 hydrochloric acid

Oral LD50 900 mg/kg (rabbit)

## Primary irritant effect:

• on the skin: No irritant effect.

 $\cdot$  on the eye: Strong irritant with the danger of severe eye injury.

• Sensitization: No sensitizing effects known.

 $\cdot$  Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations:

(Contd. on page 6)

Agilent

Reviewed on 03/30/2019

Trade name: Tellurium AA Standard (125 mL)

(Contd. of page 5)

3

Irritant · Carcinogenic categories

· IARC (International Agency for Research on Cancer)

7647-01-0 hydrochloric acid

· NTP (National Toxicology Program)

None of the ingredients is listed.

## · OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients is listed.

## **12** Ecological information

- · Toxicity
- · Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- · Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.
- · Additional ecological information:
- · General notes:
- Water hazard class 1 (Self-assessment): slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system. Must not reach bodies of water or drainage ditch undiluted or unneutralized.

- · Results of PBT and vPvB assessment
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- · Other adverse effects No further relevant information available.

# **13 Disposal considerations**

## · Waste treatment methods

· Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packagings:
- · Recommendation: Disposal must be made according to official regulations.

| · UN-Number               |   |
|---------------------------|---|
| · DOT, IMDG, IATA         | UN3264  |
| · UN proper shipping name |   |
| ·DOT                      | Corrosive liquid, acidic, inorganic, n.o.s. (Hydrochloric acid) |
| · IMDG, IATA              | CORROSIVE LIQUID, ACIDIC, INORGANIC, N.O.S.                     |
| ,                         | (HYDROCHLORIC ACID)   |



Printing date 03/30/2019

Version Number 4

Reviewed on 03/30/2019

Printing date 03/30/2019

Version Number 4

| Trade name: Tellurium AA Standard (125 mL) |
|--|
|--|

|   | (Contd. of page of   |
|---|--|
| · Transport hazard class(es)  |  |
| · DOT, IMDG, IATA   |  |
| A CONTRACTOR OF |  |
| ·Class  | 8 Corrosive substances   |
| ·Label  | 8  |
| · Packing group<br>· DOT, IMDG, IATA  | III  |
| · Environmental hazards:  | Not applicable.  |
| <ul> <li>Special precautions for user</li> <li>Danger code (Kemler):</li> <li>EMS Number:</li> <li>Segregation groups</li> </ul>  | Warning: Corrosive substances<br>80<br>F-A,S-B<br>Acids  |
| · Stowage Category  | A  |
| · Stowage Code  | SW2 Clear of living quarters.  |
| <sup>•</sup> Transport in bulk according to Annex I<br>MARPOL73/78 and the IBC Code   | I of<br>Not applicable.  |
| · Transport/Additional information:   |  |
| · DOT   |  |
| · Quantity limitations  | On passenger aircraft/rail: 5 L  |
|   | On cargo aircraft only: 60 L   |
| <ul> <li>IMDG</li> <li>Limited quantities (LQ)</li> <li>Excepted quantities (EQ)</li> </ul>   | 5L<br>Code: E1<br>Maximum net quantity per inner packaging: 30 ml<br>Maximum net quantity per outer packaging: 1000 ml |
| · UN "Model Regulation":  | UN 3264 CORROSIVE LIQUID, ACIDIC, INORGANIC, N.O.S.<br>(HYDROCHLORIC ACID), 8, III                                     |

# **15 Regulatory information**

 $\cdot$  Safety, health and environmental regulations/legislation specific for the substance or mixture  $\cdot$  Sara

· Section 355 (extremely hazardous substances):

7647-01-0 hydrochloric acid

· Section 313 (Specific toxic chemical listings):

7647-01-0 hydrochloric acid

· TSCA (Toxic Substances Control Act):

All ingredients are listed.

(Contd. on page 8)



US

Printing date 03/30/2019

· Proposition 65

### Version Number 4

Reviewed on 03/30/2019

Trade name: Tellurium AA Standard (125 mL)

(Contd. of page 7)

A4

### · Chemicals known to cause cancer:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for females:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for males:

None of the ingredients is listed.

· Chemicals known to cause developmental toxicity:

None of the ingredients is listed.

#### · Carcinogenic categories

· EPA (Environmental Protection Agency)

None of the ingredients is listed.

· TLV (Threshold Limit Value established by ACGIH)

7647-01-0 hydrochloric acid

· NIOSH-Ca (National Institute for Occupational Safety and Health)

None of the ingredients is listed.

• Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

## **16 Other information**

The information contained in this document is based on Agilent's state of knowledge at the time of preparation. No warranty as to its accurateness, completeness or suitability for a particular purpose is expressed or implied.

- · Department issuing SDS: Document Control / Regulatory
- · Contact: regulatory@ultrasci.com
- · Date of preparation / last revision 03/30/2019 / 3
- · Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

- IMDG: International Maritime Code for Dangerous Goods DOT: US Department of Transportation
- IATA: International Air Transport Association
- ACGIH: American Conference of Governmental Industrial Hygienists
- EINECS: European Inventory of Existing Commercial Chemical Substances
- ELINCS: European List of Notified Chemical Substances
- CAS: Chemical Abstracts Service (division of the American Chemical Society)
- NFPA: National Fire Protection Association (USA)
- HMIS: Hazardous Materials Identification System (USA)
- VOC: Volatile Organic Compounds (USA, EU)
- LC50: Lethal concentration, 50 percent LD50: Lethal dose, 50 percent
- PBT: Persistent, Bioaccumulative and Toxic
- vPvB: very Persistent and very Bioaccumulative
- NIOSH: National Institute for Occupational Safety
- OSHA: Occupational Safety & Health
- TLV: Threshold Limit Value
- PEL: Permissible Exposure Limit
- REL: Recommended Exposure Limit
- Eye Dam. 1: Serious eye damage/eye irritation Category 1
- \* Data compared to the previous version altered.