

Safety Data Sheet
acc. to OSHA HCS

Printing date 03/29/2019

Version Number 6

Reviewed on 03/29/2019

1 Identification

- **Product identifier**
- **Trade name:** EM 200.7 Calibration Standard no. 2 (125 mL)
- **Part number:** ICM-203
- **Application of the substance / the mixture** Reagents and Standards for Analytical Chemical Laboratory Use
- **Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**
Agilent Technologies, Inc.
5301 Stevens Creek Blvd.
Santa Clara, CA 95051 USA
- **Information department:**
Telephone: 800-227-9770
e-mail: pdl-msds_author@agilent.com
- **Emergency telephone number:** CHEMTREC®: 1-800-424-9300

2 Hazard(s) identification

- **Classification of the substance or mixture**



GHS08 Health hazard

Carc. 1A H350 May cause cancer.



GHS07

Skin Irrit. 2 H315 Causes skin irritation.

Eye Irrit. 2A H319 Causes serious eye irritation.

- **Label elements**

- **GHS label elements** The product is classified and labeled according to the Globally Harmonized System (GHS).

- **Hazard pictograms**



GHS07



GHS08

- **Signal word** Danger

- **Hazard-determining components of labeling:**

acetic acid beryllium salt

- **Hazard statements**

Causes skin irritation.

Causes serious eye irritation.

May cause cancer.

- **Precautionary statements**

Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood.

Wash thoroughly after handling.

Wear protective gloves/protective clothing/eye protection/face protection.

(Contd. on page 2)

Safety Data Sheet acc. to OSHA HCS

Printing date 03/29/2019

Version Number 6

Reviewed on 03/29/2019

Trade name: EM 200.7 Calibration Standard no. 2 (125 mL)

(Contd. of page 1)

If on skin: Wash with plenty of water.
 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
 IF exposed or concerned: Get medical advice/attention.
 Specific treatment (see on this label).
 Take off contaminated clothing and wash it before reuse.
 If skin irritation occurs: Get medical advice/attention.
 If eye irritation persists: Get medical advice/attention.
 Store locked up.
 Dispose of contents/container in accordance with local/regional/national/international regulations.

· **Classification system:**

· **NFPA ratings (scale 0 - 4)**



· **HMIS-ratings (scale 0 - 4)**

HEALTH	2	Health = *2
FIRE	0	Fire = 0
REACTIVITY	0	Reactivity = 0

· **Other hazards**

· **Results of PBT and vPvB assessment**

· **PBT:** Not applicable.

· **vPvB:** Not applicable.

3 Composition/information on ingredients

· **Chemical characterization: Mixtures**

· **Description:** Mixture of the substances listed below with nonhazardous additions.

· **Dangerous components:**

7697-37-2	nitric acid	1.98%
543-81-7	acetic acid beryllium salt	0.112%

4 First-aid measures

· **Description of first aid measures**

· **General information:** Immediately remove any clothing soiled by the product.

· **After inhalation:** In case of unconsciousness place patient stably in side position for transportation.

· **After skin contact:** Immediately wash with water and soap and rinse thoroughly.

· **After eye contact:**

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

· **After swallowing:** If symptoms persist consult doctor.

· **Information for doctor:**

· **Most important symptoms and effects, both acute and delayed** No further relevant information available.

(Contd. on page 3)

Safety Data Sheet

acc. to OSHA HCS

Printing date 03/29/2019

Version Number 6

Reviewed on 03/29/2019

Trade name: EM 200.7 Calibration Standard no. 2 (125 mL)

(Contd. of page 2)

- **Indication of any immediate medical attention and special treatment needed**
No further relevant information available.

5 Fire-fighting measures

- **Extinguishing media**
- **Suitable extinguishing agents:** Use fire fighting measures that suit the environment.
- **Special hazards arising from the substance or mixture** No further relevant information available.
- **Advice for firefighters**
- **Protective equipment:** No special measures required.

6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures** Not required.
- **Environmental precautions:** Do not allow to enter sewers/ surface or ground water.
- **Methods and material for containment and cleaning up:**
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Dispose contaminated material as waste according to item 13.
Ensure adequate ventilation.
- **Reference to other sections**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.
- **Protective Action Criteria for Chemicals**

- **PAC-1:**

7697-37-2	nitric acid	0.16 ppm
7782-61-8	iron (III) nitrate nonahydrate	22 mg/m ³
10026-22-9	cobalt (II) nitrate hexahydrate	0.3 mg/m ³
7664-39-3	hydrogen fluoride	1.0 ppm
10377-66-9	manganese dinitrate	9.8 mg/m ³
3251-23-8	copper dinitrate	8.9 mg/m ³
7803-55-6	ammonium trioxovanadate	0.01 mg/m ³
10022-31-8	barium nitrate	2.9 mg/m ³

- **PAC-2:**

7697-37-2	nitric acid	24 ppm
7782-61-8	iron (III) nitrate nonahydrate	110 mg/m ³
10026-22-9	cobalt (II) nitrate hexahydrate	23 mg/m ³
7664-39-3	hydrogen fluoride	24 ppm
10377-66-9	manganese dinitrate	16 mg/m ³
3251-23-8	copper dinitrate	31 mg/m ³
7803-55-6	ammonium trioxovanadate	0.11 mg/m ³
10022-31-8	barium nitrate	350 mg/m ³

- **PAC-3:**

7697-37-2	nitric acid	92 ppm
-----------	-------------	--------

(Contd. on page 4)

Safety Data Sheet

acc. to OSHA HCS

Printing date 03/29/2019

Version Number 6

Reviewed on 03/29/2019

Trade name: EM 200.7 Calibration Standard no. 2 (125 mL)

		(Contd. of page 3)
7782-61-8	iron (III) nitrate nonahydrate	640 mg/m ³
10026-22-9	cobalt (II) nitrate hexahydrate	140 mg/m ³
7664-39-3	hydrogen fluoride	44 ppm
10377-66-9	manganese dinitrate	96 mg/m ³
3251-23-8	copper dinitrate	190 mg/m ³
7803-55-6	ammonium trioxovanadate	80 mg/m ³
10022-31-8	barium nitrate	2,100 mg/m ³

7 Handling and storage

- **Handling:**
- **Precautions for safe handling**
Ensure good ventilation/exhaustion at the workplace.
Open and handle receptacle with care.
- **Information about protection against explosions and fires:** Keep respiratory protective device available.
- **Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:** No special requirements.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:** Keep receptacle tightly sealed.
- **Specific end use(s)** No further relevant information available.

8 Exposure controls/personal protection

- **Additional information about design of technical systems:** No further data; see item 7.

- **Control parameters**

- **Components with limit values that require monitoring at the workplace:**

7697-37-2 nitric acid

PEL	Long-term value: 5 mg/m ³ , 2 ppm
REL	Short-term value: 10 mg/m ³ , 4 ppm Long-term value: 5 mg/m ³ , 2 ppm
TLV	Short-term value: 10 mg/m ³ , 4 ppm Long-term value: 5.2 mg/m ³ , 2 ppm

- **Additional information:** The lists that were valid during the creation were used as basis.
- **Exposure controls**
- **Personal protective equipment:**
- **General protective and hygienic measures:**
Keep away from foodstuffs, beverages and feed.
Immediately remove all soiled and contaminated clothing.
Wash hands before breaks and at the end of work.
Store protective clothing separately.
Avoid contact with the eyes and skin.
- **Breathing equipment:**
When used as intended with Agilent instruments, the use of the product under normal laboratory conditions and with standard practices does not result in significant airborne exposures and therefore respiratory protection is not needed.

(Contd. on page 5)

Safety Data Sheet

acc. to OSHA HCS

Printing date 03/29/2019

Version Number 6

Reviewed on 03/29/2019

Trade name: EM 200.7 Calibration Standard no. 2 (125 mL)

(Contd. of page 4)

Under an emergency condition where a respirator is deemed necessary, use a NIOSH or equivalent approved device/equipment with appropriate organic or acid gas cartridge.

- **Protection of hands:**

Although not recommended for constant contact with the chemicals or for clean-up, nitrile gloves 11-13 mil thickness are recommended for normal use. The breakthrough time is 1 hr. For cleaning a spill where there is direct contact of the chemical, butyl rubber gloves are recommended 12-15 mil thickness with breakthrough times exceeding 4 hrs. Supplier recommendations should be followed.

- **Material of gloves**

For normal use: nitrile rubber, 11-13 mil thickness

For direct contact with the chemical: butyl rubber, 12-15 mil thickness

- **Penetration time of glove material**

For normal use: nitrile rubber: 1 hour

For direct contact with the chemical: butyl rubber: >4 hours

- **Eye protection:**



Tightly sealed goggles

9 Physical and chemical properties

- **Information on basic physical and chemical properties**

- **General Information**

- **Appearance:**

Form: Fluid

Color: Colorless

- **Odor:** Odorless

- **Odor threshold:** Not determined.

- **pH-value:** Not determined.

- **Change in condition**

Melting point/Melting range: Undetermined.

Boiling point/Boiling range: 100 °C (212 °F)

- **Flash point:** Not applicable.

- **Flammability (solid, gaseous):** Not applicable.

- **Decomposition temperature:** Not determined.

- **Auto igniting:** Product is not selfigniting.

- **Danger of explosion:** Product does not present an explosion hazard.

- **Explosion limits:**

Lower: Not determined.

Upper: Not determined.

- **Vapor pressure at 20 °C (68 °F):** 23 hPa (17.3 mm Hg)

- **Density:** Not determined.

- **Relative density** Not determined.

- **Vapor density** Not determined.

(Contd. on page 6)

US

Safety Data Sheet

acc. to OSHA HCS

Printing date 03/29/2019

Version Number 6

Reviewed on 03/29/2019

Trade name: EM 200.7 Calibration Standard no. 2 (125 mL)

(Contd. of page 5)

· Evaporation rate	Not determined.
· Solubility in / Miscibility with Water:	Not miscible or difficult to mix.
· Partition coefficient (n-octanol/water):	Not determined.
· Viscosity:	
Dynamic at 20 °C (68 °F):	0.952 mPas
Kinematic:	Not determined.
· Solvent content:	
Water:	96.9 %
VOC content:	0.00 %
	0.0 g/l / 0.00 lb/gal
Solids content:	1.1 %
· Other information	No further relevant information available.

10 Stability and reactivity

- **Reactivity** No further relevant information available.
- **Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **Possibility of hazardous reactions** No dangerous reactions known.
- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:** No dangerous decomposition products known.

11 Toxicological information

- **Information on toxicological effects**
- **Acute toxicity:**

· LD/LC50 values that are relevant for classification:		
ATE (Acute Toxicity Estimate)		
Inhalative	LC50/4 h	3,384 mg/L (rat)

7697-37-2 nitric acid		
Inhalative	LC50/4 h	67 mg/L (rat)

7664-39-3 hydrogen fluoride		
Oral	LD50	1,276 mg/kg (rat)

- **Primary irritant effect:**
- **on the skin:** Irritant to skin and mucous membranes.
- **on the eye:** Irritating effect.
- **Sensitization:** No sensitizing effects known.

- **Additional toxicological information:**

The product shows the following dangers according to internally approved calculation methods for preparations:
Irritant

(Contd. on page 7)

US

Safety Data Sheet acc. to OSHA HCS

Printing date 03/29/2019

Version Number 6

Reviewed on 03/29/2019

Trade name: EM 200.7 Calibration Standard no. 2 (125 mL)

(Contd. of page 6)

· Carcinogenic categories
· IARC (International Agency for Research on Cancer)

543-81-7	acetic acid beryllium salt	1
10026-22-9	cobalt (II) nitrate hexahydrate	2B

· NTP (National Toxicology Program)

543-81-7	acetic acid beryllium salt	K
----------	----------------------------	---

· OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients is listed.

12 Ecological information

- **Toxicity**
- **Aquatic toxicity:** No further relevant information available.
- **Persistence and degradability** No further relevant information available.
- **Behavior in environmental systems:**
- **Bioaccumulative potential** No further relevant information available.
- **Mobility in soil** No further relevant information available.
- **Additional ecological information:**
- **General notes:**
 Water hazard class 1 (Self-assessment): slightly hazardous for water
 Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **Other adverse effects** No further relevant information available.

13 Disposal considerations

- **Waste treatment methods**
- **Recommendation:**
 Must not be disposed of together with household garbage. Do not allow product to reach sewage system.
- **Uncleaned packagings:**
- **Recommendation:** Disposal must be made according to official regulations.

14 Transport information

· UN-Number	
· DOT, IMDG, IATA	UN3264
· UN proper shipping name	
· DOT	Corrosive liquid, acidic, inorganic, n.o.s. (Nitric acid)
· IMDG, IATA	CORROSIVE LIQUID, ACIDIC, INORGANIC, N.O.S. (NITRIC ACID)

(Contd. on page 8)

Safety Data Sheet

acc. to OSHA HCS

Printing date 03/29/2019

Version Number 6

Reviewed on 03/29/2019

Trade name: EM 200.7 Calibration Standard no. 2 (125 mL)

(Contd. of page 7)

- **Transport hazard class(es)**

- **DOT, IMDG, IATA**



- **Class** 8 Corrosive substances
- **Label** 8

- **Packing group**

- **DOT, IMDG, IATA** III

- **Environmental hazards:** Not applicable.

- **Special precautions for user** Warning: Corrosive substances

- **Danger code (Kemler):** 80

- **EMS Number:** F-A,S-B

- **Segregation groups** Acids

- **Stowage Category** A

- **Stowage Code** SW2 Clear of living quarters.

- **Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code** Not applicable.

- **Transport/Additional information:**

- **DOT**

- **Quantity limitations** On passenger aircraft/rail: 5 L
On cargo aircraft only: 60 L

- **IMDG**

- **Limited quantities (LQ)** 5L

- **Excepted quantities (EQ)** Code: E1
Maximum net quantity per inner packaging: 30 ml
Maximum net quantity per outer packaging: 1000 ml

- **UN "Model Regulation":** UN 3264 CORROSIVE LIQUID, ACIDIC, INORGANIC, N.O.S. (NITRIC ACID), 8, III

15 Regulatory information

- **Safety, health and environmental regulations/legislation specific for the substance or mixture**

- **Sara**

- **Section 355 (extremely hazardous substances):**

7697-37-2	nitric acid
7664-39-3	hydrogen fluoride

- **Section 313 (Specific toxic chemical listings):**

7697-37-2	nitric acid
7782-61-8	iron (III) nitrate nonahydrate
543-81-7	acetic acid beryllium salt

(Contd. on page 9)

Safety Data Sheet

acc. to OSHA HCS

Printing date 03/29/2019

Version Number 6

Reviewed on 03/29/2019

Trade name: EM 200.7 Calibration Standard no. 2 (125 mL)

(Contd. of page 8)

10026-22-9	cobalt (II) nitrate hexahydrate
7664-39-3	hydrogen fluoride
10377-66-9	manganese dinitrate
3251-23-8	copper dinitrate
7803-55-6	ammonium trioxovanadate
10022-31-8	barium nitrate

· TSCA (Toxic Substances Control Act):

7697-37-2	nitric acid
7664-39-3	hydrogen fluoride
10377-66-9	manganese dinitrate
3251-23-8	copper dinitrate
7803-55-6	ammonium trioxovanadate
10022-31-8	barium nitrate
7732-18-5	water

· TSCA new (21st Century Act): (Substances not listed)

543-81-7	acetic acid beryllium salt
----------	----------------------------

· Proposition 65
· Chemicals known to cause cancer:

543-81-7	acetic acid beryllium salt
----------	----------------------------

· Chemicals known to cause reproductive toxicity for females:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for males:

None of the ingredients is listed.

· Chemicals known to cause developmental toxicity:

None of the ingredients is listed.

· Carcinogenic categories
· EPA (Environmental Protection Agency)

10377-66-9	manganese dinitrate	D
10022-31-8	barium nitrate	D, CBD(inh), NL(oral)

· TLV (Threshold Limit Value established by ACGIH)

10022-31-8	barium nitrate	A4
------------	----------------	----

· NIOSH-Ca (National Institute for Occupational Safety and Health)

None of the ingredients is listed.

· National regulations:
· Additional classification according to Decree on Hazardous Materials:

Carcinogenic hazardous material group III (dangerous).

· Information about limitation of use:

Workers are not allowed to be exposed to the hazardous carcinogenic materials contained in this preparation.

Exceptions can be made by the authorities in certain cases.

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

US

(Contd. on page 10)

Safety Data Sheet
acc. to OSHA HCS

Printing date 03/29/2019

Version Number 6

Reviewed on 03/29/2019

Trade name: EM 200.7 Calibration Standard no. 2 (125 mL)

(Contd. of page 9)

16 Other information

The information contained in this document is based on Agilent's state of knowledge at the time of preparation. No warranty as to its accurateness, completeness or suitability for a particular purpose is expressed or implied.

· **Department issuing SDS:** Document Control / Regulatory

· **Contact:** regulatory@ultrasci.com

· **Date of preparation / last revision** 03/29/2019 / 5

· **Abbreviations and acronyms:**

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

ACGIH: American Conference of Governmental Industrial Hygienists

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety & Health

TLV: Threshold Limit Value

PEL: Permissible Exposure Limit

REL: Recommended Exposure Limit

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Irrit. 2A: Serious eye damage/eye irritation – Category 2A

Carc. 1A: Carcinogenicity – Category 1A

· *** Data compared to the previous version altered.**

US