

Printing date 03/29/2019 Version Number 5 Reviewed on 03/29/2019

1 Identification

· Product identifier

· Trade name: EM 200.7 Plasma Standard (125 mL)

· Part number: ICM-235

· Application of the substance / the mixture Reagents and Standards for Analytical Chemical Laboratory Use

· Details of the supplier of the safety data sheet

Manufacturer/Supplier:
 Agilent Technologies, Inc.
 5301 Stevens Creek Blvd.
 Santa Clara, CA 95051 USA

· Information department:

Telephone: 800-227-9770

e-mail: pdl-msds author@agilent.com

· Emergency telephone number: CHEMTREC®: 1-800-424-9300

2 Hazard(s) identification

· Classification of the substance or mixture



Skin Irrit. 2 H315 Causes skin irritation.

Eye Irrit. 2A H319 Causes serious eye irritation.

- · Label elements
- · GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS).
- · Hazard pictograms



- · Signal word Warning
- · Hazard statements

Causes skin irritation.

Causes serious eye irritation.

· Precautionary statements

Wash thoroughly after handling.

Wear protective gloves / eye protection / face protection.

If on skin: Wash with plenty of water. Specific treatment (see on this label).

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.

Continue rinsing.

If skin irritation occurs: Get medical advice/attention. Take off contaminated clothing and wash it before reuse.

If eye irritation persists: Get medical advice/attention.

(Contd. on page 2)

(Contd. of page 1)



Safety Data Sheet acc. to OSHA HCS

Version Number 5 Printing date 03/29/2019 Reviewed on 03/29/2019

Trade name: EM 200.7 Plasma Standard (125 mL)

· Classification system:

· NFPA ratings (scale 0 - 4)



Health = 2Fire = 0Reactivity = 0

· HMIS-ratings (scale 0 - 4)



 $\frac{2}{1}$ Health = 2 Fire = 0

- · Other hazards
- · Results of PBT and vPvB assessment
- **PBT:** Not applicable. · vPvB: Not applicable.

3 Composition/information on ingredients

- · Chemical characterization: Mixtures
- · **Description:** Mixture of the substances listed below with nonhazardous additions.
- · Dangerous components:

7697-37-2 nitric acid

1.4%

4 First-aid measures

- · Description of first aid measures
- General information: Immediately remove any clothing soiled by the product.
- · After inhalation: In case of unconsciousness place patient stably in side position for transportation.
- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

- · After swallowing: If symptoms persist consult doctor.
- · Information for doctor:
- · Most important symptoms and effects, both acute and delayed No further relevant information available.
- · Indication of any immediate medical attention and special treatment needed

No further relevant information available.

5 Fire-fighting measures

- · Extinguishing media
- · Suitable extinguishing agents: Use fire fighting measures that suit the environment.
- Special hazards arising from the substance or mixture No further relevant information available.
- · Advice for firefighters
- · Protective equipment: No special measures required.



Printing date 03/29/2019 Version Number 5 Reviewed on 03/29/2019

Trade name: EM 200.7 Plasma Standard (125 mL)

(Contd. of page 2)

6 Accidental release measures

- · Personal precautions, protective equipment and emergency procedures Not required.
- Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- · Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

· Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

· Protective Action Criteria for Chemicals

PAC-1:	*/ * *4	0.16
7697-37-2		0.16 ppm
	magnesium nitrate hexahydrate	16 mg/m ³
7782-61-8	iron (III) nitrate nonahydrate	22 mg/m^3
10099-74-8	lead dinitrate	0.24 mg/m ³
13478-00-7	Nitric acid, nickel(2+) salt, hexahydrate	1.5 mg/m ³
10102-45-1	thallium nitrate	0.078 mg/m
PAC-2:		
7697-37-2	nitric acid	24 ppm
13446-18-9	magnesium nitrate hexahydrate	180 mg/m
7782-61-8	iron (III) nitrate nonahydrate	110 mg/m
10099-74-8	lead dinitrate	180 mg/m
13478-00-7	Nitric acid, nickel(2+) salt, hexahydrate	53 mg/m ³
10102-45-1	thallium nitrate	4.3 mg/m
PAC-3:		
7697-37-2	nitric acid	92 ppm
13446-18-9	magnesium nitrate hexahydrate	1,100 mg/m
7782-61-8	iron (III) nitrate nonahydrate	640 mg/m³
10099-74-8	lead dinitrate	1,100 mg/m
13478-00-7	Nitric acid, nickel(2+) salt, hexahydrate	320 mg/m ³
10102-45-1	thallium nitrate	26 mg/m ³

7 Handling and storage

- · Handling:
- · Precautions for safe handling No special precautions are necessary if used correctly.
- Information about protection against explosions and fires: No special measures required.
- · Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles: No special requirements.
- · Information about storage in one common storage facility: Not required.
- Further information about storage conditions: Keep receptacle tightly sealed.

(Contd. on page 4)



Printing date 03/29/2019 Version Number 5 Reviewed on 03/29/2019

Trade name: EM 200.7 Plasma Standard (125 mL)

· Specific end use(s) No further relevant information available.

(Contd. of page 3)

8 Exposure controls/personal protection

- · Additional information about design of technical systems: No further data; see item 7.
- · Control parameters

· Components with limit values that require monitoring at the workplace:

7697-37-2 nitric acid

PEL	Long-term value: 5 mg/m ³ , 2 ppm
REL	Short-term value: 10 mg/m³, 4 ppm Long-term value: 5 mg/m³, 2 ppm
	Long-term value: 5 mg/m³, 2 ppm
TLV	Short-term value: 10 mg/m³, 4 ppm
	Long-term value: 5.2 mg/m ³ , 2 ppm

- · Additional information: The lists that were valid during the creation were used as basis.
- · Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Avoid contact with the eyes and skin.

· Breathing equipment:

When used as intended with Agilent instruments, the use of the product under normal laboratory conditions and with standard practices does not result in significant airborne exposures and therefore respiratory protection is not needed.

Under an emergency condition where a respirator is deemed necessary, use a NIOSH or equivalent approved device/equipment with appropriate organic or acid gas cartridge.

Protection of hands:

Although not recommended for constant contact with the chemicals or for clean-up, nitrile gloves 11-13 mil thickness are recommended for normal use. The breakthrough time is 1 hr. For cleaning a spill where there is direct contact of the chemical, butyl rubber gloves are recommended 12-15 mil thickness with breakthrough times exceeding 4 hrs. Supplier recommendations should be followed.

· Material of gloves

For normal use: nitrile rubber, 11-13 mil thickness

For direct contact with the chemical: butyl rubber, 12-15 mil thickness

· Penetration time of glove material

For normal use: nitrile rubber: 1 hour

For direct contact with the chemical: butyl rubber: >4 hours

· Eye protection:



Tightly sealed goggles

HS



Printing date 03/29/2019 Version Number 5 Reviewed on 03/29/2019

Trade name: EM 200.7 Plasma Standard (125 mL)

(Contd. of page 4)

Physical and chemical proper	ties
· Information on basic physical and c	
· General Information	
· Appearance:	F1:1
Form: Color:	Fluid Colorless
· Odor:	Odorless
· Odor threshold:	Not determined.
· pH-value:	Not determined.
· Change in condition	
Melting point/Melting range:	Undetermined.
Boiling point/Boiling range:	100 °C (212 °F)
· Flash point:	Not applicable.
· Flammability (solid, gaseous):	Not applicable.
· Decomposition temperature:	Not determined.
· Auto igniting:	Product is not selfigniting.
Danger of explosion:	Product does not present an explosion hazard.
· Explosion limits:	
Lower:	Not determined.
Upper:	Not determined.
· Vapor pressure at 20 °C (68 °F):	23 hPa (17.3 mm Hg)
· Density:	Not determined.
· Relative density	Not determined.
· Vapor density	Not determined.
· Evaporation rate	Not determined.
· Solubility in / Miscibility with	
Water:	Not miscible or difficult to mix.
· Partition coefficient (n-octanol/wate	er): Not determined.
· Viscosity:	
Dynamic at 20 °C (68 °F):	0.952 mPas
Kinematic:	Not determined.
· Solvent content:	
Water:	98.4 %
VOC content:	0.00 %
	0.0 g/l / 0.00 lb/gal
Solids content:	0.2 %
· Other information	No further relevant information available.

10 Stability and reactivity

· Reactivity No further relevant information available.

(Contd. on page 6)



Printing date 03/29/2019 Version Number 5 Reviewed on 03/29/2019

Trade name: EM 200.7 Plasma Standard (125 mL)

(Contd. of page 5)

- · Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

11 Toxicological information

- · Information on toxicological effects
- · Acute toxicity:
- · LD/LC50 values that are relevant for classification:

ATE (Acute Toxicity Estimate)

Inhalative LC50/4 h 4,786 mg/L (rat)

7697-37-2 nitric acid

Inhalative LC50/4 h 67 mg/L (rat)

- · Primary irritant effect:
- · on the skin: Irritant to skin and mucous membranes.
- · on the eye: Irritating effect.
- · Sensitization: No sensitizing effects known.
- · Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations: Irritant

· Carcinogenic categories

· IARC (Inter	rnational Agency for Research on Cancer)	
10099-74-8	lead dinitrate	2A
543-81-7	acetic acid beryllium salt	1
13478-00-7	Nitric acid, nickel(2+) salt, hexahydrate	1
· NTP (Natio	nal Toxicology Program)	
10099-74-8	lead dinitrate	R
543-81-7	acetic acid beryllium salt	K
13478-00-7	Nitric acid, nickel(2+) salt, hexahydrate	K
· OSHA-Ca (Occupational Safety & Health Administration)	
None of the	ingredients is listed.	

12 Ecological information

- · Toxicity
- Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- · Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.

(Contd. on page 7)



Printing date 03/29/2019 Version Number 5 Reviewed on 03/29/2019

Trade name: EM 200.7 Plasma Standard (125 mL)

(Contd. of page 6)

- · Additional ecological information:
- · General notes:

Water hazard class 1 (Self-assessment): slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

- · Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · vPvB: Not applicable.
- · Other adverse effects No further relevant information available.

13 Disposal considerations

- · Waste treatment methods
- · Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packagings:
- · Recommendation: Disposal must be made according to official regulations.

5						, ,	P .			•	
		100	me	•	\mathbf{n}		7	mo	T 3		m
		r a		111			 	 110			
-				1	~ -	٠.	 •				

· UN-Number · DOT, IMDG, IATA	UN3264
· UN proper shipping name	Corrosive liquid, acidic, inorganic, n.o.s. (Nitric acid)
· DOT	CORROSIVE LIQUID, ACIDIC, INORGANIC, N.O.S. (NITRIC
· IMDG, IATA	ACID)

- · Transport hazard class(es)
- · DOT, IMDG, IATA



· Class	8 Corrosive substances
· Label	8
Packing group	
· DOT, IMDG, IATA	III
· Environmental hazards:	Not applicable.
· Special precautions for user	Warning: Corrosive substances
· Danger code (Kemler):	80
EMS Number:	F-A,S-B
· Segregation groups	Acids
· Stowage Category	A
· Stowage Code	SW2 Clear of living quarters.

· Transport in bulk according to Annex II of

MARPOL73/78 and the IBC Code Not applicable.

(Contd. on page 8)



Printing date 03/29/2019 Version Number 5 Reviewed on 03/29/2019

Trade name: EM 200.7 Plasma Standard (125 mL)

· Transport/Additional information:

· DOT

· Quantity limitations

On passenger aircraft/rail: 5 L
On cargo aircraft only: 60 L

· IMDG

· Limited quantities (LQ)
· Excepted quantities (EQ)

· Excepted quantities (EQ)

Maximum net quantity per inner packaging: 30 ml
Maximum net quantity per outer packaging: 1000 ml

· UN "Model Regulation":

UN 3264 CORROSIVE LIQUID, ACIDIC, INORGANIC, N.O.S.

(NITRIC ACID), 8, III

15 Regulatory information

- · Safety, health and environmental regulations/legislation specific for the substance or mixture
- ·Sara

· Sara					
· Section 355	· Section 355 (extremely hazardous substances):				
7697-37-2	7697-37-2 nitric acid				
· Section 313	(Specific toxic chemical listings):				
7697-37-2	nitric acid				
13446-18-9	magnesium nitrate hexahydrate				
7782-61-8	iron (III) nitrate nonahydrate				
10099-74-8	lead dinitrate				
	acetic acid beryllium salt				
13478-00-7	Nitric acid, nickel(2+) salt, hexahydrate				
10102-45-1	thallium nitrate				
· TSCA (Tox	ic Substances Control Act):				

TSCA (Toxic Substances Control Act):

7697-37-2	
10099-74-8	lead dinitrate
10102-45-1	thallium nitrate
7732-18-5	water

· Proposition 65

· Chemicals known to cause cancer:			
10099-74-8	lead dinitrate		
543-81-7	acetic acid beryllium salt		
13478-00-7	Nitric acid, nickel(2+) salt, hexahydrate		

· Chemicals known to cause reproductive toxicity for females:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for males:

13478-00-7 Nitric acid, nickel(2+) salt, hexahydrate

(Contd. on page 9)



Printing date 03/29/2019 Version Number 5 Reviewed on 03/29/2019

Trade name: EM 200.7 Plasma Standard (125 mL)

	(Conta. of page 8)
· Chemicals known to cause developmental toxicity:	
13478-00-7 Nitric acid, nickel(2+) salt, hexahydrate	

· Carcinogenic categories				
· EPA (Environmental Protection Agency)				
10099-74-8	lead dinitrate	B2		
10102-45-1	thallium nitrate	II		
· TLV (Threshold Limit Value established by ACGIH)				
10099-74-8	lead dinitrate	A3		
· NIOSH-Ca (National Institute for Occupational Safety and Health)				
None of the ingredients is listed.				

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

The information contained in this document is based on Agilent's state of knowledge at the time of preparation. No warranty as to its accurateness, completeness or suitability for a particular purpose is expressed or implied.

- · Department issuing SDS: Document Control / Regulatory
- · Contact: regulatory@ultrasci.com
- · Date of preparation / last revision 03/29/2019 / 4
- · Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

ACGIH: American Conference of Governmental Industrial Hygienists

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety & Health

TLV: Threshold Limit Value

PEL: Permissible Exposure Limit

REL: Recommended Exposure Limit

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Irrit. 2A: Serious eye damage/eye irritation - Category 2A

* Data compared to the previous version altered.

HS