

**Safety Data Sheet**  
acc. to OSHA HCS

Printing date 04/01/2019

Version Number 3

Reviewed on 04/01/2019

**1 Identification**

- **Product identifier**
- **Trade name:** VOC Standard (1X1 mL)
- **Part number:** PMX-190-1
- **Application of the substance / the mixture** Reagents and Standards for Analytical Chemical Laboratory Use
- **Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**  
Agilent Technologies, Inc.  
5301 Stevens Creek Blvd.  
Santa Clara, CA 95051 USA
- **Information department:**  
Telephone: 800-227-9770  
e-mail: pdl-msds\_author@agilent.com
- **Emergency telephone number:** CHEMTREC®: 1-800-424-9300

**2 Hazard(s) identification**

- **Classification of the substance or mixture**



GHS02 Flame

Flam. Liq. 2 H225 Highly flammable liquid and vapor.



GHS06 Skull and crossbones

Acute Tox. 3 H331 Toxic if inhaled.



GHS08 Health hazard

Muta. 1B H340 May cause genetic defects.

Carc. 1A H350 May cause cancer.

Repr. 1A H360 May damage fertility or the unborn child.

STOT SE 1 H370 Causes damage to organs.

STOT RE 2 H373 May cause damage to organs through prolonged or repeated exposure.



GHS07

Acute Tox. 4 H312 Harmful in contact with skin.

Skin Sens. 1 H317 May cause an allergic skin reaction.

- **Label elements**

- **GHS label elements** The product is classified and labeled according to the Globally Harmonized System (GHS).

(Contd. on page 2)

## Safety Data Sheet

### acc. to OSHA HCS

Printing date 04/01/2019

Version Number 3

Reviewed on 04/01/2019

**Trade name: VOC Standard (1X1 mL)**

(Contd. of page 1)

**· Hazard pictograms**

**· Signal word Danger**
**· Hazard-determining components of labeling:**

methanol  
 benzene  
 1,1,2,2-tetrachloroethane  
 1,2-dibromo-3-chloropropane  
 carbon tetrachloride  
 tetrachloroethylene  
 acrylonitrile  
 (Z)-1,3-dichloropropene  
 trans-1,3-dichloropropene

**· Hazard statements**

Highly flammable liquid and vapor.  
 Harmful in contact with skin.  
 Toxic if inhaled.  
 May cause an allergic skin reaction.  
 May cause genetic defects.  
 May cause cancer.  
 May damage fertility or the unborn child.  
 Causes damage to organs.  
 May cause damage to organs through prolonged or repeated exposure.

**· Precautionary statements**

Obtain special instructions before use.  
 Do not handle until all safety precautions have been read and understood.  
 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.  
 Ground/bond container and receiving equipment.  
 Use explosion-proof electrical/ventilating/lighting/equipment.  
 Use only non-sparking tools.  
 Take precautionary measures against static discharge.  
 Do not breathe dust/fume/gas/mist/vapors/spray.  
 Wash thoroughly after handling.  
 Do not eat, drink or smoke when using this product.  
 Use only outdoors or in a well-ventilated area.  
 Contaminated work clothing must not be allowed out of the workplace.  
 Wear protective gloves/protective clothing/eye protection/face protection.  
 If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.  
 IF INHALED: Remove person to fresh air and keep comfortable for breathing.  
 IF exposed or concerned: Get medical advice/attention.  
 Specific treatment (see on this label).  
 Call a poison center/doctor if you feel unwell.  
 Get medical advice/attention if you feel unwell.  
 Take off contaminated clothing and wash it before reuse.  
 If skin irritation or rash occurs: Get medical advice/attention.  
 Wash contaminated clothing before reuse.  
 In case of fire: Use for extinction: CO<sub>2</sub>, powder or water spray.

(Contd. on page 3)

## Safety Data Sheet

acc. to OSHA HCS

Printing date 04/01/2019

Version Number 3

Reviewed on 04/01/2019

**Trade name: VOC Standard (1X1 mL)**

(Contd. of page 2)

Store in a well-ventilated place. Keep container tightly closed.

Store in a well-ventilated place. Keep cool.

Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

· **Classification system:**

· **NFPA ratings (scale 0 - 4)**



Health = 1

Fire = 3

Reactivity = 0

· **HMIS-ratings (scale 0 - 4)**



Health = \*1

Fire = 3

Reactivity = 0

· **Other hazards**

· **Results of PBT and vPvB assessment**

· **PBT:**

120-82-1	1,2,4-trichlorobenzene
87-68-3	hexachlorobuta-1,3-diene

· **vPvB:**

87-68-3	hexachlorobuta-1,3-diene
---------	--------------------------

### 3 Composition/information on ingredients

· **Chemical characterization: Mixtures**

· **Description:** Mixture of the substances listed below with nonhazardous additions.

· **Dangerous components:**

67-56-1	methanol	86.854%
75-15-0	carbon disulphide	0.253%
108-10-1	4-methylpentan-2-one	0.253%
591-78-6	hexan-2-one	0.253%
71-43-2	benzene	0.253%
108-88-3	toluene	0.253%
100-41-4	ethylbenzene	0.253%
100-42-5	styrene	0.253%
91-20-3	naphthalene	0.253%
75-01-4	vinyl chloride	0.253%
74-87-3	chloromethane	0.253%
75-00-3	chloroethane	0.253%
75-27-4	bromodichloromethane	0.253%
67-66-3	trichloromethane	0.253%
56-23-5	carbon tetrachloride	0.253%
75-09-2	dichloromethane	0.253%

(Contd. on page 4)

## Safety Data Sheet

### acc. to OSHA HCS

Printing date 04/01/2019

Version Number 3

Reviewed on 04/01/2019

**Trade name: VOC Standard (1X1 mL)**

(Contd. of page 3)

107-06-2	1,2-dichloroethane	0.253%
71-55-6	1,1,1-trichloroethane	0.253%
79-00-5	1,1,2-trichloroethane	0.253%
79-34-5	1,1,2,2-tetrachloroethane	0.253%
127-18-4	tetrachloroethylene	0.253%
96-12-8	1,2-dibromo-3-chloropropane	0.253%
106-93-4	1,2-dibromoethane	0.253%
106-46-7	1,4-dichlorobenzene	0.253%
120-82-1	1,2,4-trichlorobenzene	0.253%
107-13-1	acrylonitrile	0.253%
87-68-3	hexachlorobuta-1,3-diene	0.253%
630-20-6	1,1,1,2-Tetrachloroethane	0.253%
96-18-4	1,2,3-trichloropropane	0.253%
10061-01-5	(Z)-1,3-dichloropropene	0.253%
10061-02-6	trans-1,3-dichloropropene	0.253%
79-01-6	trichloroethylene	0.253%

#### 4 First-aid measures

- **Description of first aid measures**

- **General information:**

Immediately remove any clothing soiled by the product.

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

Remove breathing apparatus only after contaminated clothing have been completely removed.

In case of irregular breathing or respiratory arrest provide artificial respiration.

- **After inhalation:**

Supply fresh air or oxygen; call for doctor.

In case of unconsciousness place patient stably in side position for transportation.

- **After skin contact:** Immediately wash with water and soap and rinse thoroughly.

- **After eye contact:** Rinse opened eye for several minutes under running water. Then consult a doctor.

- **After swallowing:** If symptoms persist consult doctor.

- **Information for doctor:**

- **Most important symptoms and effects, both acute and delayed** No further relevant information available.

- **Indication of any immediate medical attention and special treatment needed**

No further relevant information available.

#### 5 Fire-fighting measures

- **Extinguishing media**

- **Suitable extinguishing agents:**

CO<sub>2</sub>, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

- **For safety reasons unsuitable extinguishing agents:** Water with full jet

- **Special hazards arising from the substance or mixture**

During heating or in case of fire poisonous gases are produced.

(Contd. on page 5)

US

## Safety Data Sheet

### acc. to OSHA HCS

Printing date 04/01/2019

Version Number 3

Reviewed on 04/01/2019

**Trade name: VOC Standard (1X1 mL)**

(Contd. of page 4)

- **Advice for firefighters**
- **Protective equipment:** Mouth respiratory protective device.

## 6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures**

Mount respiratory protective device.

Wear protective equipment. Keep unprotected persons away.

- **Environmental precautions:** Do not allow to enter sewers/ surface or ground water.

- **Methods and material for containment and cleaning up:**

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

- **Reference to other sections**

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

- **Protective Action Criteria for Chemicals**

- **PAC-1:**

67-56-1	methanol	530 ppm
75-15-0	carbon disulphide	13 ppm
1634-04-4	tert-butyl methyl ether	50 ppm
67-64-1	acetone	200 ppm
78-93-3	butanone	200 ppm
108-10-1	4-methylpentan-2-one	75 ppm
591-78-6	hexan-2-one	10 ppm
71-43-2	benzene	52 ppm
108-88-3	toluene	67 ppm
100-41-4	ethylbenzene	33 ppm
108-38-3	m-xylene	130 ppm
100-42-5	styrene	20 ppm
91-20-3	naphthalene	15 ppm
75-69-4	trichlorofluoromethane	91 ppm
74-83-9	bromomethane	19 ppm
75-01-4	vinyl chloride	250 ppm
74-87-3	chloromethane	150 ppm
75-00-3	chloroethane	300 ppm
75-71-8	dichlorodifluoromethane	3,000 ppm
75-27-4	bromodichloromethane	1.3 mg/m <sup>3</sup>
75-25-2	bromoform	1.5 ppm
67-66-3	trichloromethane	2 ppm
124-48-1	dibromochloromethane	1.1 mg/m <sup>3</sup>
56-23-5	carbon tetrachloride	1.2 ppm
75-09-2	dichloromethane	200 ppm

(Contd. on page 6)

## Safety Data Sheet

acc. to OSHA HCS

Printing date 04/01/2019

Version Number 3

Reviewed on 04/01/2019

**Trade name: VOC Standard (1X1 mL)**

(Contd. of page 5)

156-59-2	cis-dichloroethylene	140 ppm
107-06-2	1,2-dichloroethane	50 ppm
71-55-6	1,1,1-trichloroethane	230 ppm
79-00-5	1,1,2-trichloroethane	30 ppm
79-34-5	1,1,2,2-tetrachloroethane	3 ppm

**PAC-2:**

67-56-1	methanol	2,100 ppm
75-15-0	carbon disulphide	160 ppm
1634-04-4	tert-butyl methyl ether	570 ppm
67-64-1	acetone	3200* ppm
78-93-3	butanone	2700* ppm
108-10-1	4-methylpentan-2-one	500 ppm
591-78-6	hexan-2-one	830 ppm
71-43-2	benzene	800 ppm
108-88-3	toluene	560 ppm
100-41-4	ethylbenzene	1100* ppm
108-38-3	m-xylene	920 ppm
100-42-5	styrene	130 ppm
91-20-3	naphthalene	83 ppm
75-69-4	trichlorofluoromethane	1,000 ppm
74-83-9	bromomethane	210 ppm
75-01-4	vinyl chloride	1,200 ppm
74-87-3	chloromethane	910 ppm
75-00-3	chloroethane	5100* ppm
75-71-8	dichlorodifluoromethane	10,000 ppm
75-27-4	bromodichloromethane	14 mg/m <sup>3</sup>
75-25-2	bromoform	6.8 ppm
67-66-3	trichloromethane	64 ppm
124-48-1	dibromochloromethane	12 mg/m <sup>3</sup>
56-23-5	carbon tetrachloride	13 ppm
75-09-2	dichloromethane	560 ppm
156-59-2	cis-dichloroethylene	500 ppm
107-06-2	1,2-dichloroethane	200 ppm
71-55-6	1,1,1-trichloroethane	600 ppm
79-00-5	1,1,2-trichloroethane	180 ppm
79-34-5	1,1,2,2-tetrachloroethane	120 ppm

**PAC-3:**

67-56-1	methanol	7200* ppm
75-15-0	carbon disulphide	480 ppm
1634-04-4	tert-butyl methyl ether	5300* ppm
67-64-1	acetone	5700* ppm

(Contd. on page 7)

## Safety Data Sheet

acc. to OSHA HCS

Printing date 04/01/2019

Version Number 3

Reviewed on 04/01/2019

**Trade name: VOC Standard (1X1 mL)**

		(Contd. of page 6)
78-93-3	butanone	4000* ppm
108-10-1	4-methylpentan-2-one	3000* ppm
591-78-6	hexan-2-one	5000* ppm
71-43-2	benzene	4000* ppm
108-88-3	toluene	3700* ppm
100-41-4	ethylbenzene	1800* ppm
108-38-3	m-xylene	2500* ppm
100-42-5	styrene	1100* ppm
91-20-3	naphthalene	500 ppm
75-69-4	trichlorofluoromethane	10,000 ppm
74-83-9	bromomethane	740 ppm
75-01-4	vinyl chloride	4800* ppm
74-87-3	chloromethane	3,000 ppm
75-00-3	chloroethane	20000** ppm
75-71-8	dichlorodifluoromethane	50,000 ppm
75-27-4	bromodichloromethane	85 mg/m <sup>3</sup>
75-25-2	bromoform	41 ppm
67-66-3	trichloromethane	3,200 ppm
124-48-1	dibromochloromethane	73 mg/m <sup>3</sup>
56-23-5	carbon tetrachloride	340 ppm
75-09-2	dichloromethane	6,900 ppm
156-59-2	cis-dichloroethylene	850 ppm
107-06-2	1,2-dichloroethane	300 ppm
71-55-6	1,1,1-trichloroethane	4,200 ppm
79-00-5	1,1,2-trichloroethane	500 ppm
79-34-5	1,1,2,2-tetrachloroethane	150 ppm

### \* 7 Handling and storage

- **Handling:**
- **Precautions for safe handling**  
Ensure good ventilation/exhaustion at the workplace.  
Open and handle receptacle with care.  
Prevent formation of aerosols.
- **Information about protection against explosions and fires:**  
Keep ignition sources away - Do not smoke.  
Protect against electrostatic charges.  
Keep respiratory protective device available.
- **Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:** Store in a cool location.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:**  
Keep receptacle tightly sealed.

(Contd. on page 8)

## Safety Data Sheet

### acc. to OSHA HCS

Printing date 04/01/2019

Version Number 3

Reviewed on 04/01/2019

**Trade name: VOC Standard (1X1 mL)**

(Contd. of page 7)

- Store in cool, dry conditions in well sealed receptacles.
- **Specific end use(s)** No further relevant information available.

## 8 Exposure controls/personal protection

- **Additional information about design of technical systems:** No further data; see item 7.
- **Control parameters**

### · Components with limit values that require monitoring at the workplace:

#### 67-56-1 methanol

PEL	Long-term value: 260 mg/m <sup>3</sup> , 200 ppm
REL	Short-term value: 325 mg/m <sup>3</sup> , 250 ppm Long-term value: 260 mg/m <sup>3</sup> , 200 ppm Skin
TLV	Short-term value: 328 mg/m <sup>3</sup> , 250 ppm Long-term value: 262 mg/m <sup>3</sup> , 200 ppm Skin; BEI

#### 75-15-0 carbon disulphide

PEL	Long-term value: 20 ppm Ceiling limit value: 30; 100* ppm *30-min peak per 8-hr shift
REL	Short-term value: 30 mg/m <sup>3</sup> , 10 ppm Long-term value: 3 mg/m <sup>3</sup> , 1 ppm Skin
TLV	Long-term value: 3.13 mg/m <sup>3</sup> , 1 ppm Skin, BEI

#### 108-10-1 4-methylpentan-2-one

PEL	Long-term value: 410 mg/m <sup>3</sup> , 100 ppm
REL	Short-term value: 300 mg/m <sup>3</sup> , 75 ppm Long-term value: 205 mg/m <sup>3</sup> , 50 ppm
TLV	Short-term value: 307 mg/m <sup>3</sup> , 75 ppm Long-term value: 82 mg/m <sup>3</sup> , 20 ppm BEI

#### 591-78-6 hexan-2-one

PEL	Long-term value: 410 mg/m <sup>3</sup> , 100 ppm
REL	Long-term value: 4 mg/m <sup>3</sup> , 1 ppm
TLV	Short-term value: 40 mg/m <sup>3</sup> , 10 ppm Long-term value: 20 mg/m <sup>3</sup> , 5 ppm Skin, BEI

#### 71-43-2 benzene

PEL	Short-term value: 15* mg/m <sup>3</sup> , 5* ppm Long-term value: 3* mg/m <sup>3</sup> , 1* ppm *table Z-2 for exclusions in 29CFR1910.1028(d)
REL	Short-term value: 1 ppm Long-term value: 0.1 ppm See Pocket Guide App. A

(Contd. on page 9)



## Safety Data Sheet

### acc. to OSHA HCS

Printing date 04/01/2019

Version Number 3

Reviewed on 04/01/2019

**Trade name: VOC Standard (1X1 mL)**

(Contd. of page 8)

TLV Short-term value: 8 mg/m<sup>3</sup>, 2.5 ppm  
 Long-term value: 1.6 mg/m<sup>3</sup>, 0.5 ppm  
 Skin; BEI

**108-88-3 toluene**

PEL Long-term value: 200 ppm  
 Ceiling limit value: 300; 500\* ppm  
 \*10-min peak per 8-hr shift

REL Short-term value: 560 mg/m<sup>3</sup>, 150 ppm  
 Long-term value: 375 mg/m<sup>3</sup>, 100 ppm

TLV Long-term value: 75 mg/m<sup>3</sup>, 20 ppm  
 BEI

**100-41-4 ethylbenzene**

PEL Long-term value: 435 mg/m<sup>3</sup>, 100 ppm

REL Short-term value: 545 mg/m<sup>3</sup>, 125 ppm  
 Long-term value: 435 mg/m<sup>3</sup>, 100 ppm

TLV Long-term value: 87 mg/m<sup>3</sup>, 20 ppm  
 BEI

**100-42-5 styrene**

PEL Long-term value: 100 ppm  
 Ceiling limit value: 200; 600\* ppm  
 \*5-min peak in any 3 hrs

REL Short-term value: 425 mg/m<sup>3</sup>, 100 ppm  
 Long-term value: 215 mg/m<sup>3</sup>, 50 ppm

TLV Short-term value: (170) mg/m<sup>3</sup>, (40) ppm  
 Long-term value: (85) NIC-8.5 mg/m<sup>3</sup>, (20) NIC-2 ppm  
 BEI, NIC-A3, NIC-OTO

**91-20-3 naphthalene**

PEL Long-term value: 50 mg/m<sup>3</sup>, 10 ppm

REL Short-term value: 75 mg/m<sup>3</sup>, 15 ppm  
 Long-term value: 50 mg/m<sup>3</sup>, 10 ppm

TLV Long-term value: 52 mg/m<sup>3</sup>, 10 ppm  
 Skin; BEI

**75-01-4 vinyl chloride**

PEL Short-term value: 5\* ppm  
 Long-term value: 1 ppm  
 \*Avg. not exceeding any 15 min; see 29CFR1910.1017

REL See Pocket Guide App.A

TLV Long-term value: 2.6 mg/m<sup>3</sup>, 1 ppm

**74-87-3 chloromethane**

PEL Long-term value: 100 ppm  
 Ceiling limit value: 200; 300\* ppm  
 \*5-min peak in any 3 hrs

REL See Pocket Guide App. A

TLV Short-term value: 207 mg/m<sup>3</sup>, 100 ppm  
 Long-term value: 103 mg/m<sup>3</sup>, 50 ppm  
 Skin

(Contd. on page 10)

## Safety Data Sheet

### acc. to OSHA HCS

Printing date 04/01/2019

Version Number 3

Reviewed on 04/01/2019

**Trade name: VOC Standard (1X1 mL)**

(Contd. of page 9)

**75-00-3 chloroethane**

PEL	Long-term value: 2600 mg/m <sup>3</sup> , 1000 ppm
REL	Handle with caution; See Pocket Guide App. C
TLV	Long-term value: 264 mg/m <sup>3</sup> , 100 ppm Skin

**67-66-3 trichloromethane**

PEL	Ceiling limit value: 240 mg/m <sup>3</sup> , 50 ppm
REL	Short-term value: 9.78* mg/m <sup>3</sup> , 2* ppm *60-min; See Pocket Guide App. A
TLV	Long-term value: 49 mg/m <sup>3</sup> , 10 ppm

**56-23-5 carbon tetrachloride**

PEL	Long-term value: 10 ppm Ceiling limit value: 25; 200* ppm *5-min peak in any 4 hrs
REL	Short-term value: 12.6* mg/m <sup>3</sup> , 2* ppm *60-min; See Pocket Guide App. A
TLV	Short-term value: 63 mg/m <sup>3</sup> , 10 ppm Long-term value: 31 mg/m <sup>3</sup> , 5 ppm Skin

**75-09-2 dichloromethane**

PEL	Short-term value: 125 ppm Long-term value: 25 ppm see 29 CFR 1910.1052
REL	See Pocket Guide App. A
TLV	Long-term value: 174 mg/m <sup>3</sup> , 50 ppm BEI

**107-06-2 1,2-dichloroethane**

PEL	Long-term value: 50 ppm Ceiling limit value: 100; 200* ppm *5-min peak in any 3 hrs
REL	Short-term value: 8 mg/m <sup>3</sup> , 2 ppm Long-term value: 4 mg/m <sup>3</sup> , 1 ppm See Pocket Guide Apps. A and C
TLV	Long-term value: 40 mg/m <sup>3</sup> , 10 ppm

**71-55-6 1,1,1-trichloroethane**

PEL	Long-term value: 1900 mg/m <sup>3</sup> , 350 ppm
REL	Ceiling limit value: 1900* mg/m <sup>3</sup> , 350* ppm *15-min; See Pocket Guide App. C
TLV	Short-term value: 2460 mg/m <sup>3</sup> , 450 ppm Long-term value: 1910 mg/m <sup>3</sup> , 350 ppm BEI

**79-00-5 1,1,2-trichloroethane**

PEL	Long-term value: 45 mg/m <sup>3</sup> , 10 ppm Skin
-----	--

(Contd. on page 11)

## Safety Data Sheet

### acc. to OSHA HCS

Printing date 04/01/2019

Version Number 3

Reviewed on 04/01/2019

**Trade name: VOC Standard (1X1 mL)**

(Contd. of page 10)

REL	Long-term value: 45 mg/m <sup>3</sup> , 10 ppm Skin; See Pocket Guide Apps.A and C
TLV	Long-term value: 55 mg/m <sup>3</sup> , 10 ppm Skin

**79-34-5 1,1,2,2-tetrachloroethane**

PEL	Long-term value: 35 mg/m <sup>3</sup> , 5 ppm Skin
REL	Long-term value: 7 mg/m <sup>3</sup> , 1 ppm Skin; See Pocket Guide Apps. A and C
TLV	Long-term value: 6.9 mg/m <sup>3</sup> , 1 ppm Skin

**127-18-4 tetrachloroethylene**

PEL	Long-term value: 100 ppm Ceiling limit value: 200; 300* ppm *5-min peak in any 3 hrs
REL	Minimize workplace exp. concs.; Pocket Guide App. A
TLV	Short-term value: 685 mg/m <sup>3</sup> , 100 ppm Long-term value: 170 mg/m <sup>3</sup> , 25 ppm BEI

**96-12-8 1,2-dibromo-3-chloropropane**

PEL	Long-term value: 0.001 ppm see 29 CFR 1910.1044
REL	See Pocket Guide App. A

**106-93-4 1,2-dibromoethane**

PEL	Long-term value: 20 ppm Ceiling limit value: 30; 50* ppm *5-min peak per 8-hr shift
REL	Long-term value: 0.045 ppm Ceiling limit value: 0.13* ppm *15-min; See Pocket Guide App. A
TLV	Skin

**106-46-7 1,4-dichlorobenzene**

PEL	Long-term value: 450 mg/m <sup>3</sup> , 75 ppm
REL	See Pocket Guide App. A
TLV	Long-term value: 60 mg/m <sup>3</sup> , 10 ppm

**120-82-1 1,2,4-trichlorobenzene**

REL	Ceiling limit value: 40 mg/m <sup>3</sup> , 5 ppm
TLV	Ceiling limit value: 37 mg/m <sup>3</sup> , 5 ppm

**107-13-1 acrylonitrile**

PEL	Long-term value: 2 ppm Ceiling limit value: 10 ppm Skin; see 29 CFR 1910.1045
REL	Long-term value: 1 ppm Ceiling limit value: 10* ppm *15-min; Skin; See Pocket Guide App. A

(Contd. on page 12)

## Safety Data Sheet

### acc. to OSHA HCS

Printing date 04/01/2019

Version Number 3

Reviewed on 04/01/2019

**Trade name: VOC Standard (1X1 mL)**

(Contd. of page 11)

TLV	Long-term value: 4.3 mg/m <sup>3</sup> , 2 ppm Skin
<b>87-68-3 hexachlorobuta-1,3-diene</b>	
REL	Long-term value: 0.24 mg/m <sup>3</sup> , 0.02 ppm Skin; See Pocket Guide App. A
TLV	Long-term value: 0.21 mg/m <sup>3</sup> , 0.02 ppm Skin
<b>630-20-6 1,1,1,2-Tetrachloroethane</b>	
REL	Handle with caution; See Pocket Guide App. C
<b>96-18-4 1,2,3-trichloropropane</b>	
PEL	Long-term value: 300 mg/m <sup>3</sup> , 50 ppm
REL	Long-term value: 60 mg/m <sup>3</sup> , 10 ppm Skin, See Pocket Guide App. A
TLV	Long-term value: 0.03 mg/m <sup>3</sup> , 0.005 ppm
<b>79-01-6 trichloroethylene</b>	
PEL	Long-term value: 100 ppm Ceiling limit value: 200; 300* ppm *5-min peak in any 2 hrs
REL	See Pocket Guide Apps. A and C
TLV	Short-term value: 135 mg/m <sup>3</sup> , 25 ppm Long-term value: 54 mg/m <sup>3</sup> , 10 ppm BEI
<b>Ingredients with biological limit values:</b>	
<b>67-56-1 methanol</b>	
BEI	15 mg/L Medium: urine Time: end of shift Parameter: Methanol (background, nonspecific)
<b>75-15-0 carbon disulphide</b>	
BEI	0.5 mg/g creatinine Medium: urine Time: end of shift Parameter: 2-Thioxothiazolidine-4-carboxylic acid (background, nonspecific)
<b>108-10-1 4-methylpentan-2-one</b>	
BEI	1 mg/L Medium: urine Time: end of shift Parameter: MIBK
<b>591-78-6 hexan-2-one</b>	
BEI	0.4 mg/L Medium: urine Time: end of shift at end of workweek Parameter: 2.5-Hexanedione without hydrolysis

(Contd. on page 13)

## Safety Data Sheet

acc. to OSHA HCS

Printing date 04/01/2019

Version Number 3

Reviewed on 04/01/2019

**Trade name: VOC Standard (1X1 mL)**

(Contd. of page 12)

**71-43-2 benzene**

BEI 25 µg/g creatinine  
 Medium: urine  
 Time: end of shift  
 Parameter: S-Phenylmercapturic acid (background)

500 µg/g creatinine  
 Medium: urine  
 Time: end of shift  
 Parameter: t,t-Muconic acid (background)

**108-88-3 toluene**

BEI 0.02 mg/L  
 Medium: blood  
 Time: prior to last shift of workweek  
 Parameter: Toluene

0.03 mg/L  
 Medium: urine  
 Time: end of shift  
 Parameter: Toluene

0.3 mg/g creatinine  
 Medium: urine  
 Time: end of shift  
 Parameter: o-Cresol with hydrolysis (background)

**100-41-4 ethylbenzene**

BEI 0.7 g/g creatinine  
 Medium: urine  
 Time: end of shift at end of workweek  
 Parameter: Sum of mandelic acid and phenylglyoxylic acid (nonspecific, semi-quantitative)

-  
 Medium: end-exhaled air  
 Time: not critical  
 Parameter: Ethyl benzene (semi-quantitative)

**100-42-5 styrene**

BEI 400 mg/g creatinine  
 Medium: urine  
 Time: end of shift  
 Parameter: Mandelic acid plus phenylglyoxylic acid (nonspecific)

0.2 mg/L  
 Medium: venous blood  
 Time: end of shift  
 Parameter: Styrene (semi-quantitative)

**75-09-2 dichloromethane**

BEI 0.3 mg/L  
 Medium: urine  
 Time: end of shift  
 Parameter: Dichloromethane (semi-quantitative)

(Contd. on page 14)

## Safety Data Sheet

### acc. to OSHA HCS

Printing date 04/01/2019

Version Number 3

Reviewed on 04/01/2019

**Trade name: VOC Standard (1X1 mL)**

(Contd. of page 13)

**71-55-6 1,1,1-trichloroethane**

BEI 40 ppm  
 Medium: end-exhaled air  
 Time: prior to last shift of workweek  
 Parameter: Methyl chloroform

10 mg/L  
 Medium: urine  
 Time: end of workweek  
 Parameter: Trichloroacetic acid (nonspecific, semi-quantitative)

30 mg/L  
 Medium: urine  
 Time: end of shift at end of workweek  
 Parameter: Total trichloroethanol (nonspecific, semi-quantitative)

1 mg/L  
 Medium: blood  
 Time: end of shift at end of workweek  
 Parameter: Total trichloroethanol (nonspecific)

**127-18-4 tetrachloroethylene**

BEI 3 ppm  
 Medium: end-exhaled air  
 Time: prior to shift  
 Parameter: Tetrachloroethylene

0.5 mg/L  
 Medium: blood  
 Time: prior to shift  
 Parameter: Tetrachloroethylene

**79-01-6 trichloroethylene**

BEI 15 mg/L  
 Medium: urine  
 Time: end of shift at end of workweek  
 Parameter: Trichloroacetic acid (nonspecific)

0.5 mg/L  
 Medium: blood  
 Time: end of shift at end of workweek  
 Parameter: Trichloroethanol without hydrolysis (nonspecific)

-  
 Medium: blood  
 Time: end of shift at end of workweek  
 Parameter: Trichloroethylene (semi-quantitative)

-  
 Medium: end-exhaled air  
 Time: end of shift at end of workweek  
 Parameter: Trichloroethylene (semi-quantitative)

(Contd. on page 15)

## Safety Data Sheet

### acc. to OSHA HCS

Printing date 04/01/2019

Version Number 3

Reviewed on 04/01/2019

**Trade name: VOC Standard (1X1 mL)**

(Contd. of page 14)

· **Additional information:** The lists that were valid during the creation were used as basis.

· **Exposure controls**

· **Personal protective equipment:**

· **General protective and hygienic measures:**

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Store protective clothing separately.

Avoid contact with the eyes and skin.

· **Breathing equipment:**

When used as intended with Agilent instruments, the use of the product under normal laboratory conditions and with standard practices does not result in significant airborne exposures and therefore respiratory protection is not needed.

Under an emergency condition where a respirator is deemed necessary, use a NIOSH or equivalent approved device/equipment with appropriate organic or acid gas cartridge.

· **Protection of hands:**

Although not recommended for constant contact with the chemicals or for clean-up, nitrile gloves 11-13 mil thickness are recommended for normal use. The breakthrough time is 1 hr. For cleaning a spill where there is direct contact of the chemical, butyl rubber gloves are recommended 12-15 mil thickness with breakthrough times exceeding 4 hrs. Supplier recommendations should be followed.

· **Material of gloves**

For normal use: nitrile rubber, 11-13 mil thickness

For direct contact with the chemical: butyl rubber, 12-15 mil thickness

· **Penetration time of glove material**

For normal use: nitrile rubber: 1 hour

For direct contact with the chemical: butyl rubber: >4 hours

· **Eye protection:**



Tightly sealed goggles

## \* 9 Physical and chemical properties

· **Information on basic physical and chemical properties**

· **General Information**

· **Appearance:**

· **Form:** Fluid

· **Color:** According to product specification

· **Odor:** Characteristic

· **Odor threshold:** Not determined.

· **pH-value:** Not determined.

· **Change in condition**

· **Melting point/Melting range:** Undetermined.

· **Boiling point/Boiling range:** 64.7 °C (148.5 °F)

· **Flash point:** 9 °C (48.2 °F)

· **Flammability (solid, gaseous):** Not applicable.

(Contd. on page 16)

## Safety Data Sheet

### acc. to OSHA HCS

Printing date 04/01/2019

Version Number 3

Reviewed on 04/01/2019

**Trade name: VOC Standard (1X1 mL)**

(Contd. of page 15)

· <b>Ignition temperature:</b>	455 °C (851 °F)
· <b>Decomposition temperature:</b>	Not determined.
· <b>Auto igniting:</b>	Product is not selfigniting.
· <b>Danger of explosion:</b>	Product is not explosive. However, formation of explosive air/vapor mixtures are possible.
· <b>Explosion limits:</b>	
<b>Lower:</b>	5.5 Vol %
<b>Upper:</b>	44 Vol %
· <b>Vapor pressure at 20 °C (68 °F):</b>	100 hPa (75 mm Hg)
· <b>Density at 20 °C (68 °F):</b>	0.86747 g/cm <sup>3</sup> (7.23904 lbs/gal)
· <b>Relative density</b>	Not determined.
· <b>Vapor density</b>	Not determined.
· <b>Evaporation rate</b>	Not determined.
· <b>Solubility in / Miscibility with Water:</b>	Not miscible or difficult to mix.
· <b>Partition coefficient (n-octanol/water):</b>	Not determined.
· <b>Viscosity:</b>	
<b>Dynamic:</b>	Not determined.
<b>Kinematic:</b>	Not determined.
· <b>Solvent content:</b>	
<b>Organic solvents:</b>	93.4 %
<b>VOC content:</b>	92.16 %
	799.5 g/l / 6.67 lb/gal
<b>Solids content:</b>	0.8 %
· <b>Other information</b>	No further relevant information available.

### 10 Stability and reactivity

- **Reactivity** No further relevant information available.
- **Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **Possibility of hazardous reactions** No dangerous reactions known.
- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:** No dangerous decomposition products known.

 US  
 (Contd. on page 17)



## Safety Data Sheet

acc. to OSHA HCS

Printing date 04/01/2019

Version Number 3

Reviewed on 04/01/2019

<b>Trade name: VOC Standard (1X1 mL)</b>
--

(Contd. of page 16)

### 11 Toxicological information

· **Information on toxicological effects**

· **Acute toxicity:**

· **LD/LC50 values that are relevant for classification:**

**ATE (Acute Toxicity Estimate)**

Oral	LD50	5,561 mg/kg
Dermal	LD50	1,524 mg/kg
Inhalative	LC50/4 h	3.35 mg/L

**67-56-1 methanol**

Oral	LD50	5,628 mg/kg (rat)
Dermal	LD50	15,800 mg/kg (rabbit)

**75-15-0 carbon disulphide**

Oral	LD50	1,200 mg/kg (rat)
Inhalative	LC50/4 h	10.35 mg/L (rat)

**108-10-1 4-methylpentan-2-one**

Oral	LD50	2,080 mg/kg (rat)
Dermal	LD50	16,000 mg/kg (rab) >16,000 mg/kg (rabbit)
Inhalative	LC50/4 h	>8.2 mg/L (rat)

**591-78-6 hexan-2-one**

Oral	LD50	2,590 mg/kg (rat)
Dermal	LD50	4,800 mg/kg (rabbit)
Inhalative	LC50/4 h	8,000 mg/L (rat)

**71-43-2 benzene**

Oral	LD50	3,340 mg/kg (rat)
Dermal	LD50	48 mg/kg (mouse) >8,260 mg/kg (rabbit)
Inhalative	LC50/4 h	9,980 mg/L (mouse)

**108-88-3 toluene**

Oral	LD50	5,580 mg/kg (rat)
Dermal	LD50	12,124 mg/kg (rabbit)
Inhalative	LC50/4 h	5,320 mg/L (mouse) 28.1 mg/L (rat)

**100-41-4 ethylbenzene**

Oral	LD50	3,500 mg/kg (rat)
Dermal	LD50	15,354 mg/kg (rabbit)
Inhalative	LC50/4 h	17.2 mg/L (rat)

**100-42-5 styrene**

Oral	LD50	5,000 mg/kg (rat)
Dermal	LD50	>2,000 mg/kg (rat)

(Contd. on page 18)

## Safety Data Sheet

acc. to OSHA HCS

Printing date 04/01/2019

Version Number 3

Reviewed on 04/01/2019

**Trade name: VOC Standard (1X1 mL)**

(Contd. of page 17)

Inhalative	LC50/4 h	11.8 mg/L (rat)
<b>91-20-3 naphthalene</b>		
Oral	LD50	490 mg/kg (rat)
Dermal	LD50	5,000 mg/kg (rat) 20,000 mg/kg (rabbit)
<b>75-69-4 trichlorofluoromethane</b>		
Oral	LD50	>15,000 mg/kg (rat)
<b>74-83-9 bromomethane</b>		
Oral	LD50	214 mg/kg (rat)
Inhalative	LC50/4 h	302 mg/L (rat)
<b>75-01-4 vinyl chloride</b>		
Oral	LD50	500 mg/kg (rat)
<b>74-87-3 chloromethane</b>		
Oral	LD50	1,800 mg/kg (rat)
Inhalative	LC50/4 h	>21,800 mg/L (rat)
<b>75-00-3 chloroethane</b>		
Inhalative	LC50/4 h	>19,000 mg/L (rat)
<b>75-27-4 bromodichloromethane</b>		
Oral	LD50	450 mg/kg (mouse)
<b>67-66-3 trichloromethane</b>		
Oral	LD50	908 mg/kg (rat)
Dermal	LD50	75 mg/kg (rat) >20,000 mg/kg (rabbit)
<b>56-23-5 carbon tetrachloride</b>		
Oral	LD50	2,350 mg/kg (rat)
Dermal	LD50	5,070 mg/kg (rat)
<b>75-09-2 dichloromethane</b>		
Oral	LD50	1,600 mg/kg (rat)
Dermal	LD50	>2,000 mg/kg (rat)
Inhalative	LC50/4 h	88 mg/L (rat)
<b>107-06-2 1,2-dichloroethane</b>		
Oral	LD50	670 mg/kg (rat)
Dermal	LD50	2,800 mg/kg (rat) 2,800 mg/kg (rabbit)
<b>71-55-6 1,1,1-trichloroethane</b>		
Oral	LD50	10,300 mg/kg (rat)
<b>79-00-5 1,1,2-trichloroethane</b>		
Oral	LD50	836 mg/kg (rat)
<b>79-34-5 1,1,2,2-tetrachloroethane</b>		
Oral	LD50	200 mg/kg (rat)

(Contd. on page 19)

## Safety Data Sheet

acc. to OSHA HCS

Printing date 04/01/2019

Version Number 3

Reviewed on 04/01/2019

**Trade name: VOC Standard (1X1 mL)**

(Contd. of page 18)

**127-18-4 tetrachloroethylene**

Oral	LD50	2,629 mg/kg (rat)
Inhalative	LC50/4 h	4,000 mg/L (rat)

**96-12-8 1,2-dibromo-3-chloropropane**

Oral	LD50	170 mg/kg (rat)
Dermal	LD50	1,420 mg/kg (rat) 1,400 mg/kg (rabbit)

**106-93-4 1,2-dibromoethane**

Oral	LD50	108 mg/kg (rat) 55 mg/kg (rabbit)
Dermal	LD50	300 mg/kg (rabbit)

**95-50-1 1,2-dichlorobenzene**

Oral	LD50	500 mg/kg (rat)
Dermal	LD50	>10,000 mg/kg (rabbit)

**106-46-7 1,4-dichlorobenzene**

Oral	LD50	>2,000 mg/kg (rat)
Dermal	LD50	>2,000 mg/kg (rat)
Inhalative	LC50/4 h	>5.07 mg/L (rat)

**120-82-1 1,2,4-trichlorobenzene**

Oral	LD50	756 mg/kg (rat)
Dermal	LD50	6,139 mg/kg (rat)

**107-13-1 acrylonitrile**

Oral	LD50	82 mg/kg (rat)
Dermal	LD50	226 mg/kg (rabbit)
Inhalative	LC50/4 h	2.09 mg/L (rat)

**87-68-3 hexachlorobuta-1,3-diene**

Oral	LD50	82 mg/kg (rat)
Dermal	LD50	100 mg/kg (rabbit)
Inhalative	LC50/4 h	370 mg/L (mouse)

**630-20-6 1,1,1,2-Tetrachloroethane**

Oral	LD50	670 mg/kg (rat)
Dermal	LD50	20,000 mg/kg (rabbit)
Inhalative	LC50/4 h	2,100 mg/L (rat)

**96-18-4 1,2,3-trichloropropane**

Oral	LD50	152 mg/kg (rat)
Dermal	LD50	523 mg/kg (rabbit)
Inhalative	LC50/4 h	4,800 mg/L (rat)

**10061-01-5 (Z)-1,3-dichloropropene**

Oral	LD50	250 mg/kg (rat)
------	------	-----------------

**10061-02-6 trans-1,3-dichloropropene**

Oral	LD50	250 mg/kg (rat)
------	------	-----------------

(Contd. on page 20)

## Safety Data Sheet

acc. to OSHA HCS

Printing date 04/01/2019

Version Number 3

Reviewed on 04/01/2019

**Trade name: VOC Standard (1X1 mL)**

(Contd. of page 19)

**79-01-6 trichloroethylene**

Oral	LD50	2,402 mg/kg (mouse) 4,290 mg/kg (rat)
Dermal	LD50	8,450 mg/kg (mouse)

**· Primary irritant effect:**

- **on the skin:** No irritant effect.
- **on the eye:** No irritating effect.
- **Sensitization:** Sensitization possible through skin contact.

**· Additional toxicological information:**

The product shows the following dangers according to internally approved calculation methods for preparations:

Toxic  
Harmful  
Irritant

The product can cause inheritable damage.

**· Carcinogenic categories**
**· IARC (International Agency for Research on Cancer)**

1634-04-4	tert-butyl methyl ether	3
108-10-1	4-methylpentan-2-one	2B
71-43-2	benzene	1
108-88-3	toluene	3
100-41-4	ethylbenzene	2B
95-47-6	o-xylene	3
108-38-3	m-xylene	3
106-42-3	p-xylene	3
100-42-5	styrene	2B
91-20-3	naphthalene	2B
74-83-9	bromomethane	3
75-01-4	vinyl chloride	1
74-87-3	chloromethane	3
75-00-3	chloroethane	3
75-27-4	bromodichloromethane	2B
75-25-2	bromoform	3
67-66-3	trichloromethane	2B
124-48-1	dibromochloromethane	3
56-23-5	carbon tetrachloride	2B
75-09-2	dichloromethane	2A
107-06-2	1,2-dichloroethane	2B
71-55-6	1,1,1-trichloroethane	3
79-00-5	1,1,2-trichloroethane	3
79-34-5	1,1,2,2-tetrachloroethane	2B
127-18-4	tetrachloroethylene	2A
96-12-8	1,2-dibromo-3-chloropropane	2B
106-93-4	1,2-dibromoethane	2A

(Contd. on page 21)

## Safety Data Sheet

acc. to OSHA HCS

Printing date 04/01/2019

Version Number 3

Reviewed on 04/01/2019

**Trade name: VOC Standard (1X1 mL)**

(Contd. of page 20)

78-87-5	1,2-dichloropropane	1
95-50-1	1,2-dichlorobenzene	3
106-46-7	1,4-dichlorobenzene	2B

**· NTP (National Toxicology Program)**

71-43-2	benzene	K
100-42-5	styrene	R
91-20-3	naphthalene	R
75-01-4	vinyl chloride	K
75-27-4	bromodichloromethane	R
67-66-3	trichloromethane	R
56-23-5	carbon tetrachloride	R
75-09-2	dichloromethane	R
107-06-2	1,2-dichloroethane	R
127-18-4	tetrachloroethylene	R
96-12-8	1,2-dibromo-3-chloropropane	R
106-93-4	1,2-dibromoethane	R
106-46-7	1,4-dichlorobenzene	R
107-13-1	acrylonitrile	R
96-18-4	1,2,3-trichloropropane	R
79-01-6	trichloroethylene	K

**· OSHA-Ca (Occupational Safety & Health Administration)**

71-43-2	benzene
75-01-4	vinyl chloride
75-09-2	dichloromethane
96-12-8	1,2-dibromo-3-chloropropane
107-13-1	acrylonitrile

## 12 Ecological information

- **Toxicity**
- **Aquatic toxicity:** No further relevant information available.
- **Persistence and degradability** No further relevant information available.
- **Behavior in environmental systems:**
- **Bioaccumulative potential** No further relevant information available.
- **Mobility in soil** No further relevant information available.
- **Additional ecological information:**

**· General notes:**

Water hazard class 3 (Self-assessment): extremely hazardous for water

Do not allow product to reach ground water, water course or sewage system, even in small quantities.

Danger to drinking water if even extremely small quantities leak into the ground.

**· Results of PBT and vPvB assessment**
**· PBT:**

120-82-1	1,2,4-trichlorobenzene
----------	------------------------

(Contd. on page 22)

## Safety Data Sheet

acc. to OSHA HCS

Printing date 04/01/2019

Version Number 3

Reviewed on 04/01/2019

**Trade name: VOC Standard (1X1 mL)**

(Contd. of page 21)

87-68-3	hexachlorobuta-1,3-diene
---------	--------------------------

 · **vPvB:**

87-68-3	hexachlorobuta-1,3-diene
---------	--------------------------

 · **Other adverse effects** No further relevant information available.

### 13 Disposal considerations

 · **Waste treatment methods**

 · **Recommendation:**

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

 · **Uncleaned packagings:**

 · **Recommendation:** Disposal must be made according to official regulations.

### 14 Transport information

 · **Not Regulated, De minimus Quantities** -

 · **UN-Number**

 · **DOT, IMDG, IATA** UN1230

 · **UN proper shipping name**

 · **DOT** Methanol solution

 · **IMDG, IATA** METHANOL solution

 · **Transport hazard class(es)**

 · **DOT**

 · **Class** 3 Flammable liquids

 · **Label** 3, 6.1

 · **IMDG**

 · **Class** 3 Flammable liquids

 · **Label** 3/6.1

 · **IATA**

 · **Class** 3 Flammable liquids

 · **Label** 3 (6.1)

(Contd. on page 23)

## Safety Data Sheet

### acc. to OSHA HCS

Printing date 04/01/2019

Version Number 3

Reviewed on 04/01/2019

**Trade name: VOC Standard (1X1 mL)**

(Contd. of page 22)

· <b>Packing group</b> · <b>DOT, IMDG, IATA</b>	II
· <b>Environmental hazards:</b>	Not applicable.
· <b>Special precautions for user</b> · <b>Danger code (Kemler):</b> · <b>EMS Number:</b> · <b>Stowage Category</b> · <b>Stowage Code</b>	Warning: Flammable liquids 336 F-E,S-D B SW2 Clear of living quarters.
· <b>Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code</b>	Not applicable.
· <b>Transport/Additional information:</b> · <b>DOT</b> · <b>Quantity limitations</b>	On passenger aircraft/rail: 1 L On cargo aircraft only: 60 L
· <b>IMDG</b> · <b>Limited quantities (LQ)</b> · <b>Excepted quantities (EQ)</b>	1L Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml
· <b>UN "Model Regulation":</b>	UN 1230 METHANOL SOLUTION, 3 (6.1), II

### 15 Regulatory information

- Safety, health and environmental regulations/legislation specific for the substance or mixture
- Sara

· <b>Section 355 (extremely hazardous substances):</b>	
75-15-0	carbon disulphide
74-83-9	bromomethane
67-66-3	trichloromethane
107-13-1	acrylonitrile
75-34-3	1,1-dichloroethane
· <b>Section 313 (Specific toxic chemical listings):</b>	
67-56-1	methanol
75-15-0	carbon disulphide
1634-04-4	tert-butyl methyl ether
78-93-3	butanone
108-10-1	4-methylpentan-2-one
71-43-2	benzene
108-88-3	toluene
100-41-4	ethylbenzene
95-47-6	o-xylene

(Contd. on page 24)

## Safety Data Sheet

acc. to OSHA HCS

Printing date 04/01/2019

Version Number 3

Reviewed on 04/01/2019

**Trade name: VOC Standard (1X1 mL)**

(Contd. of page 23)

108-38-3	m-xylene
106-42-3	p-xylene
100-42-5	styrene
91-20-3	naphthalene
75-69-4	trichlorofluoromethane
74-83-9	bromomethane
75-01-4	vinyl chloride
74-87-3	chloromethane
75-00-3	chloroethane
75-71-8	dichlorodifluoromethane
75-27-4	bromodichloromethane
75-25-2	bromoform
67-66-3	trichloromethane
56-23-5	carbon tetrachloride
75-09-2	dichloromethane
107-06-2	1,2-dichloroethane
71-55-6	1,1,1-trichloroethane
79-00-5	1,1,2-trichloroethane
79-34-5	1,1,2,2-tetrachloroethane
127-18-4	tetrachloroethylene
96-12-8	1,2-dibromo-3-chloropropane

**TSCA (Toxic Substances Control Act):**

67-56-1	methanol
75-15-0	carbon disulphide
1634-04-4	tert-butyl methyl ether
67-64-1	acetone
78-93-3	butanone
108-10-1	4-methylpentan-2-one
591-78-6	hexan-2-one
71-43-2	benzene
108-88-3	toluene
100-41-4	ethylbenzene
95-47-6	o-xylene
108-38-3	m-xylene
106-42-3	p-xylene
100-42-5	styrene
91-20-3	naphthalene
75-69-4	trichlorofluoromethane
74-83-9	bromomethane
75-01-4	vinyl chloride
74-87-3	chloromethane

(Contd. on page 25)



**Safety Data Sheet**  
 acc. to OSHA HCS

Printing date 04/01/2019

Version Number 3

Reviewed on 04/01/2019

**Trade name: VOC Standard (1X1 mL)**

(Contd. of page 24)

75-00-3	chloroethane
75-71-8	dichlorodifluoromethane
75-27-4	bromodichloromethane
75-25-2	bromoform
67-66-3	trichloromethane
124-48-1	dibromochloromethane
56-23-5	carbon tetrachloride
75-09-2	dichloromethane
156-59-2	cis-dichloroethylene
107-06-2	1,2-dichloroethane
71-55-6	1,1,1-trichloroethane

**TSCA new (21st Century Act): (Substances not listed)**

591-78-6	hexan-2-one
75-27-4	bromodichloromethane
96-12-8	1,2-dibromo-3-chloropropane
87-68-3	hexachlorobuta-1,3-diene
10061-01-5	(Z)-1,3-dichloropropene
10061-02-6	trans-1,3-dichloropropene

**Proposition 65**
**Chemicals known to cause cancer:**

108-10-1	4-methylpentan-2-one
71-43-2	benzene
100-41-4	ethylbenzene
100-42-5	styrene
91-20-3	naphthalene
75-01-4	vinyl chloride
75-00-3	chloroethane
75-27-4	bromodichloromethane
75-25-2	bromoform
67-66-3	trichloromethane
56-23-5	carbon tetrachloride
75-09-2	dichloromethane
107-06-2	1,2-dichloroethane
79-00-5	1,1,2-trichloroethane
79-34-5	1,1,2,2-tetrachloroethane
127-18-4	tetrachloroethylene
96-12-8	1,2-dibromo-3-chloropropane
106-93-4	1,2-dibromoethane
78-87-5	1,2-dichloropropane
106-46-7	1,4-dichlorobenzene
107-13-1	acrylonitrile

(Contd. on page 26)

## Safety Data Sheet

acc. to OSHA HCS

Printing date 04/01/2019

Version Number 3

Reviewed on 04/01/2019

**Trade name: VOC Standard (1X1 mL)**

(Contd. of page 25)

87-68-3	hexachlorobuta-1,3-diene
630-20-6	1,1,1,2-Tetrachloroethane
96-18-4	1,2,3-trichloropropane
75-35-4	1,1-dichloroethylene
75-34-3	1,1-dichloroethane
79-01-6	trichloroethylene

**· Chemicals known to cause reproductive toxicity for females:**

75-15-0	carbon disulphide
---------	-------------------

**· Chemicals known to cause reproductive toxicity for males:**

75-15-0	carbon disulphide
591-78-6	hexan-2-one
71-43-2	benzene
74-87-3	chloromethane
96-12-8	1,2-dibromo-3-chloropropane
106-93-4	1,2-dibromoethane
79-01-6	trichloroethylene

**· Chemicals known to cause developmental toxicity:**

67-56-1	methanol
75-15-0	carbon disulphide
108-10-1	4-methylpentan-2-one
591-78-6	hexan-2-one
71-43-2	benzene
108-88-3	toluene
74-83-9	bromomethane
74-87-3	chloromethane
67-66-3	trichloromethane
106-93-4	1,2-dibromoethane
79-01-6	trichloroethylene

**· Carcinogenic categories**
**· EPA (Environmental Protection Agency)**

67-64-1	acetone	I
78-93-3	butanone	I
108-10-1	4-methylpentan-2-one	I
591-78-6	hexan-2-one	II
71-43-2	benzene	A, K/L
108-88-3	toluene	II
100-41-4	ethylbenzene	D
95-47-6	o-xylene	I
108-38-3	m-xylene	I
106-42-3	p-xylene	I
91-20-3	naphthalene	C, CBD

(Contd. on page 27)

## Safety Data Sheet

acc. to OSHA HCS

Printing date 04/01/2019

Version Number 3

Reviewed on 04/01/2019

**Trade name: VOC Standard (1X1 mL)**

(Contd. of page 26)

74-83-9	bromomethane	D
75-01-4	vinyl chloride	A, K/L
74-87-3	chloromethane	D, CBD
75-27-4	bromodichloromethane	B2
75-25-2	bromoform	B2
67-66-3	trichloromethane	B2, L, NL
124-48-1	dibromochloromethane	C
56-23-5	carbon tetrachloride	L
75-09-2	dichloromethane	L
156-59-2	cis-dichloroethylene	II
107-06-2	1,2-dichloroethane	B2
71-55-6	1,1,1-trichloroethane	II
79-00-5	1,1,2-trichloroethane	C
79-34-5	1,1,2,2-tetrachloroethane	L
127-18-4	tetrachloroethylene	L
106-93-4	1,2-dibromoethane	L
108-90-7	chlorobenzene	D
95-50-1	1,2-dichlorobenzene	D
120-82-1	1,2,4-trichlorobenzene	D

**· TLV (Threshold Limit Value established by ACGIH)**

75-15-0	carbon disulphide	A4
1634-04-4	tert-butyl methyl ether	A3
67-64-1	acetone	A4
71-43-2	benzene	A1
108-88-3	toluene	A4
100-41-4	ethylbenzene	A3
95-47-6	o-xylene	A4
108-38-3	m-xylene	A4
106-42-3	p-xylene	A4
100-42-5	styrene	A4
91-20-3	naphthalene	A4
75-69-4	trichlorofluoromethane	A4
74-83-9	bromomethane	A4
75-01-4	vinyl chloride	A1
74-87-3	chloromethane	A4
75-00-3	chloroethane	A3
75-71-8	dichlorodifluoromethane	A4
75-25-2	bromoform	A3
67-66-3	trichloromethane	A3
56-23-5	carbon tetrachloride	A2
75-09-2	dichloromethane	A3

(Contd. on page 28)

## Safety Data Sheet

### acc. to OSHA HCS

Printing date 04/01/2019

Version Number 3

Reviewed on 04/01/2019

**Trade name: VOC Standard (1X1 mL)**

(Contd. of page 27)

107-06-2	1,2-dichloroethane	A4
71-55-6	1,1,1-trichloroethane	A4
79-00-5	1,1,2-trichloroethane	A3
79-34-5	1,1,2,2-tetrachloroethane	A3
127-18-4	tetrachloroethylene	A3
106-93-4	1,2-dibromoethane	A3
78-87-5	1,2-dichloropropane	A4
108-90-7	chlorobenzene	A3
95-50-1	1,2-dichlorobenzene	A4

**· NIOSH-Ca (National Institute for Occupational Safety and Health)**

71-43-2	benzene
74-83-9	bromomethane
75-01-4	vinyl chloride
74-87-3	chloromethane
67-66-3	trichloromethane
56-23-5	carbon tetrachloride
75-09-2	dichloromethane
107-06-2	1,2-dichloroethane
79-00-5	1,1,2-trichloroethane
79-34-5	1,1,2,2-tetrachloroethane
127-18-4	tetrachloroethylene
96-12-8	1,2-dibromo-3-chloropropane
106-93-4	1,2-dibromoethane
78-87-5	1,2-dichloropropane
106-46-7	1,4-dichlorobenzene
107-13-1	acrylonitrile
87-68-3	hexachlorobuta-1,3-diene
96-18-4	1,2,3-trichloropropane
75-35-4	1,1-dichloroethylene
79-01-6	trichloroethylene

**· National regulations:**
**· Additional classification according to Decree on Hazardous Materials:**

Carcinogenic hazardous material group III (dangerous).

**· Information about limitation of use:**

Workers are not allowed to be exposed to the hazardous carcinogenic materials contained in this preparation. Exceptions can be made by the authorities in certain cases.

**· Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

### 16 Other information

The information contained in this document is based on Agilent's state of knowledge at the time of preparation. No warranty as to its accurateness, completeness or suitability for a particular purpose is expressed or implied.

(Contd. on page 29)

**Safety Data Sheet**  
**acc. to OSHA HCS**

Printing date 04/01/2019

Version Number 3

Reviewed on 04/01/2019

**Trade name: VOC Standard (1X1 mL)**

(Contd. of page 28)

· **Date of preparation / last revision** 04/01/2019 / 2· **Abbreviations and acronyms:**

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

ACGIH: American Conference of Governmental Industrial Hygienists

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety &amp; Health

TLV: Threshold Limit Value

PEL: Permissible Exposure Limit

REL: Recommended Exposure Limit

BEI: Biological Exposure Limit

Flam. Liq. 2: Flammable liquids – Category 2

Acute Tox. 4: Acute toxicity – Category 4

Acute Tox. 3: Acute toxicity – Category 3

Skin Sens. 1: Skin sensitisation – Category 1

Muta. 1B: Germ cell mutagenicity – Category 1B

Carc. 1A: Carcinogenicity – Category 1A

Repr. 1A: Reproductive toxicity – Category 1A

STOT SE 1: Specific target organ toxicity (single exposure) – Category 1

STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2

· **\* Data compared to the previous version altered.**

US