Agilent

#### Printing date 03/30/2019

Version Number 4

Reviewed on 03/30/2019

## **1 Identification**

- · Product identifier
- · Trade name: Kepone Standard (1X1 mL)
- · Part number: PP-440A-1
- · Application of the substance / the mixture Reagents and Standards for Analytical Chemical Laboratory Use
- · Details of the supplier of the safety data sheet

• Manufacturer/Supplier: Agilent Technologies, Inc. 5301 Stevens Creek Blvd. Santa Clara, CA 95051 USA

#### · Information department:

Telephone: 800-227-9770 e-mail: pdl-msds\_author@agilent.com • Emergency telephone number: CHEMTREC®: 1-800-424-9300

## 2 Hazard(s) identification

· Classification of the substance or mixture

GHS02 Flame

Flam. Liq. 2 H225 Highly flammable liquid and vapor.

GHS08 Health hazard

Repr. 2 H361 Suspected of damaging fertility or the unborn child.

STOT RE 2 H373 May cause damage to organs through prolonged or repeated exposure.

Asp. Tox. 1 H304 May be fatal if swallowed and enters airways.

GHS07

Skin Irrit. 2 H315 Causes skin irritation.

STOT SE 3 H336 May cause drowsiness or dizziness.

· Label elements

 $\cdot$  GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS).

· Hazard pictograms



· Signal word Danger

- Hazard-determining components of labeling: toluene
- **Hazard statements** Highly flammable liquid and vapor.

(Contd. on page 2)

US

Reviewed on 03/30/2019

(Contd. on page 3)

Trade name: Kepone Standard (1X1 mL)

(Contd. of page 1) Causes skin irritation. Suspected of damaging fertility or the unborn child. May cause drowsiness or dizziness. May cause damage to organs through prolonged or repeated exposure. May be fatal if swallowed and enters airways. · Precautionary statements Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Ground/bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting/equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Do not breathe dust/fume/gas/mist/vapors/spray. Wash thoroughly after handling. Use only outdoors or in a well-ventilated area. Wear protective gloves/protective clothing/eye protection/face protection. If swallowed: Immediately call a poison center/doctor. Specific treatment (see on this label). Do NOT induce vomiting. If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. IF INHALED: Remove person to fresh air and keep comfortable for breathing. IF exposed or concerned: Get medical advice/attention. Call a poison center/doctor if you feel unwell. Get medical advice/attention if you feel unwell. Take off contaminated clothing and wash it before reuse. If skin irritation occurs: Get medical advice/attention. In case of fire: Use for extinction: CO2, powder or water spray. Store in a well-ventilated place. Keep container tightly closed. Store in a well-ventilated place. Keep cool. Store locked up. Dispose of contents/container in accordance with local/regional/national/international regulations. · Classification system: NFPA ratings (scale 0 - 4) Health = 1Fire = 3Reactivity = 0· HMIS-ratings (scale 0 - 4) HEALTH 1 Health = 1FIRE 3 Fire = 3**REACTIVITY** Reactivity = 0· Other hazards · Results of PBT and vPvB assessment • **PBT:** Not applicable. • **vPvB**: Not applicable.



Printing date 03/30/2019

Reviewed on 03/30/2019

Trade name: Kepone Standard (1X1 mL)

**3** Composition/information on ingredients

· Chemical characterization: Mixtures

• Description: Mixture of the substances listed below with nonhazardous additions.

· Dangerous components:

108-88-3 toluene

Printing date 03/30/2019

## **4 First-aid measures**

#### · Description of first aid measures

· General information:

Immediately remove any clothing soiled by the product.

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

- After inhalation: In case of unconsciousness place patient stably in side position for transportation.
- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- After eye contact: Rinse opened eye for several minutes under running water.
- After swallowing: If symptoms persist consult doctor.
- · Information for doctor:
- · Most important symptoms and effects, both acute and delayed No further relevant information available.
- · Indication of any immediate medical attention and special treatment needed
- No further relevant information available.

## **5** Fire-fighting measures

- · Extinguishing media
- Suitable extinguishing agents:
- CO2, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- For safety reasons unsuitable extinguishing agents: Water with full jet
- · Special hazards arising from the substance or mixture
- During heating or in case of fire poisonous gases are produced.
- · Advice for firefighters
- · Protective equipment: Mouth respiratory protective device.

## **6** Accidental release measures

- **Personal precautions, protective equipment and emergency procedures** Mount respiratory protective device. Wear protective equipment. Keep unprotected persons away.
- Environmental precautions: Do not allow to enter sewers/ surface or ground water.

• Methods and material for containment and cleaning up: Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to item 13.

- Ensure adequate ventilation.
- · Reference to other sections
- See Section 7 for information on safe handling.
- See Section 8 for information on personal protection equipment.
- See Section 13 for disposal information.

(Contd. on page 4)



Version Number 4

(0.1.1.1

(Contd. of page 2)

99.989%

Reviewed on 03/30/2019

Trade name: Kepone Standard (1X1 mL)

Printing date 03/30/2019

Protective Action Criteria for Chemicals	(Contd. of page 2
PAC-1:	
108-88-3 toluene	67 ppm
143-50-0 chlordecone (ISO)	1.6 mg/m <sup>2</sup>
PAC-2:	
108-88-3 toluene	560 ppm
143-50-0 chlordecone (ISO)	17 mg/m <sup>2</sup>
PAC-3:	
108-88-3 toluene	3700* ppn
143-50-0 chlordecone (ISO)	100 mg/m <sup>3</sup>

## 7 Handling and storage

#### · Handling:

- **Precautions for safe handling** Ensure good ventilation/exhaustion at the workplace. Open and handle receptacle with care.
- Prevent formation of aerosols.
- Information about protection against explosions and fires: Keep ignition sources away - Do not smoke. Protect against electrostatic charges. Keep respiratory protective device available.
- · Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles: Store in a cool location.
- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions:
- Keep receptacle tightly sealed.
- Store in cool, dry conditions in well sealed receptacles.
- Specific end use(s) No further relevant information available.

## 8 Exposure controls/personal protection

· Additional information about design of technical systems: No further data; see item 7.

#### · Control parameters

108-8	88-3 toluene	
PEL	Long-term value: 200 ppm Ceiling limit value: 300; 500* ppm *10-min peak per 8-hr shift	
REL	Short-term value: 560 mg/m <sup>3</sup> , 150 ppm Long-term value: 375 mg/m <sup>3</sup> , 100 ppm	
TLV	Long-term value: 75 mg/m <sup>3</sup> , 20 ppm BEI	
	(Contd. on page	5)



US

# Safety Data Sheet acc. to OSHA HCS

Reviewed on 03/30/2019

Printing date 03/30/2019

## Version Number 4

Trade name: Kepone Standard (1X1 mL)

Ingredients with biological limit values: 108-88-3 tolucue BEI 0.02 mg/L Medium: blood Time: prior to last shift of workweck Parameter: Toluene 0.03 mg/L Medium: urine Time: end of shift Parameter: Toluene 0.3 mg/g creatinine Medium: urine Time: end of shift Parameter: o-Cresol with hydrolysis (background) Additional information: The lists that were valid during the creation were used as basis. Exposure controls Personal protective equipment: General protective equipment: General protective equipment: General protective and hygienic measures: Keep away from foodstuffs, beverages and feed. Immediately remove all solied and contaminated clothing. Wash hands before breaks and at the end of work. Store protective clothing separately. Avoid contact with the skin. Breathing equipment: When used as intended with Agilent instruments, the use of the product under normal laboratory conditions and with standard practices does not result in significant airborne exposures and therefore respiratory protection is not needed. Under an emergency condition where a respirator is deemed necessary, use a NIOSH or equivalent approved device/equipment with appropriate organic or acid gas cartridge. Protection of hands: Although not recommended for constant contact with the chemicals or for clean-up, nitrile gloves 11-13 mil thickness are recommended for constant contact with the chemicals or for clean-up, nitrile gloves 11-13 mil thickness are recommended for constant contact with the chemicals or for clean-up, nitrile gloves 11-13 mil thickness are recommended for normal use. The breakthrough time is 1 hr. For cleaning a spill where there is for normal use: nitrile rubber, 11-13 mil thickness Penetration time of glove material For normal use: nitrile rubber; 1 hour For moreal use: nitrile rubber: 1 hour For direct contact with the chemical: butyl rubber; >4 hours (cond. on page		(Contd. of page
BEI 0.02 mg/L Medium: blood Time: prior to last shift of workweek Parameter: Toluene 0.03 mg/L Medium: urine Time: end of shift Parameter: Toluene 0.3 mg/g creatinine Medium: urine Time: end of shift Parameter: o-Cresol with hydrolysis (background) Additional information: The lists that were valid during the creation were used as basis. Exposure controls Personal protective equipment: General protective equipment: General protective equipment: General protective equipment: Mediately remove all solied and contaminated clothing. Wash hands before breaks and at the end of work. Store protective the skin. Avoid contact with the skin. Avoid contact with the skin. Breathing equipment: When used as intended with Agilent instruments, the use of the product under normal laboratory conditions and with standard practices does not result in significant airborne exposures and therefore respiratory protection is no needed. Under an emergency condition where a respirator is deemed necessary, use a NIOSH or equivalent approved device/equipment with appropriate organic or acid gas cartridge. Protection of hands: Although not recommended for constant contact with the chemicals or for clean-up, nitrile gloves 11-13 mil thickness are recommended for normal use. The breakthrough time is 1 hr. For cleaning a spill where there is direct contact of the chemical, butyl rubber, 12-15 mil thickness For normal use: nitrile rubber, 11-13 mil thickness For direct contact with the chemical: butyl rubber, 12-15 mil thickness Penetration time of glove material For normal use: nitrile rubber: 1 hour For direct contact with the chemical: butyl rubber; >4 hours	Ingr	edients with biological limit values:
Medium: blood         Time: prior to last shift of workweek         Parameter: Toluene         0.03 mg/L         Medium: urine         Time: end of shift         Parameter: Toluene         0.3 mg/g creatinine         Medium: urine         Time: end of shift         Parameter: Toluene         0.3 mg/g creatinine         Medium: urine         Time: end of shift         Parameter: o-Cresol with hydrolysis (background)         Additional information: The lists that were valid during the creation were used as basis.         Exposure controls         Personal protective equipment:         General protective and hygienic measures:         Keep away from foodstuffs, beverages and feed.         Immediately remove all solied and contaminated clothing.         Wash hands before breaks and at the end of work.         Store protective clothing separately.         Avoid contact with the skin.         Avoid contact with the eyes and skin.         Breathing equipment:         When used as intended with Agilent instruments, the use of the product under normal laboratory conditions and with standard practices does not result in significant airborne exposures and therefore respiratory protection is no needed.         Under an emergency condition where a respirator is deemed necessary, use a NIOSH or equivalent	108-	88-3 toluene
Time: prior to last shift of workweek Parameter: Toluene 0.03 mg/L Medium: urine 0.03 mg/L Medium: urine 0.3 mg/g creatinine Medium: urine 0.3 mg/g creatinine Medium: urine Time: end of shift Parameter: Toluene 0.3 mg/g creatinine Medium: urine Time: end of shift Parameter: o-Cresol with hydrolysis (background) Additional information: The lists that were valid during the creation were used as basis. Exposure controls Personal protective equipment: General protective equipment: General protective and bygenic measures: Keep away from foodstuffs, beverages and feed. Immediately remove all soiled and contaminated clothing. Wash hands before breaks and at the end of work. Store protective all soiled and contaminated clothing. Wash hands before breaks and at the end of work. Store protective add with Agilent instruments, the use of the product under normal laboratory conditions and with standard practices does not result in significant airborne exposures and therefore respiratory protection is no needed. Under an emergency condition where a respirator is deemed necessary, use a NIOSH or equivalent approved device/equipment with appropriate organic or acid gas cartridge. Protection of hands: Protection of hands: Note recommended for constant contact with the chemicals or for clean-up, nitrile gloves 11-13 mil thickness are recommended for normal use. The breakthrough time is 1 hr. For cleaning a spill where there is direct contact of the chemical, butyl rubber, 12-15 mil thickness For normal use: nitrile rubber, 11-13 mil thickness For normal use: nitrile rubber: 1 hour For direct contact with the chemical: butyl rubber: >4 hours	BEI	0.02 mg/L
Parameter: Toluene         0.03 mg/L         Medium: urine         Time: end of shift         Parameter: Toluene         0.3 mg/g creatinine         Medium: urine         Time: end of shift         Parameter: - o-Cresol with hydrolysis (background)         Additional information: The lists that were valid during the creation were used as basis.         Exposure controls         Personal protective equipment:         General protective equipment:         General protective and hygienic measures:         Keep away from foodstuffs, beverages and feed.         Immediately remove all soiled and contaminated clothing.         Wash hands before breaks and at the end of work.         Store protective clothing separately.         Avoid contact with the skin.         Reathing equipment:         When used as intended with Agilent instruments, the use of the product under normal laboratory conditions and with standard practices does not result in significant airborne exposures and therefore respiratory protection is no needed.         Under an emergency condition where a respirator is deemed necessary, use a NIOSH or equivalent approved device/equipment with appropritae organic or acid gas cartridge.		Medium: blood
<ul> <li>0.03 mg/L</li> <li>Medium: urine</li> <li>Time: end of shift</li> <li>Parameter: Toluene</li> <li>0.3 mg/g creatinine</li> <li>Medium: urine</li> <li>Time: end of shift</li> <li>Parameter: o-Cresol with hydrolysis (background)</li> </ul> Additional information: The lists that were valid during the creation were used as basis. Exposure controls Personal protective equipment: General protective and hygienic measures: Keep away from foodstuffs, beverages and feed. Immediately remove all soiled and contaminated clothing. Wash hands before breaks and at the end of work. Store protective clothing separately. Avoid contact with the skin. Berathing equipment: When used as intended with Agilent instruments, the use of the product under normal laboratory conditions and with standard practices does not result in significant airborne exposures and therefore respiratory protection is no needed. Under an emergency condition where a respirator is deemed necessary, use a NIOSH or equivalent approved device/equipment with appropriate organic or acid gas cartridge. Protection of hands: Although not recommended for normal use. The breakthrough time is 1 hr. For cleaning a spill where there is direct contact of the chemical, butyl rubber gloves are recommended 12-15 mil thickness with breakthrough time is contact with the chemical, butyl rubber gloves are recommended 12-15 mil thickness For direct contact with the chemical; butyl rubber, 12-15 mil thickness For direct contact with the chemical; butyl rubber; >4 hours For direct contact with the chemical; butyl rubber; >4 hours For direct contact with the chemical; butyl rubber; >4 hours		Time: prior to last shift of workweek
Medium: urine         Time: end of shift         Parameter: Toluene         0.3 mg/g creatinine         Medium: urine         Time:: end of shift         Parameter: o-Cresol with hydrolysis (background)         Additional information: The lists that were valid during the creation were used as basis.         Exposure controls         Personal protective equipment:         General protective and hygienic measures:         Keep away from foodstuffs, beverages and feed.         Immediately remove all soiled and contaminated clothing.         Wash hands before breaks and at the end of work.         Store protective clothing separately.         Avoid contact with the eyes and skin.         Breathing equipment:         When used as intended with Agilent instruments, the use of the product under normal laboratory conditions and with standard practices does not result in significant airborne exposures and therefore respiratory protection is no needed.         Under an emergency condition where a respirator is deemed necessary, use a NIOSH or equivalent approved device/equipment with appropriate organic or acid gas cartridge.         Protection of hands:         Although not recommended for normal use. The breakthrough time is 1 hr. For cleaning a spill where there is direct contact of the chemical, butyl rubber gloves are recommended 12-15 mil thickness with breakthrough time exceeding 4 hrs. Supplier recommendations should be followed.         Material		Parameter: Toluene
Medium: urine         Time: end of shift         Parameter: Toluene         0.3 mg/g creatinine         Medium: urine         Time:: end of shift         Parameter: o-Cresol with hydrolysis (background)         Additional information: The lists that were valid during the creation were used as basis.         Exposure controls         Personal protective equipment:         General protective and hygienic measures:         Keep away from foodstuffs, beverages and feed.         Immediately remove all soiled and contaminated clothing.         Wash hands before breaks and at the end of work.         Store protective clothing separately.         Avoid contact with the eyes and skin.         Breathing equipment:         When used as intended with Agilent instruments, the use of the product under normal laboratory conditions and with standard practices does not result in significant airborne exposures and therefore respiratory protection is no needed.         Under an emergency condition where a respirator is deemed necessary, use a NIOSH or equivalent approved device/equipment with appropriate organic or acid gas cartridge.         Protection of hands:         Although not recommended for normal use. The breakthrough time is 1 hr. For cleaning a spill where there is direct contact of the chemical, butyl rubber gloves are recommended 12-15 mil thickness with breakthrough time exceeding 4 hrs. Supplier recommendations should be followed.         Material		0.03 mg/L
Parameter: Toluene         0.3 mg/g creatinine Medium: urine Time: end of shift Parameter: o-Cresol with hydrolysis (background)         Additional information: The lists that were valid during the creation were used as basis.         Exposure controls Personal protective equipment: General protective equipment: General protective equipment: General protective contaminated clothing.         Wash hands before breaks and at the end of work.         Store protective clothing separately.         Avoid contact with the systand skin.         Breathing equipment:         When used as intended with Agilent instruments, the use of the product under normal laboratory conditions and with standard practices does not result in significant airborne exposures and therefore respiratory protection is no needed.         Under an emergency condition where a respirator is deemed necessary, use a NIOSH or equivalent approved device/equipment with appropriate organic or acid gas cartridge.         Protection of hands:         Although not recommended for normal use. The breakthrough time is 1 hr. For cleaning a spill where there is direct contact of the chemical, butyl rubber gloves are recommended 12-15 mil thickness with breakthrough time exceeding 4 hrs. Supplier recommendations should be followed.         Material of gloves For direct contact with the chemical: butyl rubber, 12-15 mil thickness         For direct contact with the chemical: butyl rubber; >4 hours		
0.3 mg/g creatinine         Medium: urine         Time: end of shift         Parameter: o-Cresol with hydrolysis (background)         Additional information: The lists that were valid during the creation were used as basis.         Exposure controls         Personal protective equipment:         General protective and hygienic measures:         Keep away from foodstuffs, beverages and feed.         Immediately remove all soiled and contaminated clothing.         Wash hands before breaks and at the end of work.         Store protective clothing separately.         Avoid contact with the skin.         Avoid contact with the skin.         Breathing equipment:         When used as intended with Agilent instruments, the use of the product under normal laboratory conditions and with standard practices does not result in significant airborne exposures and therefore respiratory protection is no needed.         Under an emergency condition where a respirator is deemed necessary, use a NIOSH or equivalent approved device/equipment with appropriate organic or acid gas cartridge.         Protection of hands:         Although not recommended for normal use. The breakthrough time is 1 hr. For cleaning a spill where there is direct contact of the chemical, butyl rubber gloves are recommended 12-15 mil thickness with breakthrough time exceeding 4 hrs. Supplier recommendations should be followed.         Material of gloves         For direct contact with the chemical: butyl rubber, 12-15		Time: end of shift
Medium: urine         Time: end of shift         Parameter: o-Cresol with hydrolysis (background)         Additional information: The lists that were valid during the creation were used as basis.         Exposure controls         Personal protective equipment:         General protective and hygienic measures:         Keep away from foodstuffs, beverages and feed.         Immediately remove all soiled and contaminated clothing.         Wash hands before breaks and at the end of work.         Store protective clothing separately.         Avoid contact with the skin.         Avoid contact with the skin.         Breathing equipment:         When used as intended with Agilent instruments, the use of the product under normal laboratory conditions and with standard practices does not result in significant airborne exposures and therefore respiratory protection is no needed.         Under an emergency condition where a respirator is deemed necessary, use a NIOSH or equivalent approved device/equipment with appropriate organic or acid gas cartridge.         Protection of hands:         Although not recommended for normal use. The breakthrough time is 1 hr. For cleaning a spill where there is direct contact of the chemical, butyl rubber gloves are recommended 12-15 mil thickness with breakthrough time exceeding 4 hrs. Supplier recommendations should be followed.         Material of gloves         For normal use: nitrile rubber, 11-13 mil thickness         For direct contact with t		Parameter: Toluene
Medium: urine         Time: end of shift         Parameter: o-Cresol with hydrolysis (background)         Additional information: The lists that were valid during the creation were used as basis.         Exposure controls         Personal protective equipment:         General protective and hygienic measures:         Keep away from foodstuffs, beverages and feed.         Immediately remove all soiled and contaminated clothing.         Wash hands before breaks and at the end of work.         Store protective clothing separately.         Avoid contact with the skin.         Avoid contact with the skin.         Breathing equipment:         When used as intended with Agilent instruments, the use of the product under normal laboratory conditions and with standard practices does not result in significant airborne exposures and therefore respiratory protection is no needed.         Under an emergency condition where a respirator is deemed necessary, use a NIOSH or equivalent approved device/equipment with appropriate organic or acid gas cartridge.         Protection of hands:         Although not recommended for normal use. The breakthrough time is 1 hr. For cleaning a spill where there is direct contact of the chemical, butyl rubber gloves are recommended 12-15 mil thickness with breakthrough time exceeding 4 hrs. Supplier recommendations should be followed.         Material of gloves         For normal use: nitrile rubber, 11-13 mil thickness         For direct contact with t		0.3 mg/g creatinine
Time: end of shift         Parameter: o-Cresol with hydrolysis (background)         Additional information: The lists that were valid during the creation were used as basis.         Exposure controls         Personal protective equipment:         General protective and hygienic measures:         Keep away from foodstuffs, beverages and feed.         Immediately remove all soiled and contaminated clothing.         Wash hands before breaks and at the end of work.         Store protective clothing separately.         Avoid contact with the skin.         Avoid contact with the skin.         Breathing equipment:         When used as intended with Agilent instruments, the use of the product under normal laboratory conditions and with standard practices does not result in significant airborne exposures and therefore respiratory protection is no needed.         Under an emergency condition where a respirator is deemed necessary, use a NIOSH or equivalent approved device/equipment with appropriate organic or acid gas cartridge.         Protection of hands:         Although not recommended for constant contact with the chemicals or for clean-up, nitrile gloves 11-13 mil thickness are recommended for normal use. The breakthrough time is 1 hr. For cleaning a spill where there is direct contact of the chemical, butyl rubber gloves are recommended 12-15 mil thickness with breakthrough time exceeding 4 hrs. Supplier recommendations should be followed.         Material of gloves       For normal use: nitrile rubber, 11-13 mil thickness		
Parameter: o-Cresol with hydrolysis (background)         Additional information: The lists that were valid during the creation were used as basis.         Exposure controls         Personal protective equipment:         General protective and hygienic measures:         Keep away from foodstuffs, beverages and feed.         Immediately remove all soiled and contaminated clothing.         Wash hands before breaks and at the end of work.         Store protective clothing separately.         Avoid contact with the skin.         Avoid contact with the system.         Breathing equipment:         When used as intended with Agilent instruments, the use of the product under normal laboratory conditions and with standard practices does not result in significant airborne exposures and therefore respiratory protection is no needed.         Under an emergency condition where a respirator is deemed necessary, use a NIOSH or equivalent approved device/equipment with appropriate organic or acid gas cartridge.         Protection of hands:         Although not recommended for constant contact with the chemicals or for clean-up, nitrile gloves 11-13 mil thickness are recommended for normal use. The breakthrough time is 1 hr. For cleaning a spill where there is direct contact of the chemical, butyl rubber gloves are recommended 12-15 mil thickness with breakthrough time exceeding 4 hrs. Supplier recommendations should be followed.         Material of gloves         For normal use: nitrile rubber, 11-13 mil thickness         For normal use:		
Additional information: The lists that were valid during the creation were used as basis. Exposure controls Personal protective equipment: General protective and hygienic measures: Keep away from foodstuffs, beverages and feed. Immediately remove all soiled and contaminated clothing. Wash hands before breaks and at the end of work. Store protective clothing separately. Avoid contact with the skin. Avoid contact with the skin. Breathing equipment: When used as intended with Agilent instruments, the use of the product under normal laboratory conditions and with standard practices does not result in significant airborne exposures and therefore respiratory protection is no needed. Under an emergency condition where a respirator is deemed necessary, use a NIOSH or equivalent approved device/equipment with appropriate organic or acid gas cartridge. Protection of hands: Although not recommended for constant contact with the chemicals or for clean-up, nitrile gloves 11-13 mil thickness are recommended for normal use. The breakthrough time is 1 hr. For cleaning a spill where there is direct contact of the chemical, butyl rubber gloves are recommended 12-15 mil thickness with breakthrough time exceeding 4 hrs. Supplier recommendations should be followed. Material of gloves For normal use: nitrile rubber, 11-13 mil thickness For direct contact with the chemical: butyl rubber, 12-15 mil thickness Penetration time of glove material For normal use: nitrile rubber: 1 hour For direct contact with the chemical: butyl rubber, >4 hours		Parameter: o-Cresol with hydrolysis (background)
Exposure controls Personal protective equipment: General protective and hygienic measures: Keep away from foodstuffs, beverages and feed. Immediately remove all soiled and contaminated clothing. Wash hands before breaks and at the end of work. Store protective clothing separately. Avoid contact with the skin. Avoid contact with the skin. Breathing equipment: When used as intended with Agilent instruments, the use of the product under normal laboratory conditions and with standard practices does not result in significant airborne exposures and therefore respiratory protection is no needed. Under an emergency condition where a respirator is deemed necessary, use a NIOSH or equivalent approved device/equipment with appropriate organic or acid gas cartridge. Protection of hands: Although not recommended for constant contact with the chemicals or for clean-up, nitrile gloves 11-13 mil thickness are recommended for normal use. The breakthrough time is 1 hr. For cleaning a spill where there is direct contact of the chemical, butyl rubber gloves are recommended 12-15 mil thickness with breakthrough time exceeding 4 hrs. Supplier recommendations should be followed. Material of gloves For normal use: nitrile rubber, 11-13 mil thickness For direct contact with the chemical: butyl rubber; >4 hours	Add	
Under an emergency condition where a respirator is deemed necessary, use a NIOSH or equivalent approved device/equipment with appropriate organic or acid gas cartridge. <b>Protection of hands:</b> Although not recommended for constant contact with the chemicals or for clean-up, nitrile gloves 11-13 mil thickness are recommended for normal use. The breakthrough time is 1 hr. For cleaning a spill where there is direct contact of the chemical, butyl rubber gloves are recommended 12-15 mil thickness with breakthrough time exceeding 4 hrs. Supplier recommendations should be followed. <b>Material of gloves</b> For normal use: nitrile rubber, 11-13 mil thickness For direct contact with the chemical: butyl rubber, 12-15 mil thickness <b>Penetration time of glove material</b> For normal use: nitrile rubber: 1 hour For direct contact with the chemical: butyl rubber: >4 hours	Avoi <b>Brea</b> Whe with	id contact with the eyes and skin. <b>Athing equipment:</b> n used as intended with Agilent instruments, the use of the product under normal laboratory conditions and standard practices does not result in significant airborne exposures and therefore respiratory protection is no
Although not recommended for constant contact with the chemicals or for clean-up, nitrile gloves 11-13 mil thickness are recommended for normal use. The breakthrough time is 1 hr. For cleaning a spill where there is direct contact of the chemical, butyl rubber gloves are recommended 12-15 mil thickness with breakthrough time exceeding 4 hrs. Supplier recommendations should be followed. <b>Material of gloves</b> For normal use: nitrile rubber, 11-13 mil thickness For direct contact with the chemical: butyl rubber, 12-15 mil thickness <b>Penetration time of glove material</b> For normal use: nitrile rubber: 1 hour For direct contact with the chemical: butyl rubber: >4 hours	Undo devio	er an emergency condition where a respirator is deemed necessary, use a NIOSH or equivalent approved ce/equipment with appropriate organic or acid gas cartridge.
For normal use: nitrile rubber, 11-13 mil thickness For direct contact with the chemical: butyl rubber, 12-15 mil thickness <b>Penetration time of glove material</b> For normal use: nitrile rubber: 1 hour For direct contact with the chemical: butyl rubber: >4 hours	Althe thick direc exce	bugh not recommended for constant contact with the chemicals or for clean-up, nitrile gloves 11-13 mil teness are recommended for normal use. The breakthrough time is 1 hr. For cleaning a spill where there is at contact of the chemical, butyl rubber gloves are recommended 12-15 mil thickness with breakthrough time eding 4 hrs. Supplier recommendations should be followed.
For direct contact with the chemical: butyl rubber, 12-15 mil thickness <b>Penetration time of glove material</b> For normal use: nitrile rubber: 1 hour For direct contact with the chemical: butyl rubber: >4 hours		
<b>Penetration time of glove material</b> For normal use: nitrile rubber: 1 hour For direct contact with the chemical: butyl rubber: >4 hours		
For normal use: nitrile rubber: 1 hour For direct contact with the chemical: butyl rubber: >4 hours		
		tration time of grove material
		normal use: nitrile rubber: 1 hour



Reviewed on 03/30/2019

Trade name: Kepone Standard (1X1 mL)

(Contd. of page 5)

US

· Eye protection:



· Information on basic physical and c	hemical properties
• General Information • Appearance:	
Form:	Fluid
Color:	Colorless
· Odor:	Aromatic
Odor threshold:	Not determined.
· pH-value:	Not determined.
• Change in condition	
Melting point/Melting range:	-93 °C (-135.4 °F)
<b>Boiling point/Boiling range:</b>	110-111 °C (230-231.8 °F)
· Flash point:	4 °C (39.2 °F)
· Flammability (solid, gaseous):	Not applicable.
Ignition temperature:	535 °C (995 °F)
• Decomposition temperature:	Not determined.
• Auto igniting:	Product is not selfigniting.
Danger of explosion:	Product is not explosive. However, formation of explosive air/vapor mixtures are possible.
· Explosion limits:	
Lower:	1.2 Vol %
Upper:	7 Vol %
· Vapor pressure at 20 °C (68 °F):	29.1 hPa (21.8 mm Hg)
Density at 20 °C (68 °F):	0.865 g/cm <sup>3</sup> (7.21843 lbs/gal)
· Relative density	Not determined.
· Vapor density	Not determined.
· Evaporation rate	Not determined.
· Solubility in / Miscibility with	
Water at 15 °C (59 °F):	0.5 g/l
Partition coefficient (n-octanol/wate	er): Not determined.
· Viscosity:	
Dynamic at 20 °C (68 °F):	0.6 mPas Not determined.



\*

Printing date 03/30/2019

Reviewed on 03/30/2019

Trade name: Kepone Standard (1X1 mL)

		(Contd. of page 6)
<ul> <li>Solvent content: Organic solvents: VOC content:</li> </ul>	100.0 % 99.99 % 999.9 g/l / 8.34 lb/gal	
Solids content: • Other information	0.0 % No further relevant information available.	

## **10 Stability and reactivity**

· Reactivity No further relevant information available.

· Chemical stability

- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

## **11 Toxicological information**

· Information on toxicological effects

#### · Acute toxicity:

· LD/LC50 values that are	relevant for	classification:
---------------------------	--------------	-----------------

## **ATE (Acute Toxicity Estimate)**

Inhalative LC50/4 h 28.1 mg/L (rat)

#### 108-88-3 toluene

	LD50	5,580 mg/kg (rat)
Dermal	LD50	12,124 mg/kg (rabbit)
Inhalative	LC50/4 h	12,124 mg/kg (rabbit) 5,320 mg/L (mouse)
		28.1 mg/L (rat)

#### · Primary irritant effect:

• on the skin: Irritant to skin and mucous membranes.

• on the eye: No irritating effect.

· Sensitization: No sensitizing effects known.

· Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations: Irritant

#### · Carcinogenic categories

· IARC (International Agency for Research on Cancer)	
108-88-3 toluene	3
143-50-0 chlordecone (ISO)	2B
· NTP (National Toxicology Program)	
143-50-0 chlordecone (ISO)	R
	(Contd. on page 8)



Printing date 03/30/2019

Version Number 4

Reviewed on 03/30/2019

Trade name: Kepone Standard (1X1 mL)

· OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients is listed.

## **12 Ecological information**

Printing date 03/30/2019

#### · Toxicity

- · Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- · Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.
- Additional ecological information:

#### · General notes:

Water hazard class 2 (Self-assessment): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

- $\cdot$  Results of PBT and vPvB assessment
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- · Other adverse effects No further relevant information available.

## **13 Disposal considerations**

· Waste treatment methods

· Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

· Uncleaned packagings:

· Recommendation: Disposal must be made according to official regulations.

## 14 Transport information

• Not Regulated, De minimus Quantities	-
· UN-Number	
· DOT, IMDG, IATA	UN1294
· UN proper shipping name	
·DOT	Toluene solution
· IMDG, IATA	TOLUENE solution
· Transport hazard class(es)	
· DOT, IMDG, IATA	
· Class	3 Flammable liquids
	(Contd. on page 9



(Contd. of page 7)

(C- 11 C

\_\_\_\_\_

Printing date 03/30/2019

Version Number 4

Reviewed on 03/30/2019

Trade name: Kepone Standard (1X1 mL)

	(Contd. of pa	ige 8
Label	3	
Packing group		
DOT, IMDG, IATA	II	
Environmental hazards:	Not applicable.	
Special precautions for user	Warning: Flammable liquids	
Danger code (Kemler):	33	
EMS Number:	F-E,S-D	
Stowage Category	В	
Transport in bulk according to Annex	II of	
MARPOL73/78 and the IBC Code	Not applicable.	
Transport/Additional information:		
DOT		
Quantity limitations	On passenger aircraft/rail: 5 L	
	On cargo aircraft only: 60 L	
IMDG		
Limited quantities (LQ)	1L	
Excepted quantities (EQ)	Code: E2	
Excepted quantities (EQ)	Maximum net quantity per inner packaging: 30 ml	
	Maximum net quantity per unter packaging: 500 ml	
UN "Model Regulation":	UN 1294 TOLUENE SOLUTION, 3, II	

## **15 Regulatory information**

· Safety, health and environmental regulations/legislation specific for the substance or mixture · Sara

· Section 355 (extremely hazardous substances):

None of the ingredients is listed.

· Section 313 (Specific toxic chemical listings):

108-88-3 toluene

· TSCA (Toxic Substances Control Act):

108-88-3 toluene

Proposition 65

· Chemicals known to cause cancer:

143-50-0 chlordecone (ISO)

· Chemicals known to cause reproductive toxicity for females:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for males:

None of the ingredients is listed.

· Chemicals known to cause developmental toxicity:

All ingredients are listed.

(Contd. on page 10)



<sup>–</sup> US

Version Number 4

Reviewed on 03/30/2019

Trade name: Kepone Standard (1X1 mL)

(Contd. of page 9)

Π

L

A4

#### · Carcinogenic categories

· EPA (Environmental Protection Agency)

108-88-3 toluene

Printing date 03/30/2019

143-50-0 chlordecone (ISO)

· TLV (Threshold Limit Value established by ACGIH)

108-88-3 toluene

· NIOSH-Ca (National Institute for Occupational Safety and Health)

143-50-0 chlordecone (ISO)

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

#### **16 Other information**

The information contained in this document is based on Agilent's state of knowledge at the time of preparation. No warranty as to its accurateness, completeness or suitability for a particular purpose is expressed or implied.

· Department issuing SDS: Document Control / Regulatory

· Contact: regulatory@ultrasci.com

· Date of preparation / last revision 03/30/2019 / 3

· Abbreviations and acronyms: ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road) IMDG: International Maritime Code for Dangerous Goods DOT: US Department of Transportation IATA: International Air Transport Association ACGIH: American Conference of Governmental Industrial Hygienists EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society) NFPA: National Fire Protection Association (USA) HMIS: Hazardous Materials Identification System (USA) VOC: Volatile Organic Compounds (USA, EU) LC50: Lethal concentration, 50 percent LD50: Lethal dose, 50 percent PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative NIOSH: National Institute for Occupational Safety OSHA: Occupational Safety & Health TLV: Threshold Limit Value PEL: Permissible Exposure Limit REL: Recommended Exposure Limit **BEI: Biological Exposure Limit** Flam. Liq. 2: Flammable liquids - Category 2 Skin Irrit. 2: Skin corrosion/irritation - Category 2 Repr. 2: Reproductive toxicity - Category 2 STOT SE 3: Specific target organ toxicity (single exposure) - Category 3 STOT RE 2: Specific target organ toxicity (repeated exposure) - Category 2 Asp. Tox. 1: Aspiration hazard - Category 1

\* \* Data compared to the previous version altered.



US