Agilent

Printing date 03/30/2019

Version Number 3

Reviewed on 03/30/2019

1 Identification

· Product identifier

· Trade name: Dinocap Standard (1X1 mL)

- · Part number: PST-610M100A01
- · Application of the substance / the mixture Reagents and Standards for Analytical Chemical Laboratory Use
- · Details of the supplier of the safety data sheet

• Manufacturer/Supplier: Agilent Technologies, Inc. 5301 Stevens Creek Blvd. Santa Clara, CA 95051 USA

· Information department:

Telephone: 800-227-9770 e-mail: pdl-msds_author@agilent.com • Emergency telephone number: CHEMTREC®: 1-800-424-9300

2 Hazard(s) identification

· Classification of the substance or mixture

GHS02 Flame

Flam. Liq. 2 H225 Highly flammable liquid and vapor.

GHS06 Skull and crossbones

Acute Tox. 3 H331 Toxic if inhaled.

GHS08 Health hazard

STOT SE 1 H370 Causes damage to organs.

· Label elements

- · GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS).
- · Hazard pictograms



· Signal word Danger

- Hazard-determining components of labeling: methanol
- · Hazard statements

Highly flammable liquid and vapor. Toxic if inhaled. Causes damage to organs.

(Contd. on page 2)

⁻us

Reviewed on 03/30/2019

Trade name: Dinocap Standard (1X1 mL)

· Precautionary statements Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Ground/bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting/equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Do not breathe dust/fume/gas/mist/vapors/spray. Wash thoroughly after handling. Do not eat, drink or smoke when using this product. Use only outdoors or in a well-ventilated area. Wear protective gloves/protective clothing/eye protection/face protection. If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. IF INHALED: Remove person to fresh air and keep comfortable for breathing. IF exposed: Call a POISON CENTER or doctor/physician. Specific treatment (see on this label). In case of fire: Use for extinction: CO2, powder or water spray. Store in a well-ventilated place. Keep container tightly closed. Store in a well-ventilated place. Keep cool. Store locked up. Dispose of contents/container in accordance with local/regional/national/international regulations. · Classification system: · NFPA ratings (scale 0 - 4) Health = 1Fire = 3Reactivity = 0· HMIS-ratings (scale 0 - 4) HEALTH Health = *1*1 FIRE Fire = 33 **REACTIVITY** Reactivity = 0· Other hazards · Results of PBT and vPvB assessment · **PBT:** Not applicable. • **vPvB**: Not applicable.

3 Composition/information on ingredients

· Chemical characterization: Mixtures

· Description: Mixture of the substances listed below with nonhazardous additions.

· Dangerous components:

67-56-1 methanol

99.987%

4 First-aid measures

· Description of first aid measures

· General information:

Immediately remove any clothing soiled by the product.

(Contd. on page 3)



Printing date 03/30/2019

Version Number 3

(Contd. of page 1)

Version Number 3

Reviewed on 03/30/2019

Trade name: Dinocap Standard (1X1 mL)

(Contd. of page 2)

Remove breathing apparatus only after contaminated clothing have been completely removed. In case of irregular breathing or respiratory arrest provide artificial respiration.

· After inhalation:

Supply fresh air or oxygen; call for doctor.

- In case of unconsciousness place patient stably in side position for transportation.
- After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eye contact: Rinse opened eye for several minutes under running water. Then consult a doctor.
- After swallowing: If symptoms persist consult doctor.
- · Information for doctor:

• Most important symptoms and effects, both acute and delayed No further relevant information available.

- Indication of any immediate medical attention and special treatment needed
- No further relevant information available.

5 Fire-fighting measures

- · Extinguishing media
- Suitable extinguishing agents:
- CO2, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- · For safety reasons unsuitable extinguishing agents: Water with full jet
- · Special hazards arising from the substance or mixture

During heating or in case of fire poisonous gases are produced.

- Advice for firefighters
- · Protective equipment: Mouth respiratory protective device.

6 Accidental release measures

· Personal precautions, protective equipment and emergency procedures Mount respiratory protective device. Wear protective equipment. Keep unprotected persons away. · Environmental precautions: Do not allow to enter sewers/ surface or ground water. · Methods and material for containment and cleaning up: Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Dispose contaminated material as waste according to item 13. Ensure adequate ventilation. · Reference to other sections See Section 7 for information on safe handling. See Section 8 for information on personal protection equipment. See Section 13 for disposal information. · Protective Action Criteria for Chemicals · PAC-1: 67-56-1 methanol 530 ppm · PAC-2: 67-56-1 methanol 2,100 ppm · PAC-3: 67-56-1 methanol 7200* ppm

(Contd. on page 4)



Printing date 03/30/2019

Version Number 3

Reviewed on 03/30/2019

Trade name: Dinocap Standard (1X1 mL)

(Contd. of page 3)

7 Handling and storage

· Handling:

· Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace. Open and handle receptacle with care.

- Prevent formation of aerosols.
- Information about protection against explosions and fires: Keep ignition sources away - Do not smoke. Protect against electrostatic charges.
- Keep respiratory protective device available.
- · Conditions for safe storage, including any incompatibilities
- · Storage:
- Requirements to be met by storerooms and receptacles: Store in a cool location.
- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions:
- Keep receptacle tightly sealed.
- Store in cool, dry conditions in well sealed receptacles.
- Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

· Additional information about design of technical systems: No further data; see item 7.

· Control parameters

· Components with limit values that require monitoring at the workplace:		
67-5	56-1 methanol	
PEL	Long-term value: 260 mg/m ³ , 200 ppm	
REL	 Short-term value: 325 mg/m³, 250 ppm Long-term value: 260 mg/m³, 200 ppm Skin 	
TLV	 ⁷ Short-term value: 328 mg/m³, 250 ppm Long-term value: 262 mg/m³, 200 ppm Skin; BEI 	
· Ingr	edients with biological limit values:	
67-5	56-1 methanol	
BEI	15 mg/L Medium: urine Time: end of shift Parameter: Methanol (background, nonspecific)	
· Add	itional information: The lists that were valid during the creation were used as basis.	
· Pers · Gen Keep Imm Was	osure controls sonal protective equipment: eral protective and hygienic measures: p away from foodstuffs, beverages and feed. nediately remove all soiled and contaminated clothing. th hands before breaks and at the end of work. e protective clothing separately. (Contd. on page 5)	



Printing date 03/30/2019

)19

Version Number 3

Reviewed on 03/30/2019

Trade name: Dinocap Standard (1X1 mL)

(Contd. of page 4)

· Breathing equipment:

When used as intended with Agilent instruments, the use of the product under normal laboratory conditions and with standard practices does not result in significant airborne exposures and therefore respiratory protection is not needed.

Under an emergency condition where a respirator is deemed necessary, use a NIOSH or equivalent approved device/equipment with appropriate organic or acid gas cartridge.

· Protection of hands:

Although not recommended for constant contact with the chemicals or for clean-up, nitrile gloves 11-13 mil thickness are recommended for normal use. The breakthrough time is 1 hr. For cleaning a spill where there is direct contact of the chemical, butyl rubber gloves are recommended 12-15 mil thickness with breakthrough times exceeding 4 hrs. Supplier recommendations should be followed.

· Material of gloves

For normal use: nitrile rubber, 11-13 mil thickness

For direct contact with the chemical: butyl rubber, 12-15 mil thickness

· Penetration time of glove material

For normal use: nitrile rubber: 1 hour

For direct contact with the chemical: butyl rubber: >4 hours

• Eye protection:



Tightly sealed goggles

Physical and chemical proper	
Information on basic physical and o	chemical properties
General Information	
Appearance: Form:	Fluid
Form: Color:	Colorless
Odor:	Alcohol-like
Odor threshold:	Not determined.
pH-value:	Not determined.
Change in condition	
Melting point/Melting range:	-98 °C (-144.4 °F)
Boiling point/Boiling range:	64 °C (147.2 °F)
Flash point:	9 °C (48.2 °F)
Flammability (solid, gaseous):	Not applicable.
Ignition temperature:	455 °C (851 °F)
Decomposition temperature:	Not determined.
Auto igniting:	Product is not selfigniting.
Danger of explosion:	Product is not explosive. However, formation of explosive air/vapor mixtures are possible.
Explosion limits:	
Lower:	5.5 Vol %

Agilent

Printing date 03/30/2019

Reviewed on 03/30/2019

Trade name: Dinocap Standard (1X1 mL)

Printing date 03/30/2019

		(Contd. of pa
Upper:	44 Vol %	
· Vapor pressure at 20 °C (68 °F):	100 hPa (75 mm Hg)	
· Density at 20 °C (68 °F):	0.80004 g/cm3 (6.67633 lbs/gal)	
· Relative density	Not determined.	
· Vapor density	Not determined.	
· Evaporation rate	Not determined.	
· Solubility in / Miscibility with		
Water:	Not miscible or difficult to mix.	
· Partition coefficient (n-octanol/wate	r): Not determined.	
· Viscosity:		
Dynamic:	Not determined.	
Kinematic:	Not determined.	
· Solvent content:		
Organic solvents:	100.0 %	
VOC content:	100.00 %	
	800.0 g/l / 6.68 lb/gal	
• Other information	No further relevant information available.	

10 Stability and reactivity

· Reactivity No further relevant information available.

- · Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

11 Toxicological information

· Information on toxicological effects

· Acute toxicity:

· LD/LC50 values that are relevant for classification:

ATE (Acute Toxicity Estimate)

Inhalative LC50/4 h 3 mg/L

67-56-1 methanol

Oral	LD50	5,628 mg/kg (rat)
Dermal	LD50	15,800 mg/kg (rabbit)

39300-45-3 dinocap (ISO)

Oral	LD30	/oo mg/kg (rat)
Dermal	LD50	9,400 mg/kg (rat)

· Primary irritant effect:

• on the skin: No irritant effect.

(Contd. on page 7)



Version Number 3

.

US

Reviewed on 03/30/2019

Trade name: Dinocap Standard (1X1 mL)

(Contd. of page 6)

• on the eye: No irritating effect.

· Sensitization: No sensitizing effects known.

· Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations: Toxic

· Carcinogenic categories

· IARC (International Agency for Research on Cancer)

None of the ingredients is listed.

· NTP (National Toxicology Program)

None of the ingredients is listed.

· OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients is listed.

12 Ecological information

- · Toxicity
- · Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- · Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.
- Additional ecological information:
- · General notes:

Water hazard class 1 (Self-assessment): slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

- · Results of PBT and vPvB assessment
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- · Other adverse effects No further relevant information available.

13 Disposal considerations

- · Waste treatment methods
- · Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packagings:
- Recommendation: Disposal must be made according to official regulations.

14 Transport information

(Contd. on page



Printing date 03/30/2019

Version Number 3

Reviewed on 03/30/2019

Trade name: Dinocap Standard (1X1 mL)

DOT Class 3 Flammable liquids 3, 6.1 IMDG Class 3, 6.1 IMDG Class 3, 6.1 IMDG Class 3 Flammable liquids 3/6.1 IATA Class 3/6.1 IATA Class 3/6.1 I I Environmental hazards: Not applicable. Special precautions for user Marming: Flammable liquids 3d6 Special precautions for user Source (Kemler): 3d6 Supplicable. Special precautions for user Special precautions for user Special precautions for user Special precautions for user Marming: Flammable liquids 3d6 Swage Code SW2 Clear of living quarters. Transport in bulk according to Annex II of MARPOL7378 and the IBC Code Not applicable. Transport/Additional information: DOT		(Contd. of page
DOT by by b	IMDG, IATA	METHANOL
Vertical Sector 3 Flammable liquids Label 3, 6.1 MDG 3 Flammable liquids Vertical Sector 3 Flammable liquids Label 3 Flammable liquids Jass 3 Flammable liquids Label 3/6.1 IATA Vertical Sector Vertical Sector 3 Flammable liquids Jabel 3/6.1 IATA Vertical Sector Vertical Sector 3 Flammable liquids Jabel 3 (6.1) Packing group DOT, MDG, IATA Dott, MDG, IATA II Environmental hazards: Not applicable. Special precautions for user Warning: Flammable liquids Jafe 3/6 Stowage Code SW2 Clear of living quarters. Transport in bulk according to Annex II of MARPOL7/37 and the IBC Code Not applicable. Transport/Additional information: On passenger aircraft/rail: 1 L On cargo aircraft only: 60 L DOT Maximum net quantities (LO) IL Excepted quantities (LO)	Transport hazard class(es)	
Label 3, 6.1 IMDG IMDG IMDG Second Class 3 Flammable liquids Label 3/6.1 IATA Second Second Second IATA Second IATA Second Second Second Second Second Second Presentations Second Presentations Second Presentations Second Presentations Stowage Code SW2 Clear of living quarters. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code Not applicable. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code Not applicable. DOT On passenger aircraft/rail: 1 L On cargo aircraft only: 60 L IMDG	DOT	
Label 3, 6.1 IMDG IMDG IMDG Second Class 3 Flammable liquids Label 3/6.1 IATA Second Second Second IATA Second IATA Second Second Second Second Second Second Presentations Second Presentations Second Presentations Second Presentations Stowage Code SW2 Clear of living quarters. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code Not applicable. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code Not applicable. DOT On passenger aircraft/rail: 1 L On cargo aircraft only: 60 L IMDG		
IMDG Vol Vol Class 3 Flammable liquids John 3/6.1 IATA Vol Vol <	· Class	3 Flammable liquids
View View Class 3 Flammable liquids Label 3/6.1 IATA View View View View View Class 3 Flammable liquids Label 3 (6.1) Packing group Ot DOT, IMDG, IATA II Environmental hazards: Not applicable. Special precautions for user Warning: Flammable liquids Dager code (Kemler): 336 EMS Number: F-E,S-D Stowage Code SW2 Clear of living quarters. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code MARPOL73/78 and the IBC Code Not applicable. Transport/Additional information: On passenger aircraft/rail: 1 L On cargo aircraft only: 60 L IMDG IL Limited quantities (LO) 1L Excepted quantities (EQ) 1L Code: E2 Maximum net quantity per inner packaging: 30 ml	Label	3, 6.1
Label 3/6.1 IATA IATA IATA I Class 3 Flammable liquids Label 3 (6.1) Packing group 3 (6.1) Packing group II Environmental hazards: Not applicable. Special precautions for user Warning: Flammable liquids Danger code (Kemler): 336 EMS Number: F-E,S-D Stowage Code SW2 Clear of living quarters. Stowage Code SW2 Clear of living quarters. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code Not applicable. Transport/Additional information: DOT Quantity limitations DOT Quantity limitations On passenger aircraft/rail: 1 L On cargo aircraft only: 60 L IMDG IL Excepted quantities (LQ) IL Excepted quantities (LQ) IL Maximum net quantity per inner packaging: 30 ml	IMDG	
Label 3/6.1 IATA IATA IATA I Class 3 Flammable liquids Label 3 (6.1) Packing group 3 (6.1) Packing group II Environmental hazards: Not applicable. Special precautions for user Warning: Flammable liquids Danger code (Kemler): 336 EMS Number: F-E,S-D Stowage Code SW2 Clear of living quarters. Stowage Code SW2 Clear of living quarters. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code Not applicable. Transport/Additional information: DOT Quantity limitations DOT Quantity limitations On passenger aircraft/rail: 1 L On cargo aircraft only: 60 L IMDG IL Excepted quantities (LQ) IL Excepted quantities (LQ) IL Maximum net quantity per inner packaging: 30 ml		
IATA Image: Special precautions for user Special precautions for user Varning: Flammable liquids Darger code (Kemler): 336 EMS Number: F-E,S-D Stowage Category B Stowage Code SW2 Clear of living quarters. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code Not applicable. Transport/Additional information: DOT Quantity limitations On passenger aircraft/rail: 1 L On cargo aircraft only: 60 L IMDG Limited quantities (LQ) IL Excepted quantities (LQ) IL Excepted quantities (EQ) IL Code: E2 Maximum net quantity per inner packaging: 30 ml	· Class	
Class 3 Flammable liquids Label 3 (6.1) Packing group Jon, IMDG, IATA Dor, IMDG, IATA II Environmental hazards: Not applicable. Special precautions for user Warning: Flammable liquids Danger code (Kemler): 336 EMS Number: F-E,S-D Stowage Category B Stowage Code SW2 Clear of living quarters. Transport in bulk according to Annex II of Mot applicable. MARPOL73/78 and the IBC Code Not applicable. Transport/Additional information: Not applicable. DOT Quantity limitations On passenger aircraft/rail: 1 L On cargo aircraft only: 60 L On passenger aircraft/rail: 2 M IMDG Limited quantities (LQ) IL Excepted quantities (EQ) IL Code: E2 Maximum net quantity per inner packaging: 30 ml		3/6.1
Label3 (6.1)Packing group DOT, IMDG, IATAIIEnvironmental hazards:Not applicable.Special precautions for userWarning: Flammable liquidsDanger code (Kemler):336EMS Number:F-E,S-DStowage CategoryBStowage CodeSW2 Clear of living quarters.Transport in bulk according to Annex II of MARPOL73/78 and the IBC CodeNot applicable.Transport/Additional information: DOT Quantity limitationsOn passenger aircraft/rail: 1 L On cargo aircraft only: 60 LIMDG Limited quantities (LQ)IL Code: E2 Maximum net quantity per inner packaging: 30 ml	IATA	
Label3 (6.1)Packing group DOT, IMDG, IATAIIEnvironmental hazards:Not applicable.Special precautions for userWarning: Flammable liquidsDanger code (Kemler):336EMS Number:F-E,S-DStowage CategoryBStowage CodeSW2 Clear of living quarters.Transport in bulk according to Annex II of MARPOL73/78 and the IBC CodeNot applicable.Transport/Additional information: DOT Quantity limitationsOn passenger aircraft/rail: 1 L On cargo aircraft only: 60 LIMDG Limited quantities (LQ)IL Code: E2 Maximum net quantity per inner packaging: 30 ml		
Packing group DOT, IMDG, IATA II Environmental hazards: Not applicable. Special precautions for user Warning: Flammable liquids Danger code (Kemler): 336 EMS Number: F-E,S-D Stowage Category B Stowage Code SW2 Clear of living quarters. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code Not applicable. Transport/Additional information: DOT Quantity limitations On passenger aircraft/rail: 1 L On cargo aircraft only: 60 L On passenger aircraft/rail: 1 L On cargo aircraft only: 60 L IMDG Limited quantities (LQ) IL Excepted quantities (EQ) Code: E2 Maximum net quantity per inner packaging: 30 ml	· Class	
DOT, IMDG, IATAIIEnvironmental hazards:Not applicable.Special precautions for userWarning: Flammable liquidsDanger code (Kemler):336EMS Number:F-E,S-DStowage CategoryBStowage CodeSW2 Clear of living quarters.Transport in bulk according to Annex II of MARPOL73/78 and the IBC CodeNot applicable.DOT Quantity limitationsOn passenger aircraft/rail: 1 L On cargo aircraft only: 60 LIMDG Limited quantities (LQ)IL Excepted quantities (EQ)IL Code: E2 Maximum net quantity per inner packaging: 30 ml		3 (6.1)
Special precautions for user Warning: Flammable liquids Danger code (Kemler): 336 EMS Number: F-E,S-D Stowage Category B Stowage Code SW2 Clear of living quarters. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code Not applicable. Transport/Additional information: DOT Quantity limitations On passenger aircraft/rail: 1 L On cargo aircraft only: 60 L IMDG IL Limited quantities (LQ) 1L Excepted quantities (EQ) Code: E2 Maximum net quantity per inner packaging: 30 ml	Packing group DOT, IMDG, IATA	II
Danger code (Kemler):336EMS Number:F-E,S-DStowage CategoryBStowage CodeSW2 Clear of living quarters.Transport in bulk according to Annex II of MARPOL73/78 and the IBC CodeNot applicable.Transport/Additional information:Not applicable.DOT Quantity limitationsOn passenger aircraft/rail: 1 L On cargo aircraft only: 60 LIMDG Limited quantities (LQ)1L Code: E2 Maximum net quantity per inner packaging: 30 ml	Environmental hazards:	Not applicable.
EMS Number:F-E,S-DStowage CategoryBStowage CodeSW2 Clear of living quarters.Transport in bulk according to Annex II of MARPOL73/78 and the IBC CodeNot applicable.Transport/Additional information:Not applicable.DOT Quantity limitationsOn passenger aircraft/rail: 1 L On cargo aircraft only: 60 LIMDG Limited quantities (LQ)IL Code: E2 Maximum net quantity per inner packaging: 30 ml	Special precautions for user	
Stowage Category Stowage CodeBStowage CodeSW2 Clear of living quarters.Transport in bulk according to Annex II of MARPOL73/78 and the IBC CodeNot applicable.Transport/Additional information:Not applicable.DOT Quantity limitationsOn passenger aircraft/rail: 1 L On cargo aircraft only: 60 LIMDG Limited quantities (LQ)1L Code: E2 Maximum net quantity per inner packaging: 30 ml		
Stowage CodeSW2 Clear of living quarters.Transport in bulk according to Annex II of MARPOL73/78 and the IBC CodeNot applicable.Transport/Additional information:Not applicable.DOT Quantity limitationsOn passenger aircraft/rail: 1 L On cargo aircraft only: 60 LIMDG Limited quantities (LQ)1L Code: E2 Maximum net quantity per inner packaging: 30 ml		
Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code Not applicable. Transport/Additional information: Not applicable. DOT Quantity limitations On passenger aircraft/rail: 1 L On cargo aircraft only: 60 L IMDG Limited quantities (LQ) 1L Code: E2 Maximum net quantity per inner packaging: 30 ml	Stowage Category Stowage Code	
MARPOL73/78 and the IBC Code Not applicable. Transport/Additional information: On passenger aircraft/rail: 1 L DOT On passenger aircraft/rail: 1 L Quantity limitations On passenger aircraft/rail: 1 L IMDG IL Excepted quantities (LQ) 1L Excepted quantities (EQ) Code: E2 Maximum net quantity per inner packaging: 30 ml	Transport in bulk according to Annex	
DOT On passenger aircraft/rail: 1 L Quantity limitations On passenger aircraft/rail: 1 L On cargo aircraft only: 60 L IL IMDG IL Excepted quantities (LQ) 1L Excepted quantities (EQ) Code: E2 Maximum net quantity per inner packaging: 30 ml		
DOT On passenger aircraft/rail: 1 L Quantity limitations On passenger aircraft/rail: 1 L On cargo aircraft only: 60 L IMDG Limited quantities (LQ) 1L Excepted quantities (EQ) Code: E2 Maximum net quantity per inner packaging: 30 ml	Transport/Additional information:	
Quantity limitations On passenger aircraft/rail: 1 L On cargo aircraft only: 60 L IMDG IL Excepted quantities (LQ) 1L Excepted quantities (EQ) Code: E2 Maximum net quantity per inner packaging: 30 ml	-	
IMDG Limited quantities (LQ) 1L Excepted quantities (EQ) Code: E2 Maximum net quantity per inner packaging: 30 ml	Quantity limitations	
Limited quantities (LQ)1LExcepted quantities (EQ)Code: E2Maximum net quantity per inner packaging: 30 ml	IMDC	
Excepted quantities (EQ) Code: E2 Maximum net quantity per inner packaging: 30 ml		11.
Maximum net quantity per inner packaging: 30 ml		
	······································	



Printing date 03/30/2019

Version Number 3

Reviewed on 03/30/2019

Trade name: Dinocap Standard (1X1 mL)

· UN "Model Regulation":

Printing date 03/30/2019

UN 1230 METHANOL, 3 (6.1), II

15 Regulatory information

 \cdot Safety, health and environmental regulations/legislation specific for the substance or mixture \cdot Sara

· Section 355 (extremely hazardous substances):

None of the ingredients is listed.

· Section 313 (Specific toxic chemical listings):

All ingredients are listed.

· TSCA (Toxic Substances Control Act):

67-56-1 methanol

· Proposition 65

· Chemicals known to cause cancer:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for females:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for males:

None of the ingredients is listed.

· Chemicals known to cause developmental toxicity:

All ingredients are listed.

· Carcinogenic categories

· EPA (Environmental Protection Agency)

None of the ingredients is listed.

· TLV (Threshold Limit Value established by ACGIH)

None of the ingredients is listed.

· NIOSH-Ca (National Institute for Occupational Safety and Health)

None of the ingredients is listed.

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

The information contained in this document is based on Agilent's state of knowledge at the time of preparation. No warranty as to its accurateness, completeness or suitability for a particular purpose is expressed or implied.

· Department issuing SDS: Document Control / Regulatory

· Contact: regulatory@ultrasci.com

• Date of preparation / last revision 03/30/2019 / 2

• Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

ACGIH: American Conference of Governmental Industrial Hygienists



Version Number 3

(Contd. of page 8)

Reviewed on 03/30/2019

Printing date 03/30/2019

Version Number 3

Trade name: Dinocap Standard (1X1 mL)

	(Contd. of page 9)
EINECS: European Inventory of Existing Commercial Chemical Substances	
ELINCS: European List of Notified Chemical Substances	
CAS: Chemical Abstracts Service (division of the American Chemical Society)	
NFPA: National Fire Protection Association (USA)	
HMIS: Hazardous Materials Identification System (USA)	
VOC: Volatile Organic Compounds (USA, EU)	
LC50: Lethal concentration, 50 percent	
LD50: Lethal dose, 50 percent	
PBT: Persistent, Bioaccumulative and Toxic	
vPvB: very Persistent and very Bioaccumulative	
NIOSH: National Institute for Occupational Safety	
OSHA: Occupational Safety & Health	
TLV: Threshold Limit Value	
PEL: Permissible Exposure Limit	
REL: Recommended Exposure Limit	
BEI: Biological Exposure Limit	
Flam. Liq. 2: Flammable liquids – Category 2	
Acute Tox. 3: Acute toxicity – Category 3	
STOT SE 1: Specific target organ toxicity (single exposure) – Category 1	
** Data compared to the previous version altered.	
• •	US

