

Printing date 03/24/2019 Version Number 2 Reviewed on 03/24/2019

1 Identification

· Product identifier

Trade name: Bis(2-chloroethyl) Ether

· Part number: RCC-088

· CAS Number: 111-44-4 · EC number:

203-870-1 • Index number: 603-029-00-2

- · Application of the substance / the mixture Reagents and Standards for Analytical Chemical Laboratory Use
- · Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

Agilent Technologies, Inc. 5301 Stevens Creek Blvd. Santa Clara, CA 95051 USA

· Information department:

Telephone: 800-227-9770

e-mail: pdl-msds author@agilent.com

· Emergency telephone number: CHEMTREC®: 1-800-424-9300

2 Hazard(s) identification

· Classification of the substance or mixture



GHS02 Flame

Flam. Liq. 3 H226 Flammable liquid and vapor.



GHS06 Skull and crossbones

Acute Tox. 2 H300 Fatal if swallowed.

Acute Tox. 1 H310 Fatal in contact with skin.

Acute Tox. 2 H330 Fatal if inhaled.



GHS08 Health hazard

Carc. 2 H351 Suspected of causing cancer.

- · Label elements
- · GHS label elements The substance is classified and labeled according to the Globally Harmonized System (GHS).
- · Hazard pictograms







GHS02 GHS06

GHS08

(Contd. on page 2)



Printing date 03/24/2019 Version Number 2 Reviewed on 03/24/2019

Trade name: Bis(2-chloroethyl) Ether

(Contd. of page 1)

· Signal word Danger

· Hazard-determining components of labeling:

bis(2-chloroethyl) ether

· Hazard statements

Flammable liquid and vapor.

Fatal if swallowed, in contact with skin or if inhaled.

Suspected of causing cancer.

· Precautionary statements

Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood.

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

Ground/bond container and receiving equipment.

Use explosion-proof electrical/ventilating/lighting/equipment.

Use only non-sparking tools.

Take precautionary measures against static discharge.

Do not breathe dust/fume/gas/mist/vapors/spray.

Do not get in eyes, on skin, or on clothing.

Wash thoroughly after handling.

Do not eat, drink or smoke when using this product.

Use only outdoors or in a well-ventilated area.

Wear protective gloves/protective clothing/eye protection/face protection.

[In case of inadequate ventilation] wear respiratory protection.

If swallowed: Immediately call a poison center/doctor.

Rinse mouth.

If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

IF exposed or concerned: Get medical advice/attention.

Specific treatment is urgent (see on this label).

Take off immediately all contaminated clothing and wash it before reuse.

In case of fire: Use for extinction: CO2, powder or water spray.

Store in a well-ventilated place. Keep container tightly closed.

Store in a well-ventilated place. Keep cool.

Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

- · Classification system:
- · NFPA ratings (scale 0 4)



Health = 3Fire = 2Reactivity = 0

· HMIS-ratings (scale 0 - 4)



Health = 3 Fire = 2 Reactivity = 0

- · Other hazards
- · Results of PBT and vPvB assessment
- · PBT: Not applicable.

(Contd. on page 3)



Printing date 03/24/2019 Version Number 2 Reviewed on 03/24/2019

Trade name: Bis(2-chloroethyl) Ether

· **vPvB**: Not applicable.

(Contd. of page 2)

3 Composition/information on ingredients

· Chemical characterization: Substances

· CAS No. Description

111-44-4 bis(2-chloroethyl) ether

· Identification number(s)

• EC number: 203-870-1 • Index number: 603-029-00-2

4 First-aid measures

· Description of first aid measures

· General information:

Immediately remove any clothing soiled by the product.

Remove breathing apparatus only after contaminated clothing have been completely removed.

In case of irregular breathing or respiratory arrest provide artificial respiration.

· After inhalation:

Supply fresh air or oxygen; call for doctor.

In case of unconsciousness place patient stably in side position for transportation.

- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eye contact: Rinse opened eye for several minutes under running water. Then consult a doctor.
- · After swallowing: Do not induce vomiting; immediately call for medical help.
- · Information for doctor:
- · Most important symptoms and effects, both acute and delayed No further relevant information available.
- · Indication of any immediate medical attention and special treatment needed

No further relevant information available.

5 Fire-fighting measures

- · Extinguishing media
- · Suitable extinguishing agents:

CO2, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

- · For safety reasons unsuitable extinguishing agents: Water with full jet
- · Special hazards arising from the substance or mixture

During heating or in case of fire poisonous gases are produced.

- · Advice for firefighters
- · Protective equipment: Mouth respiratory protective device.

6 Accidental release measures

· Personal precautions, protective equipment and emergency procedures

Mount respiratory protective device.

Wear protective equipment. Keep unprotected persons away.

- Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- · Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

(Contd. on page 4)



Printing date 03/24/2019 Version Number 2 Reviewed on 03/24/2019

Trade name: Bis(2-chloroethyl) Ether

(Contd. of page 3)

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

· Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

· Protective Action Criteria for Chemicals

PAC-1:	
	10 ppm
· PAC-2:	
	25 ppm
· PAC-3:	
	250 ppm

7 Handling and storage

- · Handling:
- · Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Open and handle receptacle with care.

Prevent formation of aerosols.

· Information about protection against explosions and fires:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

Keep respiratory protective device available.

- · Conditions for safe storage, including any incompatibilities
- · Storage:
- Requirements to be met by storerooms and receptacles: No special requirements.
- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions: Keep receptacle tightly sealed.
- · Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

- · Additional information about design of technical systems: No further data; see item 7.
- · Control parameters

· Components with	limit values	that require	monitoring at	the workplace:
-------------------	--------------	--------------	---------------	----------------

111-44-4 bis(2-chloroethyl) ether

PEL	Ceiling limit value: 90 mg/m³, 15 ppm Skin
REL	Short-term value: 60 mg/m³, 10 ppm Long-term value: 30 mg/m³, 5 ppm Skin; See Pocket Guide App. A
TLV	Short-term value: 58 mg/m³, 10 ppm Long-term value: 29 mg/m³, 5 ppm Skin

(Contd. on page 5)



Printing date 03/24/2019 Version Number 2 Reviewed on 03/24/2019

Trade name: Bis(2-chloroethyl) Ether

(Contd. of page 4)

- · Additional information: The lists that were valid during the creation were used as basis.
- · Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Store protective clothing separately.

Avoid contact with the eyes and skin.

· Breathing equipment:

When used as intended with Agilent instruments, the use of the product under normal laboratory conditions and with standard practices does not result in significant airborne exposures and therefore respiratory protection is not needed

Under an emergency condition where a respirator is deemed necessary, use a NIOSH or equivalent approved device/equipment with appropriate organic or acid gas cartridge.

· Protection of hands:

Although not recommended for constant contact with the chemicals or for clean-up, nitrile gloves 11-13 mil thickness are recommended for normal use. The breakthrough time is 1 hr. For cleaning a spill where there is direct contact of the chemical, butyl rubber gloves are recommended 12-15 mil thickness with breakthrough times exceeding 4 hrs. Supplier recommendations should be followed.

· Material of gloves

For normal use: nitrile rubber, 11-13 mil thickness

For direct contact with the chemical: butyl rubber, 12-15 mil thickness

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer.

· Penetration time of glove material

For normal use: nitrile rubber: 1 hour

For direct contact with the chemical: butyl rubber: >4 hours

· Eye protection:



Tightly sealed goggles

9 Physical and chemical properties

- · Information on basic physical and chemical properties
- · General Information
- · Appearance:

Form: Fluid
Color: Colorless
Odor: Pungent
Odor threshold: Not determined.

· pH-value: Not determined.

· Change in condition

Melting point/Melting range: -50 °C (-58 °F) Boiling point/Boiling range: 177 °C (350.6 °F)

(Contd. on page 6)



Printing date 03/24/2019 Version Number 2 Reviewed on 03/24/2019

Trade name: Bis(2-chloroethyl) Ether

	(Contd. of p	age
· Flash point:	55 °C (131 °F)	
· Flammability (solid, gaseous):	Not applicable.	
· Ignition temperature:	365 °C (689 °F)	
· Decomposition temperature:	Not determined.	
· Auto igniting:	Not determined.	
· Danger of explosion:	Not determined.	
· Explosion limits:		
Lower:	Not determined.	
Upper:	Not determined.	
· Vapor pressure at 20 °C (68 °F):	1.1 hPa (0.8 mm Hg)	
· Density at 20 °C (68 °F):	1.22 g/cm³ (10.1809 lbs/gal)	
· Relative density	Not determined.	
· Vapor density	Not determined.	
· Evaporation rate	Not determined.	
· Solubility in / Miscibility with		
Water at 20 °C (68 °F):	1.1 g/l	
Partition coefficient (n-octanol/water): Not determined.		
Viscosity:		
Dynamic:	Not determined.	
Kinematic:	Not determined.	
VOC content:	0.00 %	
	0.0 g/l / 0.00 lb/gal	
· Other information	No further relevant information available.	

10 Stability and reactivity

- · Reactivity No further relevant information available.
- · Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

11 Toxicological information

- · Information on toxicological effects
- · Acute toxicity:

LD/LC50 values that are relevant for classification:		
ATE (Acute Toxicity Estimate)		
Oral	LD50	75 mg/kg (rat)
Dermal	LD50	90 mg/kg (rabbit)
Inhalative	LC50/4 h	330 mg/L (rat)

(Contd. on page 7)



Printing date 03/24/2019 Version Number 2 Reviewed on 03/24/2019

Trade name: Bis(2-chloroethyl) Ether

(Contd. of page 6)

111-44-4 bis(2-chloroethyl) etherOralLD5075 mg/kg (rat)DermalLD5090 mg/kg (rabbit)

Inhalative LC50/4 h 330 mg/L (rat)

- · Primary irritant effect:
- · on the skin: No irritant effect.
- · on the eye: No irritating effect.
- · Sensitization: No sensitizing effects known.
- · Additional toxicological information: Danger through skin absorption.
- · Carcinogenic categories
- · IARC (International Agency for Research on Cancer)

3

· NTP (National Toxicology Program)

Substance is not listed.

· OSHA-Ca (Occupational Safety & Health Administration)

Substance is not listed.

12 Ecological information

- · Toxicity
- · Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- · Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.
- Additional ecological information:
- · General notes:

Water hazard class 2 (Assessment by list): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

- · Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.
- · Other adverse effects No further relevant information available.

13 Disposal considerations

- · Waste treatment methods
- · Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packagings:
- · Recommendation: Disposal must be made according to official regulations.

US



Printing date 03/24/2019 Version Number 2 Reviewed on 03/24/2019

Trade name: Bis(2-chloroethyl) Ether

(Contd. of page 7)

14 Transport information	
· UN-Number	
· DOT, IMDG, IATA	UN1916
· UN proper shipping name	
·DOT	2,2'-Dichlorodiethyl ether
· IMDG, IATA	2,2'-DICHLORODIETHYL ETHER
· Transport hazard class(es)	
· DOT	
· Class	6.1 Toxic substances
· Label	6.1, 3
· IMDG	
· Class	6.1 Toxic substances
· Label	6.1/3
·IATA	
· Class	6.1 Toxic substances
· Label	6.1 (3)
· Packing group	
· DOT, IMDG, IATA	II
· Environmental hazards:	Not applicable.
· Special precautions for user	Warning: Toxic substances
Danger code (Kemler):	63
· EMS Number: · Stowage Category	6.1-01 A
· Transport in bulk according to Annex l	
MARPOL73/78 and the IBC Code	Not applicable.
· Transport/Additional information:	
· DOT	
· Quantity limitations	On passenger aircraft/rail: 5 L
· Hazardous substance:	On cargo aircraft only: 60 L 10 lbs, 4.54 kg
Trazaruous substance:	
	(Contd. on page 9)



Printing date 03/24/2019 Version Number 2 Reviewed on 03/24/2019

Trade name: Bis(2-chloroethyl) Ether

(Contd. of page 8)

· IMDG

Limited quantities (LQ)
 Excepted quantities (EQ)
 Code: E4

Maximum net quantity per inner packaging: 1 ml Maximum net quantity per outer packaging: 500 ml

· UN "Model Regulation": UN 1916 2,2'-DICHLORODIETHYL ETHER, 6.1 (3), II

15 Regulatory information

- · Safety, health and environmental regulations/legislation specific for the substance or mixture
- Sara
- · Section 355 (extremely hazardous substances):

Substance is listed.

· Section 313 (Specific toxic chemical listings):

Substance is listed.

· TSCA (Toxic Substances Control Act):

Substance is listed.

- · Proposition 65
- · Chemicals known to cause cancer:

Substance is listed.

· Chemicals known to cause reproductive toxicity for females:

Substance is not listed.

· Chemicals known to cause reproductive toxicity for males:

Substance is not listed.

· Chemicals known to cause developmental toxicity:

Substance is not listed.

· Carcinogenic categories

· EPA (Environmental Protection Agency)

B2

· TLV (Threshold Limit Value established by ACGIH)

A4

· NIOSH-Ca (National Institute for Occupational Safety and Health)

Substance is listed.

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

The information contained in this document is based on Agilent's state of knowledge at the time of preparation. No warranty as to its accurateness, completeness or suitability for a particular purpose is expressed or implied.

- · Department issuing SDS: Document Control / Regulatory
- · Contact: regulatory@ultrasci.com
- · Date of preparation / last revision 03/24/2019 / 1

(Contd. on page 10)



Printing date 03/24/2019 Version Number 2 Reviewed on 03/24/2019

Trade name: Bis(2-chloroethyl) Ether

(Contd. of page 9)

· Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

ACGIH: American Conference of Governmental Industrial Hygienists EINECS: European Inventory of Existing Commercial Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA) HMIS: Hazardous Materials Identification System (USA)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety & Health TLV: Threshold Limit Value PEL: Permissible Exposure Limit REL: Recommended Exposure Limit Flam. Lig. 3: Flammable liquids – Cate

Flam. Liq. 3: Flammable liquids – Category 3 Acute Tox. 2: Acute toxicity – Category 2 Acute Tox. 1: Acute toxicity – Category 1 Carc. 2: Carcinogenicity – Category 2

* Data compared to the previous version altered.

US ·