Printing date 03/30/2019

Version Number 3

Reviewed on 03/30/2019

### **1** Identification

Agilent

· Product identifier

· Trade name: ASTM D6584 Standard (1X1 mL)

- · Part number: RGO-314-1
- · Application of the substance / the mixture Reagents and Standards for Analytical Chemical Laboratory Use
- · Details of the supplier of the safety data sheet

• Manufacturer/Supplier: Agilent Technologies, Inc. 5301 Stevens Creek Blvd. Santa Clara, CA 95051 USA

· Information department:

Telephone: 800-227-9770 e-mail: pdl-msds\_author@agilent.com • Emergency telephone number: CHEMTREC®: 1-800-424-9300

## 2 Hazard(s) identification

· Classification of the substance or mixture

GHS02 Flame

Flam. Liq. 2 H225 Highly flammable liquid and vapor.



Acute Tox. 4 H302 Harmful if swallowed.

Acute Tox. 4 H312 Harmful in contact with skin.

Acute Tox. 4 H332 Harmful if inhaled.

· Label elements

· GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS).

· Hazard pictograms



· Signal word Danger

Hazard-determining components of labeling: pyridine
Hazard statements
Highly flammable liquid and vapor.
Harmful if swallowed, in contact with skin or if inhaled.
Precautionary statements
Keep away from heat/sparks/open flames/hot surfaces. - No smoking.
Keep container tightly closed.
Ground/bond container and receiving equipment.

Use explosion-proof electrical/ventilating/lighting/equipment.

(Contd. on page 2)

- 05

Version Number 3

Reviewed on 03/30/2019

(Contd. of page 1)

#### Trade name: ASTM D6584 Standard (1X1 mL)

Use only non-sparking tools.

Take precautionary measures against static discharge. Avoid breathing dust/fume/gas/mist/vapors/spray Wash thoroughly after handling. Do not eat, drink or smoke when using this product. Use only outdoors or in a well-ventilated area. Wear protective gloves/protective clothing/eye protection/face protection. If swallowed: Call a poison center/doctor if you feel unwell. If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. IF INHALED: Remove person to fresh air and keep comfortable for breathing. Specific treatment (see on this label). Rinse mouth. Take off contaminated clothing and wash it before reuse. In case of fire: Use for extinction: CO2, powder or water spray. Store in a well-ventilated place. Keep cool. Dispose of contents/container in accordance with local/regional/national/international regulations. · Classification system: · NFPA ratings (scale 0 - 4) Health = 1Fire = 3Reactivity = 0· HMIS-ratings (scale 0 - 4)



- · Other hazards
- · Results of PBT and vPvB assessment
- **PBT:** Not applicable.
- **vPvB:** Not applicable.

## **3** Composition/information on ingredients

- · Chemical characterization: Mixtures
- Description: Mixture of the substances listed below with nonhazardous additions.
- · Dangerous components:
- 110-86-1 pyridine

### 99.791%

### **4 First-aid measures**

### · Description of first aid measures

- · General information:
- Immediately remove any clothing soiled by the product.

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

#### · After inhalation:

Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist.

(Contd. on page 3)



Printing date 03/30/2019

Reviewed on 03/30/2019

### Trade name: ASTM D6584 Standard (1X1 mL)

 $(Contd. \ of \ page \ 2)$ 

- In case of unconsciousness place patient stably in side position for transportation.
- After skin contact: Immediately rinse with water.
- · After eye contact: Rinse opened eye for several minutes under running water.
- After swallowing: Immediately call a doctor.

· Information for doctor:

- · Most important symptoms and effects, both acute and delayed No further relevant information available.
- · Indication of any immediate medical attention and special treatment needed

No further relevant information available.

### **5** Fire-fighting measures

- · Extinguishing media
- Suitable extinguishing agents:
- CO2, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- For safety reasons unsuitable extinguishing agents: Water with full jet
- Special hazards arising from the substance or mixture No further relevant information available.
- · Advice for firefighters
- Protective equipment: Mouth respiratory protective device.

#### **6** Accidental release measures

· Personal	precautions, protective equipment and emergency procedures	
Wear prot	tective equipment. Keep unprotected persons away.	
·Environn	nental precautions: Do not allow to enter sewers/ surface or ground water.	
· Methods	and material for containment and cleaning up:	
Absorb w	ith liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).	
Dispose c	ontaminated material as waste according to item 13.	
Ensure ad	lequate ventilation.	
· Referenc	e to other sections	
See Section	on 7 for information on safe handling.	
See Section	on 8 for information on personal protection equipment.	
See Section	on 13 for disposal information.	
· Protectiv	e Action Criteria for Chemicals	
· PAC-1:		
110-86-1	pyridine	3 ppm
56-81-5	glycerol	45 mg/m <sup>3</sup>
· PAC-2:		
110-86-1	pyridine	19 ppm
56-81-5	glycerol	180 mg/m <sup>3</sup>
· PAC-3:		
110-86-1	pyridine	3600* ppm
56-81-5	glycerol	1,100 mg/m <sup>3</sup>
	1	

(Contd. on page 4)



Printing date 03/30/2019

Version Number 3

Version Number 3

Reviewed on 03/30/2019

Trade name: ASTM D6584 Standard (1X1 mL)

(Contd. of page 3)

#### 7 Handling and storage

· Handling:

- **Precautions for safe handling** Ensure good ventilation/exhaustion at the workplace. Prevent formation of aerosols.
- Information about protection against explosions and fires: Keep ignition sources away - Do not smoke. Protect against electrostatic charges.
- · Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles: Store in a cool location.
- · Information about storage in one common storage facility: Not required.
- Further information about storage conditions:
- Keep receptacle tightly sealed.

Store in cool, dry conditions in well sealed receptacles.

• Specific end use(s) No further relevant information available.

#### **8 Exposure controls/personal protection**

• Additional information about design of technical systems: No further data; see item 7.

· Control parameters

· Components with limit values that require monitoring at the workplace:

#### 110-86-1 pyridine

PEL Long-term value: 15 mg/m<sup>3</sup>, 5 ppm

REL Long-term value: 15 mg/m<sup>3</sup>, 5 ppm

TLV Long-term value: 3.1 mg/m<sup>3</sup>, 1 ppm

• Additional information: The lists that were valid during the creation were used as basis.

#### · Exposure controls

#### · Personal protective equipment:

· General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Avoid contact with the eyes and skin.

· Breathing equipment:

When used as intended with Agilent instruments, the use of the product under normal laboratory conditions and with standard practices does not result in significant airborne exposures and therefore respiratory protection is not needed.

Under an emergency condition where a respirator is deemed necessary, use a NIOSH or equivalent approved device/equipment with appropriate organic or acid gas cartridge.

Protection of hands:

Although not recommended for constant contact with the chemicals or for clean-up, nitrile gloves 11-13 mil thickness are recommended for normal use. The breakthrough time is 1 hr. For cleaning a spill where there is direct contact of the chemical, butyl rubber gloves are recommended 12-15 mil thickness with breakthrough times exceeding 4 hrs. Supplier recommendations should be followed.

US



#### Printing date 03/30/2019

Reviewed on 03/30/2019

#### Trade name: ASTM D6584 Standard (1X1 mL)

(Contd. of page 4)

· Material of gloves

For normal use: nitrile rubber, 11-13 mil thickness

For direct contact with the chemical: butyl rubber, 12-15 mil thickness

· Penetration time of glove material

For normal use: nitrile rubber: 1 hour

- For direct contact with the chemical: butyl rubber: >4 hours
- Eye protection:

Tightly sealed goggles

# 9 Physical and chemical properties

Appearance:	
Form:	Fluid
Color:	Colorless
Odor:	Unpleasant Not determined.
Odor threshold:	Not determined.
pH-value:	Not determined.
Change in condition	
Melting point/Melting range:	-41.8 °C (-43.2 °F)
<b>Boiling point/Boiling range:</b>	115.5 °C (239.9 °F)
Flash point:	17 °C (62.6 °F)
Flammability (solid, gaseous):	Not applicable.
Ignition temperature:	550 °C (1,022 °F)
Decomposition temperature:	Not determined.
Auto igniting:	Product is not selfigniting.
Danger of explosion:	Product is not explosive. However, formation of explosive air/vapor mixtures are possible.
Explosion limits:	
Lower:	1.7 Vol %
Upper:	10.6 Vol %
Vapor pressure at 20 °C (68 °F):	20 hPa (15 mm Hg)
Density at 20 °C (68 °F):	0.978 g/cm <sup>3</sup> (8.16141 lbs/gal)
Relative density	Not determined.
Vapor density	Not determined.
Evaporation rate	Not determined.
Solubility in / Miscibility with	
Water:	Not miscible or difficult to mix.
Partition coefficient (n-octanol/wate	er): Not determined.



Printing date 03/30/2019

Version Number 3

Review

Reviewed on 03/30/2019

Trade name: ASTM D6584 Standard (1X1 mL)

	(Contd. of	f page
· Viscosity:		
Dynamic:	Not determined.	
Kinematic:	Not determined.	
Solvent content:		
<b>Organic solvents:</b>	0.0 %	
VOC content:	0.00 %	
	0.0 g/l / 0.00 lb/gal	
Solids content:	0.0 %	
• Other information	No further relevant information available.	

## **10** Stability and reactivity

· Reactivity No further relevant information available.

- · Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

### **11 Toxicological information**

· Information on toxicological effects

· Acute toxicity:

· LD/LC50 values that are relevant for classification:

### **ATE (Acute Toxicity Estimate)**

Oral	LD50	893 mg/kg (rat)
Dermal	LD50	1,123 mg/kg (rabbit)
Inhalative	LC50/4 h	11 mg/L

#### 110-86-1 pyridine

Oral	LD50	891 mg/kg (rat)
Dermal	LD50	1,121 mg/kg (rabbit)

· Primary irritant effect:

- on the skin: No irritant effect.
- on the eye: No irritating effect.
- · Sensitization: No sensitizing effects known.
- · Additional toxicological information: Harmful

· Carcinogenic categories

<ul> <li>IARC (International</li> </ul>	Agency for	Research on	Cancer)

110-86-1 pyridine

· NTP (National Toxicology Program)

None of the ingredients is listed.

(Contd. on page 7)

3



Printing date 03/30/2019

Version Number 3

US

Version Number 3

Reviewed on 03/30/2019

Trade name: ASTM D6584 Standard (1X1 mL)

· OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients is listed.

### **12 Ecological information**

Printing date 03/30/2019

#### · Toxicity

- · Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- · Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.
- Additional ecological information:

#### · General notes:

Water hazard class 2 (Self-assessment): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

- $\cdot$  Results of PBT and vPvB assessment
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- · Other adverse effects No further relevant information available.

### **13 Disposal considerations**

· Waste treatment methods

· Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

· Uncleaned packagings:

· Recommendation: Disposal must be made according to official regulations.

### 14 Transport information

· Not Regulated, De minimus Quantities	-
· UN-Number	
· DOT, IMDG, IATA	UN1282
· UN proper shipping name	
·DOT	Pyridine solution
· IMDG, IATA	PYRIDINE solution
· Transport hazard class(es)	
· DOT, IMDG, IATA	
· Class	3 Flammable liquids
	(Contd. on page 8)



(Contd. of page 6)

Version Number 3

Reviewed on 03/30/2019

#### Trade name: ASTM D6584 Standard (1X1 mL)

	(Contd. of page
Label	3
Packing group	
DOT, IMDG, IATA	II
Environmental hazards:	Not applicable.
Special precautions for user	Warning: Flammable liquids
Danger code (Kemler):	33
EMS Number:	F-E,S-D
Stowage Category	В
Stowage Code	SW2 Clear of living quarters.
Transport in bulk according to Annex	
MARPOL73/78 and the IBC Code	Not applicable.
Transport/Additional information:	
DOT	
Quantity limitations	On passenger aircraft/rail: 5 L
	On cargo aircraft only: 60 L
IMDG	
Limited quantities (LQ)	1L
Excepted quantities (EQ)	Code: E2
	Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per outer packaging: 500 ml
UN "Model Regulation":	UN 1282 PYRIDINE SOLUTION, 3, II

# **15 Regulatory information**

 $\cdot$  Safety, health and environmental regulations/legislation specific for the substance or mixture  $\cdot$  Sara

None of	f the ingredients is listed.	
· Section	313 (Specific toxic chemical listings):	
110-86-1	1 pyridine	
· TSCA (	(Toxic Substances Control Act):	
110-86-1	1 pyridine	
111-03-5	5 monoolein	
122-32-7	7 triolein	
56-81-5	5 glycerol	
· Proposit	ition 65	
· Chemica	cals known to cause cancer:	
110-86-1	-1 pyridine	
· Chemica	cals known to cause reproductive toxicity for females:	
None of	f the ingredients is listed.	
· Chemica	cals known to cause reproductive toxicity for males:	
	f the ingredients is listed.	



Printing date 03/30/2019

Printing date 03/30/2019

#### Version Number 3

Reviewed on 03/30/2019

(Contd. of page 8)

A3

Trade name: ASTM D6584 Standard (1X1 mL)

· Chemicals known to cause developmental toxicity:

None of the ingredients is listed.

#### · Carcinogenic categories

· EPA (Environmental Protection Agency)

None of the ingredients is listed.

· TLV (Threshold Limit Value established by ACGIH)

110-86-1 pyridine

· NIOSH-Ca (National Institute for Occupational Safety and Health)

None of the ingredients is listed.

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

### **16 Other information**

The information contained in this document is based on Agilent's state of knowledge at the time of preparation. No warranty as to its accurateness, completeness or suitability for a particular purpose is expressed or implied.

· Department issuing SDS: Document Control / Regulatory

· Contact: regulatory@ultrasci.com

· Date of preparation / last revision 03/30/2019 / 2 · Abbreviations and acronyms: ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road) IMDG: International Maritime Code for Dangerous Goods DOT: US Department of Transportation IATA: International Air Transport Association ACGIH: American Conference of Governmental Industrial Hygienists EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society) NFPA: National Fire Protection Association (USA) HMIS: Hazardous Materials Identification System (USA) VOC: Volatile Organic Compounds (USA, EU) LC50: Lethal concentration, 50 percent LD50: Lethal dose, 50 percent PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative NIOSH: National Institute for Occupational Safety OSHA: Occupational Safety & Health TLV: Threshold Limit Value PEL: Permissible Exposure Limit REL: Recommended Exposure Limit Flam. Liq. 2: Flammable liquids - Category 2 Acute Tox. 4: Acute toxicity - Category 4 \* \* Data compared to the previous version altered.

