SAFETY DATA SHEET



ICP/MS Tuning Solution 10ug/L

Section 1. Identification

1.1 Product identifier

Product name : ICP/MS Tuning Solution 10ug/L

Part no. : 5184-3566 **Validation date** : 5/31/2024

1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified uses : Reagents and Standards for Analytical Chemistry Laboratory Use

A set of 2 x 500 mL

1.3 Details of the supplier of the safety data sheet

Supplier/Manufacturer: Agilent Technologies, Inc.

5301 Stevens Creek Blvd Santa Clara, CA 95051, USA

800-227-9770

1.4 Emergency telephone number

In case of emergency : CHEMTREC®: 1-800-424-9300

Section 2. Hazards identification

2.1 Classification of the substance or mixture

OSHA/HCS status : This material is considered hazardous by the OSHA Hazard Communication Standard

(29 CFR 1910.1200).

Classification of the substance or mixture

₱290CORROSIVE TO METALS - Category 1H315SKIN IRRITATION - Category 2H318SERIOUS EYE DAMAGE - Category 1

2.2 GHS label elements

Hazard pictograms :



Signal word : Danger

Hazard statements : H290 - May be corrosive to metals.

H315 - Causes skin irritation.

H318 - Causes serious eye damage.

Precautionary statements

Prevention: P280 - Wear protective gloves. Wear eye or face protection.

P234 - Keep only in original packaging. P264 - Wash thoroughly after handling.

Response : P390 - Absorb spillage to prevent material damage.

P362 + P364 - Take off contaminated clothing and wash it before reuse.

P302 + P352 - IF ON SKIN: Wash with plenty of water.

P305 + P351 + P338, P310 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Immediately call a POISON CENTER or doctor.

Storage : Not applicable.

Date of issue: 05/31/2024 **1/13**

CP/MS Tuning Solution 10ug/L

Section 2. Hazards identification

Disposal

: Not applicable.

Supplemental label elements

: Keep container tightly closed. Do not breathe vapor or spray. Use only with adequate

2.3 Other hazards

Hazards not otherwise classified

: Causes respiratory tract burns.

Section 3. Composition/information on ingredients

Substance/mixture : Mixture

Ingredient name	%	CAS number
ntric acid	≤3	7697-37-2

Any concentration shown as a range is to protect confidentiality or is due to batch variation.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

Section 4. First aid measures

4.1 Description of necessary first aid measures

Eye contact

: Get medical attention immediately. Call a poison center or physician. Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Chemical burns must be treated promptly by a physician.

Inhalation

: Get medical attention immediately. Call a poison center or physician. Remove victim to fresh air and keep at rest in a position comfortable for breathing. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband. In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.

Skin contact

: Get medical attention immediately. Call a poison center or physician. Wash contaminated skin with soap and water. Remove contaminated clothing and shoes. Wash contaminated clothing thoroughly with water before removing it, or wear gloves. Continue to rinse for at least 10 minutes. Chemical burns must be treated promptly by a physician. Wash clothing before reuse. Clean shoes thoroughly before reuse.

Ingestion

: Get medical attention immediately. Call a poison center or physician. Wash out mouth with water. Remove dentures if any. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Chemical burns must be treated promptly by a physician. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

4.2 Most important symptoms/effects, acute and delayed

Potential acute health effects

Eye contact : Causes serious eye damage.

Date of issue: 05/31/2024 **2/13**

Section 4. First aid measures

Inhalation : Corrosive to the respiratory system.

Skin contact : Causes skin irritation.

Ingestion: May cause burns to mouth, throat and stomach.

Over-exposure signs/symptoms

Eye contact : Adverse symptoms may include the following:

pain watering redness

Inhalation : Adverse symptoms may include the following:

respiratory tract irritation

coughing

Skin contact: Adverse symptoms may include the following:

pain or irritation

redness

blistering may occur

Ingestion: Adverse symptoms may include the following:

stomach pains

4.3 Indication of immediate medical attention and special treatment needed, if necessary

Notes to physician : In case of inhalation of decomposition products in a fire, symptoms may be delayed.

The exposed person may need to be kept under medical surveillance for 48 hours.

Specific treatments: No specific treatment.

Protection of first-aiders : No action shall be taken involving any personal risk or without suitable training. If it is

suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water

before removing it, or wear gloves.

See toxicological information (Section 11)

Section 5. Fire-fighting measures

5.1 Extinguishing media

Suitable extinguishing media

: Use an extinguishing agent suitable for the surrounding fire.

Unsuitable extinguishing

media

: None known.

5.2 Special hazards arising from the substance or mixture

Specific hazards arising from the chemical

: In a fire or if heated, a pressure increase will occur and the container may burst.

Hazardous thermal decomposition products

: Decomposition products may include the following materials:

nitrogen oxides

5.3 Advice for firefighters

Special protective actions for fire-fighters

: Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.

Special protective : F

equipment for fire-fighters

: Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

Date of issue: 05/31/2024 3/13

Section 6. Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

: No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Do not breathe vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.

For emergency responders:

If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

6.2 Environmental precautions

: Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

6.3 Methods and materials for containment and cleaning up

Methods for cleaning up

: Stop leak if without risk. Move containers from spill area. The spilled material may be neutralized with sodium carbonate, sodium bicarbonate or sodium hydroxide. Absorb spillage to prevent material damage. Dispose of via a licensed waste disposal contractor.

Section 7. Handling and storage

7.1 Precautions for safe handling

Protective measures

: Put on appropriate personal protective equipment (see Section 8). Do not get in eyes or on skin or clothing. Do not breathe vapor or mist. Do not ingest. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Keep away from alkalis. Empty containers retain product residue and can be hazardous. Do not reuse container. Absorb spillage to prevent material damage.

Advice on general occupational hygiene

: Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

7.2 Conditions for safe storage, including any incompatibilities

: Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store in a corrosion resistant container with a resistant inner liner. Store locked up. Separate from alkalis. Keep away from metals. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

7.3 Specific end use(s)

Recommendations

: Industrial applications, Professional applications.

Industrial sector specific

: Not available.

solutions

Date of issue: 05/31/2024 **4/13**

Section 8. Exposure controls/personal protection

8.1 Control parameters

Occupational exposure limits

Ingredient name	Exposure limits
ingredient name intric acid	ACGIH TLV (United States, 1/2024). TWA: 2 ppm 8 hours. TWA: 5.2 mg/m³ 8 hours. STEL: 4 ppm 15 minutes. STEL: 10 mg/m³ 15 minutes. OSHA PEL 1989 (United States, 3/1989). TWA: 2 ppm 8 hours. TWA: 5 mg/m³ 8 hours. STEL: 4 ppm 15 minutes. STEL: 10 mg/m³ 15 minutes. NIOSH REL (United States, 10/2020). TWA: 2 ppm 10 hours. TWA: 5 mg/m³ 10 hours. STEL: 4 ppm 15 minutes. STEL: 10 mg/m³ 15 minutes. STEL: 10 mg/m³ 15 minutes. CSHA PEL (United States, 5/2018). TWA: 2 ppm 8 hours. TWA: 5 mg/m³ 8 hours. CAL OSHA PEL (United States, 5/2018).

Biological exposure indices

No exposure indices known.

8.2 Exposure controls

Appropriate engineering controls

: Use only with adequate ventilation. If user operations generate dust, fumes, gas, vapor or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits.

Environmental exposure controls

: Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

Individual protection measures

Hygiene measures

: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period.

Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

Eye/face protection

: Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: chemical splash goggles and/ or face shield. If inhalation hazards exist, a full-face respirator may be required instead.

Skin protection

Date of issue: 05/31/2024 5/13

Section 8. Exposure controls/personal protection

Hand protection

: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.

Body protection

: Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Other skin protection

: Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Respiratory protection

: Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use.

Section 9. Physical and chemical properties and safety characteristics

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

<u>Appearance</u>

Physical state : Liquid.

Color : Colorless to light yellow.

Odor threshold : Odorless.

Not available.

pH : 1

Melting point/freezing point : 0°C (32°F)

Boiling point, initial boiling : 100°C (212°F)

point, and boiling range

Flash point : Not available.

Evaporation rate : >1 (butyl acetate = 1)

Flammability : Not applicable.

Lower and upper explosion : Not available.

limit/flammability limit

Vapor pressure

	Vapor Pressure at 20°C			Vapor pressure at 50°C		
Ingredient name	mm Hg	kPa	Method	mm Hg	kPa	Method
ntric acid	48.0039	6.4	-	-	-	-
water	17.5	2.3	-	92.258	12.3	-

Relative vapor density: Not available.

Relative density : 1.008

Density : 1.008 g/cm³

Solubility(ies) :	Media	Result
	water	Soluble

Miscible with water : Yes.

Partition coefficient: n-

octanol/water

Auto-ignition temperature : Not available.

: Not applicable.

Date of issue: 05/31/2024 6/13

P/MS Tuning Solution 10ug/L

Section 9. Physical and chemical properties and safety characteristics

Decomposition temperature : Not available. **Viscosity** : Not available.

Particle characteristics

Median particle size : Not applicable.

Section 10. Stability and reactivity

10.1 Reactivity : No specific test data related to reactivity available for this product or its ingredients.

10.2 Chemical stability : The product is stable.

10.3 Possibility of hazardous reactions

: Under normal conditions of storage and use, hazardous reactions will not occur.

10.4 Conditions to avoid : No specific data.

10.5 Incompatible materials : Attacks many metals producing extremely flammable hydrogen gas which can form

explosive mixtures with air.

Reactive or incompatible with the following materials:

alkalis metals

Reactive or incompatible with the following materials: oxidizing materials.

10.6 Hazardous decomposition products

: Under normal conditions of storage and use, hazardous decomposition products should not be produced.

Section 11. Toxicological information

11.1 Information on toxicological effects

Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
	LC50 Inhalation Vapor LC50 Inhalation Vapor		2500 ppm 130 mg/m³	1 hours 4 hours

Irritation/Corrosion

Not available.

Sensitization

Not available.

Mutagenicity

Conclusion/Summary: Not available.

Carcinogenicity

Conclusion/Summary: Not available.

Reproductive toxicity

Conclusion/Summary: Not available.

Teratogenicity

Conclusion/Summary: Not available.

Specific target organ toxicity (single exposure)

Not available.

Specific target organ toxicity (repeated exposure)

Not available.

Date of issue: 05/31/2024 7/13

Section 11. Toxicological information

Aspiration hazard

Not available.

Information on the likely

routes of exposure

: Routes of entry anticipated: Oral, Dermal, Inhalation, Eyes.

Potential acute health effects

Eye contact : Causes serious eye damage.

Inhalation : Corrosive to the respiratory system.

Skin contact: Causes skin irritation.

Ingestion: May cause burns to mouth, throat and stomach.

Symptoms related to the physical, chemical and toxicological characteristics

Eye contact : Adverse symptoms may include the following:

pain watering redness

Inhalation : Adverse symptoms may include the following:

respiratory tract irritation

coughing

Skin contact: Adverse symptoms may include the following:

pain or irritation

redness

blistering may occur

Ingestion : Adverse symptoms may include the following:

stomach pains

Delayed and immediate effects and also chronic effects from short and long term exposure

Short term exposure

Potential immediate

: Not available.

effects

Potential delayed effects : Not available.

Long term exposure

Potential immediate : Not available.

effects

Potential delayed effects: Not available.

Potential chronic health effects

General : No known significant effects or critical hazards.
 Carcinogenicity : No known significant effects or critical hazards.
 Mutagenicity : No known significant effects or critical hazards.
 Reproductive toxicity : No known significant effects or critical hazards.

Numerical measures of toxicity

Acute toxicity estimates

Product/ingredient name	(3	 Inhalation (gases) (ppm)	(vapors)	Inhalation (dusts and mists) (mg/ I)
j, 3	N/A N/A	N/A N/A	132.5 2.65	80.6 1.61125

Date of issue: 05/31/2024 **8/13**

Section 11. Toxicological information

Section 12. Ecological information

12.1 Toxicity

Product/ingredient name	Result	Species	Exposure
mtric acid	Acute LC50 180000 μg/l Marine water	Crustaceans - Carcinus maenas - Adult	48 hours

12.2 Persistence and degradability

Product/ingredient name	Aquatic half-life	Photolysis	Biodegradability
ntric acid	-	-	Readily

12.3 Bioaccumulative potential

Product/ingredient name	LogPow	BCF	Potential
ntric acid	-0.21	-	Low

12.4 Mobility in soil

Soil/water partition coefficient (K_{oc})

: Not available.

12.5 Other adverse effects

: No known significant effects or critical hazards.

Section 13. Disposal considerations

13.1 Waste treatment methods

Disposal methods

: The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

Disposal should be in accordance with applicable regional, national and local laws and regulations. Local regulations may be more stringent than regional or national requirements.

The information presented below only applies to the material as supplied. The identification based on characteristic(s) or listing may not apply if the material has been used or otherwise contaminated. It is the responsibility of the waste generator to determine the toxicity and physical properties of the material generated to determine the proper waste identification and disposal methods in compliance with applicable regulations.

Refer to Section 7: HANDLING AND STORAGE and Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION for additional handling information and protection of employees.

Date of issue: 05/31/2024 9/13

Section 14. Transport information

	DOT Classification	TDG Classification	Mexico Classification	IMDG	IATA
UN number	UN3264	UN3264	UN3264	UN3264	UN3264
UN proper shipping name	Corrosive liquid, acidic, inorganic, n. o.s. (nitric acid, solution)	CORROSIVE LIQUID, ACIDIC, INORGANIC, N.O. S. (nitric acid, solution)	LIQUIDO CORROSIVO, ACIDO, INORGANICO, N. E.P. (Contains Nitric acid)	CORROSIVE LIQUID, ACIDIC, INORGANIC, N.O. S. (nitric acid, solution)	Corrosive liquid, acidic, inorganic, n. o.s. (nitric acid, solution)
Transport hazard class(es)	8	8	8	8	8
Packing group	III	III	III	III	III
Environmental hazards	No.	No.	No.	No.	No.

Additional information

DOT Classification

: Reportable quantity 50000 lbs / 22700 kg [5949.1 gal / 22519.8 L]. Package sizes shipped in quantities less than the product reportable quantity are not subject to the RQ (reportable quantity) transportation requirements.

Limited quantity Yes.

Packaging instruction Exceptions: 154. Non-bulk: 203. Bulk: 241. Quantity limitation Passenger aircraft/rail: 5 L. Cargo aircraft: 60 L.

Special provisions IB3, T7, TP1, TP28

TDG Classification

: Product classified as per the following sections of the Transportation of Dangerous

Goods Regulations: 2.40-2.42 (Class 8).

Explosive Limit and Limited Quantity Index 5 Passenger Carrying Road or Rail Index 5

Special provisions 16

Mexico Classification

IMDG

: Special provisions 223, 274

: **Emergency schedules** F-A, S-B

Special provisions 223, 274

IATA : Quantity limitation Passenger and Cargo Aircraft: 5 L. Packaging instructions: 852. Cargo Aircraft Only: 60 L. Packaging instructions: 856. Limited Quantities - Passenger

Aircraft: 1 L. Packaging instructions: Y841.

Special provisions A3, A803

Special precautions for user : Transport within user's premises: always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

Transport in bulk according : Not available. to IMO instruments

Date of issue: 05/31/2024 10/13

Section 15. Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

U.S. Federal regulations : TSCA 8(a) CDR Exempt/Partial exemption: Not determined

> Clean Water Act (CWA) 307: Thallium nitrate Clean Water Act (CWA) 311: nitric acid

Clean Air Act (CAA) 112 regulated toxic substances: nitric acid

Clean Air Act Section 112

(b) Hazardous Air **Pollutants (HAPs)** : Listed

Clean Air Act Section 602

Class I Substances

: Not listed

Clean Air Act Section 602

Class II Substances

: Not listed

DEA List I Chemicals

: Not listed

(Precursor Chemicals)

: Not listed

DEA List II Chemicals

(Essential Chemicals)

SARA 302/304

Composition/information on ingredients

			SARA 302 1	TPQ	SARA 304 F	RQ
Name	%	EHS	(lbs)	(gallons)	(lbs)	(gallons)
ntric acid	≤3	Yes.	1000	85.7	1000	85.7

SARA 304 RQ : 50000 lbs / 22700 kg [5949.1 gal / 22519.8 L]

SARA 311/312

Classification : CORROSIVE TO METALS - Category 1

> SKIN IRRITATION - Category 2 SERIOUS EYE DAMAGE - Category 1 HNOC - Corrosive to respiratory tract

Composition/information on ingredients

Name	%	Classification
ntric acid		OXIDIZING LIQUIDS - Category 3 CORROSIVE TO METALS - Category 1 ACUTE TOXICITY (inhalation) - Category 3 SKIN CORROSION - Category 1A SERIOUS EYE DAMAGE - Category 1 HNOC - Corrosive to digestive tract HNOC - Corrosive to respiratory tract

SARA 313

	Product name	CAS number	%
Form R - Reporting requirements	mitric acid	7697-37-2	≤3
Supplier notification	mitric acid	7697-37-2	≤3

SARA 313 notifications must not be detached from the SDS and any copying and redistribution of the SDS shall include copying and redistribution of the notice attached to copies of the SDS subsequently redistributed.

State regulations

Massachusetts : The following components are listed: NITRIC ACID **New York** : The following components are listed: Nitric acid **New Jersey** : The following components are listed: NITRIC ACID

05/31/2024 Date of issue: 11/13

Section 15. Regulatory information

Pennsylvania : The following components are listed: NITRIC ACID

California Prop. 65

MARNING: This product can expose you to Cobalt metal powder, which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov.

Ingredient name		Maximum acceptable dosage level
Cobalt metal powder	-	-

International regulations

Chemical Weapon Convention List Schedules I, II & III Chemicals

Not listed.

Montreal Protocol

Not listed.

Stockholm Convention on Persistent Organic Pollutants

Not listed.

Rotterdam Convention on Prior Informed Consent (PIC)

Not listed.

UNECE Aarhus Protocol on POPs and Heavy Metals

Not listed.

Inventory list

Australia : Not determined.

Canada : At least one component is not listed in DSL but all such components are listed in NDSL.

China : All components are listed or exempted. **Japan** : Japan inventory (CSCL): Not determined.

Japan inventory (ISHL): All components are listed or exempted.

New Zealand All components are listed or exempted. **Philippines** : All components are listed or exempted. Republic of Korea : All components are listed or exempted. : All components are listed or exempted. **Taiwan**

Thailand : Not determined. **Turkey** Not determined.

United States : All components are active or exempted. **Viet Nam** : All components are listed or exempted.

: 05/31/2024

: 10/26/2022

Section 16. Other information

Procedure used to derive the classification

Classification	Justification
ORROSIVE TO METALS - Category 1	Expert judgment
SKIN IRRITATION - Category 2	Expert judgment
SERIOUS EYE DAMAGE - Category 1	On basis of test data

History

Date of issue/Date of

Date of previous issue

revision

Date of issue: 05/31/2024 12/13

Section 16. Other information

Version

: 9

Key to abbreviations

: ATE = Acute Toxicity Estimate

BCF = Bioconcentration Factor

GHS = Globally Harmonized System of Classification and Labelling of Chemicals

IATA = International Air Transport Association

IBC = Intermediate Bulk Container

IMDG = International Maritime Dangerous Goods

LogPow = logarithm of the octanol/water partition coefficient

MARPOL = International Convention for the Prevention of Pollution From Ships, 1973

as modified by the Protocol of 1978. ("Marpol" = marine pollution)

N/A = Not available
UN = United Nations

▼ Indicates information that has changed from previously issued version.

Notice to reader

Disclaimer: The information contained in this document is based on Agilent's state of knowledge at the time of preparation. No warranty as to its accurateness, completeness or suitability for a particular purpose is expressed or implied.

Date of issue: 05/31/2024 **13/13**